



LED Post Top Light Multi Wattage Multi CCT



FEATURES

- IP65 rated
- Type 5 lens
- Rust & corrosion proof
- 50,000 hours lifetime

APPLICATIONS

- Area lighting
- Auto dealerships
- High masts
- Housing complexes
- Shopping malls
- Parks and recreational areas
- Parking lots and decks



CONSTRUCTION Polyester powder-coated finish.	CONTROLS AND DIMMING 0-10V dimming standard.
OPTICAL SYSTEM Lumileds LUXEON 3030 2D LED chips. 120° beam angle.	INSTALLATION AND MOUNTING Pole mounting. Suitable for 3" pole.
ELECTRICAL 120-277V input. -20°C to 50°C (-4°F to 122°F).	WARRANTY 5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

OPTIONAL ACCESSORIES



Microwave Sensor
120-MWS-MW-ACYG1
Compatible with 120-RCU-G1 White



Microwave Bluetooth Sensor
120-MWS-BT-ACYG1
Compatible with App



PIR Sensor
120-PIR-ACYG1
Compatible with 120-RCU-G1 White



PIR Bluetooth Sensor
120-PIR-BT-ACYG1
Compatible with App



Remote Control
120-RCU-ACYG1-White



Photocell / Daylight Sensor
120-PCU-DS-226
Not Compatible with Remote Control 120-RCU-100



Motion Sensor
120-MSU-BM-ANT54T
Compatible with 120-RCU-100



Remote Control
120-RCU-100



LED Post Top Light Multi Wattage Multi CCT

Part Number 120-PTXX-150-50-27-DIM

WATTAGE SELECTABLE	CCT SELECTABLE	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
60W	3000K/4000K/5000K	8,251.8LM	137.53lm/W	120-277V	71	.974	8%	50-100W HID
80W	3000K/4000K/5000K	11,001.4LM	137.53lm/W	120-277V	71	.974	8%	50-100W HID
100W	3000K/4000K/5000K	13,753LM	137.53lm/W	120-277V	71	.974	8%	50-100W HID
150W	3000K/4000K/5000K	20,897LM	137.53lm/W	120-277V	71	.974	8%	50-100W HID

PRODUCT DIMENSIONS

