



LED Wall Pack Multi Wattage CCT 5000K



20W / 25W / 40W / 60W



60W / 80W / 100W / 120W



Quick Mount Back Plate (included)

FEATURES

- IP65 rated
- Photocell included
- Semi cut-off
- Corrosion and rust proof
- 50,000 hours lifetime

APPLICATIONS

- Auto Dealerships
- Commercial/Industrial
- Factories
- Parking Lots
- Shopping Malls
- Supermarkets
- Warehouses
- Logistic Centers



CONSTRUCTION	CONTROLS AND DIMMING
Heavy die-cast aluminum alloy housing with bronze powder-coated finish. Glass lens.	0-10V dimming. Photocell included.
OPTICAL SYSTEM	INSTALLATION AND MOUNTING
Lumileds LUXEON 3030 2D LED chips. High quality tempered glass optics. 120° beam angle.	Wall mount with quick mount back plate for easy installation.
ELECTRICAL	WARRANTY
120-277V input. -40°C to 40°C (-40°F to 104°F).	5-year limited warranty. Actual performance may differ as a result of end-user environment and application.

OPTIONAL ACCESSORIES



Emergency Back-up Driver
120-EMBU-15W-050



Cut-off Shield
120-SH-WP-CO



Wire Guard
120-SH-WP-WR



LED Wall Pack Multi Wattage CCT 5000K

Part Number 120-WPX-T60-50-DIM

WATTAGE SELECTABLE	CCT	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
20W	5000K	2,700LM	135lm/W	120-277V	70	.9	20%	70W-150W HID
25W	5000K	3,375LM	135lm/W	120-277V	70	.9	20%	70W-150W HID
40W	5000K	5,400LM	135lm/W	120-277V	70	.9	20%	175W-250W HID
60W	5000K	8,100LM	135lm/W	120-277V	70	.9	20%	175W-250W HID

Part Number 120-WPX-T120-50-DIM

WATTAGE SELECTABLE	CCT	LUMENS	EFFICACY	VOLTAGE	CRI	POWER FACTOR	THD	REPLACES
60W	5000K	8,286LM	138.1lm/W	120-277V	74	.967	20%	175W-250W HID
80W	5000K	11,048LM	138.1lm/W	120-277V	74	.967	20%	175W-250W HID
100W	5000K	13,810LM	138.1lm/W	120-277V	74	.967	20%	320W-400W HID
120W	5000K	16,572LM	138.1lm/W	120-277V	74	.967	20%	320W-400W HID

PRODUCT DIMENSIONS

