



### APU SC10-6 Series (large)

<b>Portable</b>	Yes
<b>Frame</b>	Stainless steel
<b>Pressure gauge</b>	Glycerine filled
<b>Reduction unit air control</b>	Easy control of outgoing pressure
<b>Ratio</b>	5:1 t/m 740:1
<b>Max working pressure</b>	35 bar t/m 4480 bar
<b>Volume per stroke</b>	9290 t/m 2 cc
<b>Flow rate</b>	65 t/m 0,48 l/min

### Options:

<b>Portable</b>	Extra handles
	Wheels
<b>Test certificate</b>	Option
<b>Digital display</b>	Option
<b>Pressure transmitter</b>	Option

Model	Ratio	Maximum working pressure		Volume per stroke		Flow rate	
		Bar	PSI	Cc	in <sup>3</sup>	l/min	US gpm
<b>APU SC10-6-5</b>	5:10	35	464	290	17.7	65	17.17
<b>APU SC10-6-10</b>	10:1	70	1015	145.85	9.9	35	9.25
<b>APU SC10-6-20</b>	20:1	140	2030	66.37	4.05	16	4.23
<b>APU SC10-6-25</b>	25:1	175	2610	55.38	3.38	13	3.43
<b>APU SC10-6-35</b>	35:1	245	3553	40.8	2.49	11	2.91
<b>APU SC10-6-55</b>	55:1	385	5583	24.85	1.5	6.25	1.65
<b>APU SC10-6-95</b>	95:1	665	9700	15.2	0.928	3.8	1
<b>APU SC10-6-145</b>	145:1	1015	14721	10.21	0.623	2.7	0.71
<b>APU SC10-6-180</b>	180:1	1260	18274	8.02	0.49	2.1	0.55
<b>APU SC10-6-240</b>	240:1	1680	24366	6.14	0.375	1.6	0.42
<b>APU SC10-6-330</b>	330:1	2310	33503	4.5	0.275	1.1	0.29
<b>APU SC10-6-460</b>	460:1	3220	46702	3.16	0.193	0.75	0.2
<b>APU SC10-6-740</b>	740:1	4480	65000	2	0.123	0.48	0.13