

## STAR HEADLIGHT & LANTERN CO.




DLQS-4



## **Specifications and Features**

- Weatherproof interior or exterior mount
- 34 customer selectable warning flash patterns plus 5 phase options
- Twelve traffic director patterns (6 and 8 head versions only)
- DLQS-4 comes with a 2' three-wire cable (power, ground, pattern select)
- DLQS-6 (8) comes with a 25' six wire cable, (power, ground, program wire, left enable, right enable, warn enable, center-out = L + R)
- Bottom and rear T-slots allow for easy mounting via industry standard #10 carriage bolt
- Front load assembly design allows quick and easy swap of heads
- Built-in Traffic Director function available (six head and eight head models only)
- Sealed DLITS or DLITE heads for maximum reliability
- · Shipped standard with L-brackets
- Dual Warn option (8 head module only):
   Programmable to allow the end heads to flash a warning pattern, while the center 6 heads flash a traffic director pattern


- Ideal for front push bumpers, rear SUV window or pickup trucks, headache rack, and running board lights
- Dimensions: (DLQS-4) 20 ½" L x 1 ½" W x 1 ¾16" H (DLQS-6) 30 ¾4" L x 1 ½32" W x 1 ¾16" H (DLQS-8) 40 ¾464" L x 1 ½32" W x 1 ¾16" H
- Voltage: 10-16V DC
- Amp draw: 2 amps average (4 head)
  3 amps average (6 head) 4 amps average (8 head)
- Color combinations:
- Approvals: SAE Class I (A,B,C,R DLITS only)



## **Model Numbers/Descriptions:**

DLQS-4	Four LED heads
DLQS-6	Six LED heads, with traffic director function
DLQS-8	Eight LED heads, with traffic director function





SF190 Rev - 6-27-2017





Star Headlight & Lantern Co., Inc.

455 Rochester Street Avon, NY 14414 Phone: 585-226-9500 Fax: 888-478-2797 starheadlight.com





PROUDLY MADE IN THE U.S.A.

An ISO 9001:2008 Certified Company