

# ***indespension***

## ***Trailer Catalogue***



***Camping & Utility Trailers / Car Transporters / Commercial Goods Trailers /  
Flatbed Trailers / Livestock Trailers / Marine Trailers / Motorcycle Trailers /  
Plant Trailers / Tipper Trailers / Tow-A-Van Box Trailers***

***Call your nearest Branch with any trailer enquiries 0845 3 720 720***

***[indespension.co.uk](http://indespension.co.uk)***

# indespension

## GT Goods Trailer

Goods trailers in the GT range from Indespension are versatile, robust and have fixed side panels allowing them to transport a wide range of materials, equipment and machinery. They are constructed with SuperRide™ rubber torsion suspension as standard, enabling stable towing even when empty.



		GT13064	GT13084	GT26084	GT26085	GT26106	GT26106	GT26126
<b>Gross Weight</b>	<b>KG</b>	1300	1300	2700	2700	2700	2700	2700
<b>Unladen Weight</b>	<b>KG</b>	332	364	490	545	595	610	640
<b>Payload</b>	<b>KG</b>	968	963	2210	2195	2105	2090	2060
<b>Internal Dimensions</b>	<b>ft x ins</b>	6' X 4'1"	8'3" X 4'1"	8'3" X 4'1"	8'3" X 5'1"	10' X 5'1"	10' X 5'8"	10' X 5'8"
<b>Number of Axles</b>		1	1	2	2	2	2	2

### Options

Ladder rack, Spare wheel including carrier, Mesh kits for ramptail, Ramptail / Extended ramptail, Additional deck rings, Aluminium treadplate floor, Internal tie down points

## SE Goods Trailer

Whilst goods trailers in the SE range from Indespension are lightweight, they are robust and adaptable for bulk loads and machinery making them popular with builders and landscape gardeners alike. With a wide range of options available, they are configurable to meet your exact requirements.

Innovation is at the heart of the SE range; advanced suspension technology ensures that whilst the trailers have cutting edge features to enhance their safety characteristics, the towing experience is refined, smooth and efficient. Optional features such as user-friendly loading ramps and secure tie down points make using the trailers simple but effective.



		SE07064	SE07064R	SE07084	SE07084R	SE07085R
<b>Gross Weight</b>	<b>KG</b>	750	750	750	750	750
<b>Unladen Weight</b>	<b>KG</b>	185	195	200	210	220
<b>Payload</b>	<b>KG</b>	565	555	550	540	530
<b>Internal Dimensions</b>	<b>ft x ins</b>	6'6" X 4'	6'6" X 4'	8' X 4'	8' X 4'	8' X 5'
<b>Tyre Size</b>		Balloon 20.5 x 8-10	Balloon 20.5 x 8-10	Balloon 20.5 x 8-10	Balloon 20.5 x 8-10	Balloon 20.5 x 8-10

### Options

- **Ladder Rack** - Provides extra stability when transporting equipment.
- **Prop Stands x2** - Ensure stable foundation for your load.
- **Mesh Kits for Ramptail** - Added flexibility allowing you to expand your cargo options.
- **Ramptail exc. Prop Stands** - Simplifying the loading process.
- **Spare Wheel Including Carrier** - You'll never be left stranded without a spare wheel.
- **Triplelock™ High Security Coupling** - Protect against any potential threats.





# indespension Plant Trailer

Indespension trailers are the number one choice for all your plant needs. From the industry leading AD range including the super lightweight Alumax, to our Beavertail, there is a trailer that will meet all your demanding requirements.



### Designed with Precision:

Crafted with meticulous attention to detail, our Plant Trailers are a fusion of cutting-edge engineering and practical innovation. Each trailer is designed to accommodate various sizes and types of machinery, from excavators to loaders. With a focus on stability, safety and ease of use, our trailers ensure a seamless loading, transport and unloading experience.

### Strength Meets Durability:

Built with the top industry grade materials, Indespension Plant Trailers have exceptional strength and durability. These trailers are engineered to withstand rigorous demanding work environments, providing peace of mind that your valuable equipment will reach its destination safely.

## CHALLENGER 50 BEAVERTAIL

		Challenger 50 Beavertail Range		
		AD27094BTS	AD3510BTS	AD35126BTS
<b>Gross Weight</b>	<b>KG</b>	2700	3500	3500
<b>Unladen Weight</b>	<b>KG</b>	570	745	815
<b>Payload</b>	<b>KG</b>	2130	2755	2685
<b>Internal Dimensions LxWxH</b>	<b>ft x ins</b>	9'1" x 4'1"	10' x 5'6"	12' x 6'
<b>Studding</b>		5 X M16 ON 165.1MM PCD	5 X M16 ON 165.1MM PCD	5 X M16 ON 165.1MM PCD
<b>Tyre Size</b>		165 R13C	185/70 R13C	185/70 R13C



## AD Range



		AD RANGE		
		AD2000	AD2800SPLED	ALUMAX
<b>Gross Weight</b>	<b>KG</b>	2700	3500	3500
<b>Unladen Weight</b>	<b>KG</b>	540	760	590
<b>Payload</b>	<b>KG</b>	2160	2740	2910
<b>Internal Dimensions LxWxH</b>	<b>ft x ins</b>	8'2" x 4'1½"	10'1" x 5'11"	10' x 5'7"
<b>Studding</b>		5 X M16 ON 165.1MM PCD	5 X M16 ON 165.1MM PCD	5 X M16 ON 165.1MM PCD
<b>Tyre Size</b>		165 R13C	185/70 R13C	185/70 R13C

### Options

Spare Wheel, Additional Deck Rings, Locking Head, Bag of Ratchet Straps.

# Indespension Autoclamp™ Range



## Key Features

- The Autoclamp™ transporter system is fully patented and exclusive to Indespension.
- The excavator is fully clamped in four positions; a big advantage over other strapless trailers.
- The front clamp is self-adjusting, unlike other strapless trailers, which must be initially set-to-suit and altered when changing excavator.
- Auto adjusting brakes, Sealed for life bearing (SFL) and large PCD all as standard, providing exceptional wheel security.
- Its boom lock/dipper arm has a multi selection function to provide quick location and added security.
- Its ramps are swaged steel, which increases durability and offers greater grip.

## Autoclamp™ Trailer

The Autoclamp™ trailer can carry all popular sizes of 1.5 Tonne excavator.

Its automatic clamping system self-adjusts according to different track heights and adjusts automatically as the rubber excavator tracks degrade. The clamping system operates as the excavator drives into the clamping mechanism, locking into place on the tracks.

When unloading the machine, the clamping system automatically releases and resets ready for the load. The biggest advantage to the Autoclamp™ trailer is that no tools or straps are required to secure the excavator for transit.

The Autoclamp™ trailer is also fitted with a bucket and boom rest, which is fastened with a securing pin. The Autoclamp™ makes transporting mini excavators and mini diggers easy and simple.

	Autoclamp
<b>Gross Weight (KG)</b>	2700
<b>Carry Weight (KG)</b>	2000
<b>Overall Dimensions</b>	W 1805mm L 4795mm H 1800mm
<b>Ramps Style</b>	Swaged Steel Split Ramps w/ bolt on knees
<b>Wheel &amp; Tyres Size</b>	165R13 5 x M16 on 165.1mmPCD

## Autoclamp™ Utility Trailer

	Autoclamp Utility
<b>Gross Weight (KG)</b>	3500
<b>Carry Weight (KG)</b>	2520
<b>Overall Dimensions</b>	W 2305mm L 5070mm H 1720mm
<b>Ramps Style</b>	Swaged Steel Split Ramps w/ bolt on knees
<b>Storage Facility</b>	Up to 16 Chapter Barriers Up to 18 Cones Up to 6-8 Road Signs



## Key Features

- Patented carrier cages for Chapter 8 barriers.
- Adjustable coupling height.
- Side channel storage for sandbags & barrier posts etc.
- Patented adjustable 4 point AutoClamp™ system.
- The boom/ dipper arm has a multi select function to provide good security and quick location.
- Auto adjusting brakes, Sealed for life bearing (SFL) and large PCD all as standard, providing exceptional wheel security.
- Pecker location bracket [+2 KG to trailer weight].

## Optional Extras

- 50mm Coupling Head.
- TripleLock™ Coupling Head.
- 30mm, 40mm & Nato Towing Eyes.
- Spare Wheel [loose].

## Autoclamp™ Compact Utility Trailer

	Autoclamp Compact
<b>Gross Weight (KG)</b>	3500
<b>Carry Weight (KG)</b>	2582
<b>Overall Dimensions</b>	W 2030mm L 5070mm H 1720mm
<b>Ramps Style</b>	Swaged steel split Ramps w/ bolt on knees
<b>Storage Facility</b>	Up to 12 Chapter Barriers Up to 18 Cones Up to 6-8 Road Signs

The Autoclamp™ Compact Utility offers the capacity to transport all your equipment in one load. By carrying all your equipment at once, you will improve work efficiency and achieve a quick return on investment.



# indespension Flatbed Trailer



The adaptable indespension flatbed trailer is engineered to be the best in class for transporting general goods, materials and machinery and is designed with your convenience in mind. The optional side panels are fitted for removed in seconds, and you can choose between the resilient strength of phenolic flooring or the clean lines of lightweight Aluminium. Enhanced with brushed spring hangers, a seamlessly welded drawbar and a seven-leaf suspension system; they are built to last. The convenience of underfloor ramp storage and the advantage of low-profile wheels ensure that you will not be disappointed.

### Options:

- Ladder Rack.
- Deck Rings.
- Mesh Kit.
- Fitted Spare Wheel.
- Winch Post Including Winch & Strap.
- Drop Sides including Head Board.
- Head Board Only.
- Aluminium Floor Option.
- 6' Spring Ramp.
- 8' Steel Ramp (Including Propstands).
- 8' Aluminium Ramp (Including Propstands).



		<b>FTL27105</b>	<b>FTL35106</b>	<b>FTL35126</b>	<b>FTL35146</b>	<b>FTL35146TRI</b>	<b>FTL35166</b>	<b>FTL35166TRI</b>
<b>Gross Weight</b>	<b>KG</b>	2700	3500	3500	3500	3500	3500	3500
<b>Unladen Weight</b>	<b>KG</b>	587	680	712	749	849	791	891
<b>Payload</b>	<b>KG</b>	2113	2820	2788	2751	2651	2709	2609
<b>Internal Dimensions LxWxH</b>	<b>M ft x ins</b>	3.0 X 1.62 9'10" X 5'4"	3.0 X 1.92 9'10" X 6'3½"	3.61 X 1.92 11'10" X 6'3½"	4.22 X 1.92 13'10" X 6'3½"	4.22 X 1.92 13'10" X 6'3½"	4.83 X 1.92 15'10" X 6'3½"	4.83 X 1.92 15'10" X 6'3½"
<b>Axles</b>		2	2	2	2	3	2	3
<b>Tyre Size</b>		195/50 R13	195/50 R13	195/50 R13	195/50 R13	195/50 R13	195/50 R13	195/50 R13

# indespension U-Tilt Trailer



The U-Tilt trailer combines the versatility of a low loading tilt deck with the bed size of a flatbed. Accessibility has become more efficient for the loading of heavy machinery. Its rapid transition to the tilt position ensures that you spend less time loading and more time on the move. With the load distributed across two robust rams, you can trust in its stability and durability even with heavy cargo. The strengthened headboard adds an extra layer of security for your loads, while multiple lashing points provide adjustable options for securing your payload, giving you the peace of mind that your precious cargo is in safe hands on every journey.



<b>U-Tilt</b>		
<b>Gross Weight</b>	<b>KG</b>	3500KG
<b>Payload</b>	<b>KG</b>	2500KG (2400KG with Drop Sides)
<b>Bed Dimensions</b>	<b>mm ft</b>	L 4930 x W 1980mm (Without Drop Sides Fitted) L 16'.2" x W 6'.6"
<b>Overall Dimensions:</b>	<b>mm ft</b>	L 6376mm x W 1980mm x H 1607mm (SA Ramps) L 20'.9" x W 6'.5" x H 5'.2"
<b>Tyre Size</b>		195/55R10
<b>Suspension</b>		Leaf Springs or SuperRide

### Options:

Drop Side Kit, Ladder Rack, Mesh side extenders, Adjustable winch, 1.8 high full width mesh ramp.



# indespension Car Transporter

Our vehicle and car transporters are built to be lightweight, strong and reliable with a range of specifications and options to suit your requirements and budget. There are two ranges available – tilt deck and fixed bed.

The fixed bed trailers from indespension are fitted with 18mm phenolic resin coated plywood centre decking, which makes them versatile for carrying a range of goods. They are also fitted with easy slide pull out galvanised steel ramps, which cannot be fully removed, avoiding lost parts!

The tilt bed range of trailers is designed to enable the loading and unloading of very low vehicles. They are constructed with an all steel hot dipped galvanized chassis providing maximum strength and durability with no rusting.



		Gross Weight (KG)	Unladen Weight (KG)	Overall Dimensions	Tyre Size
TILTDECK RANGE	TD35166	3500	775	20'8" X 7½"	155/70 R12
	TD35167	3500	795	20'8" X 7'4½"	155/70 R12
	TD35166T	3500	889	20'8" X 7'½"	195/55 R10C
	TD35167T	3500	907	20'8" X 7'4½"	195/55 R10C
	TD35187T	3500	973	22'11" X 7'4½"	195/55 R10C
FIXED BED RANGE	CT27147	2700	672	18'9¼" X 7'6½"	155/70 R12
	CT27167	2700	690	20'8¾" X 7'6½"	155/70 R12

# indespension Tipper Trailer



indespension Tipper trailers have an excellent tipping angle of 50 degrees, the steepest angle on the market. They are built with removable drop sides and a choice of a manual or electrically operated hydraulic lift (depending on the model chosen). Constructed with a fully welded and reinforced box section chassis, low profile wheels and tyres, indespension's 'Super-Ride™' suspension, sealed for life bearings, and a heavy duty jockey wheel; these trailers are built for strength and durability meaning you will be choosing the ideal companion for any job.

### Optional Extras

- Ladder Rack.
- Deck Rings.
- Mesh Kit.
- Spare Wheel & Carrier.
- Loading Ramps Steel.
- Loading Ramps Aluminium .

	Gross Weight (KG)	Unladen Weight (KG)	Internal Dimensions	Tipper Type
TPR27085	2700	665	8'1" x 5'3"	Manual
TRP27085E	2700	665	8'1" x 5'3"	Electric +Manual Override Option
TPR35126E	3500	1095	11'10" x 6'3"	Electric +Manual Override Option



# indespension Livestock Trailer

The indespension Livestock trailer range is designed from the ground up to create an industry leading range, setting new standards of robustness and longevity. Packed full of invaluable features, the whole trailer experience is hassle free. Whether you want to transport pigs, sheep or cattle, there is a model to meet your exacting requirements.

## Pig & Sheep Trailers

Ideal for carrying smaller livestock loads, these trailers boast features such as our patented SuperRide™ suspension as well as optional stock doors, prop stands and fold down fronts.

### Special Features

- Rear loading ramp with optional stock door - improving safety when loading/ inspecting.
- Longer side vents - improved appearance, speed and ease of use.

### Optional Extras

- Fold down front.
- Stock ramp door.
- Dividing gate - increased loading flexibility.
- Spare wheel.
- Prop stands.
- Aluminium treadplate floor.



		<u>LT07584</u>	<u>LT14084</u>
<b>Gross Weight</b>	<b>KG</b>	750	1400
<b>Unladen Weight</b>	<b>KG</b>	323	455
<b>Internal Dimensions</b>	<b>LxWxH ft x ins</b>	2.45 x 1.2 x 1.2 8' x 4' x 4'	2.45 x 1.2 x 1.2 8' x 4' x 4'
<b>Tyre Size</b>		20.5 x 8-10	165 R13C

# Livestock Trailer

Designed for heavy duty usage and speed of operation. From a robust seven leaf spring suspension system, exclusive Premium AL-KO auto adjust brakes and waterproof IP67 LED lighting, to our strong cast coupling, our quality, strength and range of specification is unbeatable.



		<u>LT35126</u>	<u>LV35146TRI</u>
<b>Gross Weight</b>	<b>KG</b>	3500	3500
<b>Unladen Weight</b>	<b>KG</b>	1186	1402
<b>Internal Dimensions</b>	<b>LxWxH ft x ins</b>	3.65 x 1.8 x 1.8 12' x 6' x 6'	4.26 x 1.8 x 1.8 14' x 6' x 6'
<b>Standard Ramp Dimensions</b>	<b>mm</b>	C: 1690 X 1796 S: 2395 X 1796	C: 1690 X 1796 S: 2397 X 1796
<b>Tyre Size</b>		185R13C	185R13C

### BODY

- Inspection doors on both sides as standard - improves safety when loading or inspecting.
- Hanging positions for dividing gates on every arch maximises flexibility in use.
- Upper and lower lift-off access doors are easier to remove and refit.
- Longer side vents mean they are quicker and easier to deploy.
- Robust one piece aluminium mudguards - no sagging plastic.
- Easy single lever quick release on ramp.
- Chequer plate steps front & rear of mudguards- maximises inspection access.
- Strong anti-burst rail.
- Aluminium side sheeting is lightweight and robust.
- Aluminium chequer plate over tanalised timber floor.

### COUPLING

- TripleLock™ high security head fitted as standard - strong cast iron head, zinc coated with integral lock. Bolt cupped and capped for improved security.
- Cast iron delta style indespension coupling - able to withstand greater force.

### JOCKEY WHEEL

- 48mm heavy duty jockey wheel with unique anti-vibration lock pin design.
- No need for locking R clip.





# indespension Marine Trailer

## Coaster Trailer

The indespension unbraked Coaster range makes moving smaller craft plain sailing, with a choice of self-aligning rollers or adjustable bunks. Starting with the Coaster Nano designed as an entry level jet ski trailer, moving onto the Coaster Micro and Micro Swing through to the wider chassis Coaster and Coaster Swing. The Coaster Swing range uses the famous indespension 'Easy Launch and Recovery System', saving you both time and effort.

		Coaster Nano	Coaster Micro	Coaster Micro Swing	Coaster Mini	Coaster Mini Swing	Coaster 5	Coaster 5 Swing
<b>Gross Weight</b>	<b>KG</b>	350	710	710	710	710	710	710
<b>Carry Weight</b>	<b>KG</b>	270	560	575	575	575	560	560
<b>Max Boat Length</b>	<b>M</b>	Spare Jet Ski	3.9	3.9	4.5	4.5	5	5
<b>Max Rib</b>	<b>M</b>	Spare Jet Ski	4.5	4.5	5	5	5.5	5.5
<b>No. of Rollers</b>		Bunks	Bunks	17	Bunks	17	Bunks	14

### Optional Extras

- Spare Wheel.
- TripleLock™ Head.
- Wide Wheels.



## Roller Coaster™ Trailer

As the first trailer introduced to the UK to rely solely on rollers, the Roller Coaster™ set the bar for all marine trailers. All Roller Coaster™ models feature swinging beams to maintain maximum roller to hull contact during launch and recovery. They also include a two speed braked winch giving you ultimate launch control.



	Gross Weight (KG)	Carry Weight (KG)	Maximum Boat Length (M)	Maximum Rib (M)	Number of Rollers
<b>RC1</b>	750	510	5	5.5	14
<b>RC1.3</b>	1100	800	5	5.5	14
<b>RC3</b>	1100	775	5.2	6	17
<b>RC3.5</b>	1300	945	5.2	6	25
<b>RC5</b>	1300	925	5.8	7	25
<b>RC7</b>	1500	1140	5.2	6	25
<b>RC8.5</b>	1650	1190	5.8	7	25
<b>RC9</b>	1650	1200	5.2	6	25
<b>RC10</b>	1650	1375	5.8	7	33



# Super Roller Coaster™

You can rely on the twin axle Super Roller Coaster™ to transport larger craft safely and smoothly.

Easy launch and recovery technology means more time on the water and less time on the slip for you and your boat.

All Super Roller Coaster™ models feature swinging beams to maintain maximum roller to hull contact during launch and recovery. They also include a two speed braked winch giving you ultimate launch control.



	Gross Weight (KG)	Carry Weight (KG)	Maximum Boat Length (M)	Maximum Rib (M)	Number of Rollers
<b>SUPER ROLLER COASTER 5.5</b>	1800	1315	5.8	7	33
<b>SUPER ROLLER COASTER 6</b>	2000	1400	6.7	8	33
<b>SUPER ROLLER COASTER 7</b>	2600	1900	6.7	8	49
<b>SUPER ROLLER COASTER 8</b>	3200	2400	6.7	8	65
<b>SUPER ROLLER COASTER 10</b>	3500	2675	7.3	8.5	65
<b>SUPER ROLLER COASTER 10EX</b>	3500	2650	8.3	9	65

# Dipper and Big Dipper

## Single & Twin Axle



If your hull shape isn't suitable for a roller system or if you require more weight capacity, the Dipper and Big Dipper range is for you. Fully adjustable to suit many shapes and sizes of boats from 4.5m to 9m. Carpeted bunks and keel rollers give maximum hull and keel support. The option of an inboard propeller cut out frame is available for under hull propeller boats.

	Gross Weight (KG)	Carry Weight (KG)	Maximum Boat Length (M)	Maximum Rib (M)	Roller or Bunks
<b>Dipper 1</b>	1100	780	5.2	6	Bunks
<b>Dipper 2</b>	1300	965	5.8	7	Bunks
<b>Dipper 3</b>	1650	1250	5.8	7	Bunks
<b>Dipper 4</b>	1800	1435	5.8	7	Bunks
<b>Big Dipper 1</b>	2000	1450	5.8	7	Bunks
<b>Big Dipper 2</b>	2400	1750	6.7	8	Bunks
<b>Big Dipper 3</b>	3500	2200	7	8	Bunks
<b>Big Dipper 4</b>	3500	2750	8	9	Bunks

### Options

- **Flush Kit** - Helps to clean brakes from corrosive salt water.
- **TripleLock™** - Protect against any potential threats.
- **Spare Wheel** - You'll never be left stranded without a spare wheel.



# indespension

## Tow-A-Van™ Trailer

Clean lines, robust construction and ease of use are the principal design features of the Tow-A-Van™. The side panels are aluminium coated which makes them extremely light yet highly durable; and the metallic finish is unique to the Tow-a-Van™ range. Features such as protected rear clusters, stainless steel lockable door fittings and anti-theft TripleLock™ hitch all help to make the Tow-a-Van™ a pleasure to use, easy to signwrite and maintain.



### BLV Box Van Trailer

These van trailers will give you all the extra carrying capacity you could need. They are designed with an aerodynamic nose cone to reduce noise and fuel consumption. The white GRP side panels are perfect for sign writing.

	Gross Weight (KG)	Unladen Weight (KG)	Payload (KG)	Internal Dims (LxWxH)	Axles
TAV 1	740	240	510	6' x 4' x 4'	Single/Unbraked
TAV 3	1500	457	1043	8'4" x 4'10" x 4'8"	Single/Unbraked
TAV 4	2600	565	2035	8'4" x 4'10" x 4'8"	Twin/Braked
TAV 4H	2600	605	1995	8'4" x 4'10" x 6'	Twin/Braked
TAV 5	2600	630	1970	10'4" x 4'10" x 4'8"	Twin/Braked
TAV 5H	2600	680	1920	10'4" x 4'10" x 6'	Twin/Braked

	Gross Weight (KG)	Unladen Weight (KG)	Payload (KG)	Internal Dims (LxWxH)
BLV1185	1300	500	800	8' x 5' x 6'
BLV1585	1700	500	1200	8' x 5' x 6'
BLV26105	2600	600	2000	10' x 5' x 6'
BLV26106	2600	600	2000	10' x 6' x 6'
BLV26126	2600	675	1925	12' x 6' x 6'6"
BLV35146	3500	675	2825	14' x 6' x 6'6"

# indespension

## Camping & Utility Trailer

indespension's range of camping, utility and leisure trailers offer a wide variety of options to cover most purposes and to suit every budget. Whether you are going camping, sailing, wanting to move furniture, or disposing of rubbish, our wide range of Daxara Trailers provide the ideal solution. Daxara Trailers are manufactured by Erde in France and assembled in the UK by our experienced team of technicians. With a variety of different models available, all with great features, the Daxara boasts a huge range of sizes and carrying capacities. Add to that a list of affordable options and accessories, the Daxara is ideal for both domestic, leisure and light commercial use.



### Options

- Hard Top
- Prop Stands x2
- Mesh Sides
- Jockey Wheel
- Spare Wheel
- Cycle Carrier

		Daxara 107	Daxara 127	Daxara 148	Daxara 158	Daxara 198
Gross Weight	KG	350	400	600	650	750
Unladen Weight	KG	55	65	110	110	165
Payload	KG	295	335	502	540	585
Internal Dimensions LxWxH	M	1.06 x 0.85 x 0.32	1.20 x 0.92 x 0.35	1.44 x 0.99 x 0.4	1.44 x 0.99 x 0.40	1.85 x 1.15 x 0.04

## Motorcycle Trailer

indespension can offer a number of different Motorcycle Trailers to choose from. Whether you choose from either of the single motorcycle trailers available or from the 2 multipurpose, multi-bike trailers we have to offer, you can be rest assured that each one comes with the familiar quality features and benefits.



		CH751N	PM310
Gross Weight	KG	750	300
Unladen Weight	KG	125	60
Payload	KG	624	240
Overall Dimensions LxW	M	3.06 x 1.86	2.34 x 1.45

### Options

- 2m Load Rail
- Ratchet Straps
- 1m Loading Ramp
- 1.5m Loading Ramp
- Spare Wheel
- Checkerplate Flooring





# ***indespension***

## **We're *in* the know**

Not sure what you need then simply contact our team of experts - we're here to help!

**Central Sales:** 01204 478591

## **We're *in* the places you are**

With Branches located all over the UK and Ireland you're never too far away from a professional and friendly service for your trailer or towbar needs.

## **Visit your nearest Branch**

Opening times may vary due to seasonal changes. Please contact your nearest Branch to confirm their current opening times.

**T: 0845 3 720 720**



**1. Belfast (BT36 4WX)**

028 9083 9933

**2. Bolton (BL3 2RY)**

01204 397999

**3. Cardiff (CF11 8TX)**

029 2035 9073

**5. Derby (DE24 8ST)**

01332 348555

**6. Dublin (D12 PD36)**

00 353 18081300

**7. Edinburgh (EH52 5NN)**

0131 661 7571

**8. Gatwick (RH11 OPS)**

01293 526300

**9. Glasgow (G62 6PS)**

0141 956 3055

**10. Ipswich (IP1 4JR)**

01473 749922

**11. Leeds (LS10 1TD)**

01132 707444

**12. Limerick (V94 PR80)**

00 353 61 225700

**13. Newcastle (NE27 ONB)**

0191 253 0411

**14. Northampton (NN4 8JD)**

01604 875126

**15. Portsmouth (P07 6QX)**

023 9226 7955

**16. West Midlands (B62 8JE)**

0121 561 5467