



Trailers above may be shown with options.

Warranty Limited Lifetime Structural

25 Year Roof

10 Year Torsion

5 Year Tire & Wheels

	6' Wide Includes a 3' V-Nose	7' Wide Includes a 3' V-Nose	8' Wide Includes a 3' V-Nose
Available Lengths (Single) Available Lengths (Tandem)	13', 15' 15'	15' 15', 17', 19', 21', 23'	N/A 17', 19', 21', 23'
GVWR (Single) GVWR (Tandem)	2,990# 7,000#	2,990# 7,000#	N/A 7,000#
*Axles	3,500# Torsion	3,500# Torsion	3,500# Torsion
Coupler (Single) Coupler (Tandem)	2" Straight 2 5/16" Straight	2" Straight 2 5/16" Straight	N/A 2 5/16" Straight
Cross Members	2" x 3" Tube 24" OC	2" x 3" Tube 24" OC	2" x 3" Tube 16" OC
Exterior Skin	Bonded, Screwless .030 Alum. w/ Divider Stripe	Bonded, Screwless .030 Alum. w/ Divider Stripe	Bonded, Screwless .030 Alum. w/ Divider Stripe
Frame	2" x 4" Tube	2" x 4" Tube	2" x 4" Tube
Interior Height	78"	78"	78"
Interior Width	69"	79"	93"
Rear Door Opening	61" Wide x 73" Tall	71" Wide x 73" Tall	85" Wide x 73" Tall
Rear Door Hardware (Ramp)	Stainless Steel + Black Locking Hasps	Stainless Steel + Black Locking Hasps	Stainless Steel + Black Locking Hasps
Roof Bows	1" x 1" Tube 24" OC (w/ Stringers)	1" x 1" Tube 24" OC (w/ Stringers)	1" x 1" Tube 24" OC (w/ Stringers)
Side Door	30" x 68" Curbside RV w/ Flush Lock & Alum. Holdback (Black Frame)	30" x 68" Curbside RV w/ Flush Lock & Alum. Holdback (Black Frame)	30" x 68" Curbside RV w/ Flush Lock & Alum. Holdback (Black Frame)
Tie Downs	4- 1,000# D-Rings Installed	4- 1,000# D-Rings Installed	4- 1,000# D-Rings Installed
Tires/Wheels	ST205/75R15 Aluminum (Gunmetal or Black)	ST205/75R15 Aluminum (Gunmetal or Black)	ST205/75R15 Aluminum (Gunmetal or Black)
Vents	2 Plastic Side Air Vents	2 Plastic Side Air Vents	2 Plastic Side Air Vents
Wall/Ceiling Interior	3/8" Engineered Wood Panel Unfinished Ceiling	3/8" Engineered Wood Panel Unfinished Ceiling	3/8" Engineered Wood Panel Unfinished Ceiling
Wall Structure	1" x 1.5" Tube 16" OC	1" x 1.5" Tube 16" OC	1" x 1.5" Tube 16" OC

* Single Axles Standard with 1 Idler / Tandem Axles Standard with 2 Brakes