



Specification Page

HH SERIES FLAT TOP CARGO - SINGLE AXLE ENCLOSED TRAILERS

	5' x 8' (3K)	5' x 10' (3K)	6' x 10' (3K)	6' x 12' (3K)	6' x 14' (3K)	7' x 10' (3K)	7' x 12' (3K)
Model	H608SFTV-035	H6010SFTV-035	H7210SFTV-035	H7212SFTV-035	H7214SFTV-035	H8410SFTV-035	H8412SFTV-035
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500	3500
GWVR (lb.)	2990	2990	2990	2990	2990	2990	2990
Curb Weight (lb.)	1030	1100	1320	1375	1500	1530	1650
Payload Capacity (lb.)	1960	1890	1670	1615	1490	1460	1340
Frame Construction	3" Tube Steel	3" Tube Steel	3" Tube Steel	3" Tube Steel	3" Tube Steel	4" Tube Steel	4" Tube Steel
Crossmembers	Formed Channel Steel, 24" OC		Formed Channel Steel, 24" OC			Formed Channel Steel, 24" OC	
Wall Uprights	Tube Steel, 24" OC		Tube Steel, 24" OC			Tube Steel, 24" OC	
Roof Bows	Galvanized Tube Steel, 24" OC		Galvanized Tube Steel, 24" OC			Galvanized Tube Steel, 24" OC	
Exterior Sheeting	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
Tongue Construction	3" Tube Steel	3" Tube Steel	3" Tube Steel	3" Tube Steel	3" Tube Steel	4" Tube Steel	4" Tube Steel
Coupler	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame	2" A-Frame
Coupler Height	17"	17"	17"	17"	17"	17"	17"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel
Axle Type	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler	Drop Spring Idler
Brakes	-	-	-	-	-	-	-
Breakaway Kit	-	-	-	-	-	-	-
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	4-Prong Flat	4-Prong Flat	4-Prong Flat	4-Prong Flat	4-Prong Flat	4-Prong Flat	4-Prong Flat
Exterior Lighting	LED	LED	LED	LED	LED	LED	LED
Interior Lighting	(1) 12V, LED Dome Light		(1) 12V, LED Dome Light			(1) 12V, LED Dome Light	
Side Escape Door	N/A	Yes	Yes	Yes	Yes	Yes	Yes
Side Door (H x W)	-	64" x 32"	68" x 32"	68" x 32"	68" x 32"	68" x 32"	68" x 32"
Rear Door Type	Spring Assist Ramp		Spring Assist Ramp			Spring Assist Ramp	
Rear Opening (H x W)	65" x 58"	65" x 58"	70" x 66"	70" x 66"	70" x 66"	70" x 78"	70" x 78"
Load Capacity (lb.)	1000	1000	1000	1000	1000	1000	1000
Overall Length	13'-6"	15'-6"	15'-6"	17'-6"	19'-6"	15'-6"	17'-6"
Overall Width	93"	93"	93"	93"	93"	102"	102"
Overall Height	7'-2"	7'-2"	7'-8"	7'-8"	7'-8"	8'-0"	8'-0"
Overall Interior Length	12'-2"	14'-2"	14'-2"	16'-2"	12'-2"	14'-2"	14'-2"
Deck Box Length	57"	57"	69"	69"	81"	81"	81"
Interior Width	-	-	-	-	-	-	-
Between Wheel Wells	66"	66"	73"	73"	73"	73"	73"
Interior Height	18"	18"	18"	18"	18"	18"	18"
Deck Height	9'-10"	11'-10"	11'-10"	13'-10"	9'-10"	11'-10"	13'-10"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Tube Frame Steel Formed Channel Crossmembers Steel Tube Wall Uprights Galvanized Steel Tube Row Bows Body Fully Undercoated Vapor Barrier Flat Roof with .024 Aluminum Sheeting 30" V-Nose Steel Tube A-Frame Tongue 2" A-Frame Posi-Lock Coupler Dual Safety Chains and Hooks 	<ul style="list-style-type: none"> 2K Rated Swivel Jack .030 Aluminum Exterior Sheeting Standard Color Options: White / Black / Charcoal / Silver 24" Aluminum Tread Plate Rock Guard Weather Coated Tongue and Rear Bulkhead 3/8" Engineered Wood Interior Walls Aluminum H-Channel Wall Transitions 66" Wall Height - 5' Wide Models 72" Wall Height - 6' and 7' Wide Models 	<ul style="list-style-type: none"> 3/4" Engineered Wood Flooring 32" Side Door RV-Style Latch (Excludes 5x8) Aluminum Door Hold Back Spring Assist Rear Ramp Door Aluminum Tapered Square Fenders Drop Spring Idler Suspension with Easy Lube Hubs Radial Tires on White Steel Wheels 12V LED Dome Light and Switch, Wall Mounted Full LED, DOT Compliant Lighting
--	---	---