



HH SERIES FLAT TOP CARGO - TANDEM AXLE

6' AND 7' WIDE ENCLOSED TRAILERS

	6' x 12'	7' x 12'	7' x 14'	7' x 16'	7' x 18'	7' x 20'
7K Model	H7212TFTV-070	H8412TFTV-070	H8414TFTV-070	H8416TFTV-070	H8418TFTV-070	H8420TFTV-070
GAWR (lb./axle)	3500	3500	3500	3500	3500	3500
GWVR (lb.)	7000	7000	7000	7000	7000	7000
Curb Weight (lb.)	1750	1930	2100	2220	2380	2470
Payload Capacity (lb.)	5250	5070	4900	4780	4620	4530
10K Model	H7212TFTV-100	H8412TFTV-100	H8414TFTV-100	H8416TFTV-100	H8418TFTV-100	H8420TFTV-100
GAWR (lb./axle)	na	5200	5200	5200	5200	5200
GWVR (lb.)	na	9900	9900	9900	9900	9900
Curb Weight (lb.)	na	2200	2250	2400	2630	2870
Payload Capacity (lb.)	na	7700	7650	7500	7270	7030
Frame Construction	4" Tube Steel	4" Tube Steel	4" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Crossmembers	Formed Channel Steel, 16" OC					
Wall Uprights	Tube Steel, 24" OC	Tube Steel, 24" OC	Tube Steel, 24" OC	Tube Steel, 24" OC	Tube Steel, 24" OC	Tube Steel, 24" OC
Roof Bows	Galvanized Tube Steel, 24" OC					
Exterior Sheeting	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum	.030 Aluminum
Tongue Construction	4" Tube Steel	4" Tube Steel	4" Tube Steel	4" Tube Steel	6" Tube Steel	6" Tube Steel
Coupler	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame	2-5/16" A-Frame
Coupler Height	18"	18"	18"	18"	18"	18"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes
Jack	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel	2K Rated Swivel
Axle Type	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake	Drop Spring Brake
Brakes	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	Yes	Yes	Yes	Yes	Yes	Yes
Tires: 7K	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
10K	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'	ST225/75R15 'D'
Wheels: 7K	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
10K	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5	15", 6 on 5.5
Trailer Plug	7-Way	7-Way	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED
Interior Lighting	(2) 12V, LED Dome Light					
Side Escape Door	Yes	Yes	Yes	Yes	Yes	Yes
Side Door (H x W)	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"	68" x 36"
Rear Door Type	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp	Spring Assist Ramp
Rear Opening (H x W)	69" x 66"	69" x 78"	69" x 78"	69" x 78"	69" x 78"	69" x 78"
Load Capacity (lb.)	1000	1000	1000	1000	1000	1000
Overall Length	17'-6"	17'-10"	19'-10"	21'-10"	23'-10"	26'-10"
Overall Width	92"	102"	102"	102"	102"	102"
Overall Height: 7K	7'-9"	8'-1"	8'-1"	8'-1"	8'-3"	8'-3"
10K	-	8'-2"	8'-2"	8'-2"	8'-4"	8'-4"
Interior Length	14'-2"	14'-2"	16'-2"	18'-2"	20'-2"	22'-3"
Deck Box Length	11'-10"	11'-10"	13'-10"	15'-10"	17'-10"	19'-10"
Interior Width	69"	82"	82"	82"	82"	82"
Between Wheel Wells	-	-	-	-	-	-
Interior Height	73"	73"	73"	73"	73"	73"
Deck Height: 7K	19"	19"	19"	19"	20"	20"
10K	20"	20"	20"	20"	20"	20"

STANDARD FEATURES

<ul style="list-style-type: none"> Steel Tube Frame Steel Formed Channel Crossmembers Steel Tube Wall Uprights Galvanized Steel Tube Row Bows Body Fully Undercoated Vapor Barrier Flat Roof with .024 Aluminum Sheeting 30" V-Nose Steel Tube A-Frame Tongue 2 5/16" A-Frame Posi-Lock Coupler 	<ul style="list-style-type: none"> Dual Safety Chains and Hooks 2K Rated Swivel Jack .030 Aluminum Exterior Sheeting Standard Color Options: <ul style="list-style-type: none"> White / Black / Charcoal / Silver 24" Aluminum Tread Plate Rock Guard Weather Coated Tongue and Rear Bulkhead 3/8" Engineered Wood Interior Walls - 72" Height Aluminum H-Channel Wall Transitions 3/4" Engineered Wood Flooring 	<ul style="list-style-type: none"> 36" Side Door RV-Style Latch Aluminum Door Hold Back Spring Assist Rear Ramp Door Aluminum Teardrop Fenders Drop Spring Brake Suspension Easy Lube Hubs Radial Tires on White Steel Wheels (2) 12V LED Dome Light and Switch, Wall Mounted Full LED, DOT Compliant Lighting
---	---	---