



ALUMINUM ATV UTILITY UTILITY TRAILERS



	82" x 12' (3K)	82" x 14' (3K)	82" x 14' (7K)	82" x 16' (7K)	82" x 18' (7K)	82" x 20' (7K)
Model	H8212RSAV-030	H8214RSAV-030	H8214TRSAV-070	H8216TRSAV-070	H8218TRSAV-070	H8220TRSAV-070
GAWR (lb. / axle)	3500	3500	3500	3500	3500	3500
GVWR (lb.)	2990	2990	7000	7000	7000	7000
Curb Weight (lb.)	1000	1090	1585	1650	1740	1900
Payload Capacity (lb.)	1990	1900	5415	5350	5260	5100
Frame Construction	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle	3"x2" Angle
Crossmembers	3"x2" Angle	3"x2" Angle	3" Channel	3" Channel	3" Channel	3" Channel
Top Rail	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube	2"x2" Tube
Uprights/Sides	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube	2"x1 1/2" Tube
Tongue Construction	4" Tube	4" Tube	5" Tube	5" Tube	5" Tube	5" Tube
Coupler	2" A-Frame	2" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame	2 5/16" A-Frame
Coupler Height	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"	14 1/2"
Safety Chains	Yes	Yes	Yes	Yes	Yes	Yes
Jack	1K Rated Swivel	1K Rated Swivel	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back	2K Rated Set-Back
Axle Type	Leaf Spring Idler	Leaf Spring Idler	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake	Leaf Spring Brake
Brakes	-	-	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric	4-Wheel Electric
Breakaway Kit	-	-	Yes	Yes	Yes	Yes
Tires	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'	ST205/75R15 'C'
Wheels	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5	15", 5 on 4.5
Trailer Plug	4-Prong	4-Prong	7-Way	7-Way	7-Way	7-Way
Exterior Lighting	LED	LED	LED	LED	LED	LED
Decking	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine	Pressure Treated Pine
Ramp Style	Bi-Fold Gate	Bi-Fold Gate	Bi-Fold Gate	Bi-Fold Gate	Bi-Fold Gate	Bi-Fold Gate
Ramp Length x Width	54 1/2" x 79"	54 1/2" x 79"	54 1/2" x 79"	54 1/2" x 79"	54 1/2" x 79"	54 1/2" x 79"
Load Capacity (lb.)	2200	2200	2200	2200	2200	2200
Overall Length	16'-9"	18'-9"	18'-9"	20'-9"	22'-9"	24'-9"
Overall Width	100 1/4"	100 1/4"	102"	102"	102"	102"
Overall Height	49"	49"	49"	49"	49"	49"
Deck Height	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"	17 1/2"
Deck Length	12'-0"	14'-0"	14'-0"	16'-0"	18'-0"	20'-0"
Deck Width	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"	82 1/4"

STANDARD FEATURES

<ul style="list-style-type: none"> Aluminum Angle Extrusion Frame Single Axle, Aluminum Angle Crossmembers Tandem Axle, Aluminum Channel Crossmembers 2" x 1-1/2" Aluminum Extrusion Tube Uprights 2" x 2" Aluminum Tube Top Rail (2) 3" X 5' Side Ramp Conversions (2,400 lb. Load Rating) 	<ul style="list-style-type: none"> Aluminum Tube Tongue A-Frame Posi-Lock Coupler Dual Safety Chains and Hooks Single Axle, 1K Rated Swivel with Caster Wheel Tandem Axle, 2K Rated Set-Back with Foot 2x8 Treated, #1 Grade Wood Decking Front and Rear End Caps 	<ul style="list-style-type: none"> 54" Bi-fold Gate Aluminum Radius Fenders Spring Suspension with Easy Lube Hubs Radial Tires on Aluminum Wheels Full LED, DOT Compliant Lighting Sealed Wiring Harness Aluminum Stake Pockets
---	--	--