



DATA SHEET

Nitrile NBR/SBR

Grade	A40	
Colour	BLACK	
Elastomer	NITRILE	
Quality	COMMERCIAL	
Hardness Shore A ± 5	70	ISO 7619-1
SG (g/cm ³)	1.4	ISO 2781
Tensile (N/mm ²)	5	ISO 37
Elongation %	300	ISO 37
Compression %	35	ISO 37
Tear Strength		ISO 34-1
Abrasion mm ³	0	ISO 37
Temperature (°C) from	-28	
Temperature (°C) to	80	

Roll Tolerances		
Width tolerance:	+/- 2%	ISO 3302 SW1
Length tolerance:	+/- 2%	ISO 3302 SW1

Thickness	
0.5– 1mm	+/- 0.2mm
1.5mm –3mm	+/- 0.3mm
4mm—5mm	+/- 0.4mm
6mm	+/- 0.5mm
8mm	+/- 0.7mm
10mm—15mm	+/- 1mm
20mm	+/- 1.4mm
25mm	+/- 1.75mm

Thicknesses available	
1mm to 6mm	1.4m x10m
8mm to 25mm	1.4m x 5m
32mm, 38mm, 40mm and 52mm	1m x 1m

The information given is based upon average values and is in no way intended as a warranty. The purchaser shall be responsible for determining the suitability of the product for any particular application.



Kent Gaskets Ltd



@gaskets247



CERTIFICATE NO. 19809
ISO9001