

INTODUCTION

Kent Gaskets Grade

KG-700 is a general purpose commercial FKM rubber. It has outstanding resistance to oxygen, ozone, weather, flame and chemicals. Suitable for higher temperature applications withing the Petrochemical, Pharmaceutical and Aerospace Industries.

DATA SHEET

Viton Rubber Sheeting KG-700 - 60

PROPERTIES	TEST METHOD	VALUE
BASE POLYMER	FLUOROELASTOMER	
HARDNESS	ASTM D2240 00	65° SHORE 'A'
TENSILE STRENGTH	ASTM D412	6 MPa
SPECIFIC GRAVITY	ASTM D792	1.98 g/cm ³
ELONGATION @ BREAK	ASTM D412	250% min
MIN CONTINUOUS WORKING TEMP		-30° C
MAX CONTINUOUS WORKING TEMP		210° C
MAX INTERMITTENT WORKING TEMP		210° C
COMPRESSION SET (70° FOR 22 HOURS)	ASTM D395 METHOD B	50% Max

GENERAL GUIDELINES FOR USE		
ABRASION RESISTANCE	MODERATE	
GENERAL PURPOSE	NOT RECOMMENDED	
FOOD USE	NOT RECOMMENDED	
OZONE WEATHER RESISTANCE	EXCELLENT	
FLAME RETARDENCY	NOT RECOMMENDED	
ELECTRICAL RESISTANCE	MODERATE	







CERTIFICATE NO. 19809 ISO9001 The information given is based upon average values and is in no way intended as a warranty. The purchaser shall be responsible for determining the suitability of the product for any particular application.