Uniform Mitigation Verification Inspection Form

	opy of this form and a	any documentation pro	ovided with the insuran	ce policy	
Inspection Date:					
Owner Information					
Owner Name:	1		Contact Person:		
Address:			Home Phone:		
City:	Zip:		Work Phone:		
County:			Cell Phone:		
Insurance Company:			Policy #:		
Year of Home: 1958	# of Stories:	1	Email:		
NOTE: Any documentation use accompany this form. At least o though 7. The insurer may ask	ne photograph must acc	company this form to val	idate each attribute marke	ed in questions 3	
1. <u>Building Code</u> : Was the structure the HVHZ (Miami-Dade or Br	roward counties), South Fl	lorida Building Code (SFE	BC-94)?		
a date after 3/1/2002: Buil	ding Permit Application I	Date (MM/DD/YYYY)	t in 2002/2003 provide a pe		
provide a permit application	on with a date after 9/1/19	94: Building Permit Appl	For homes built in 1 ication Date (MM/DD/YYYY)		
C. Unknown or does not n	neet the requirements of A	Answer "A" or "B"			
 Roof Covering: Select all root OR Year of Original Installation covering identified. 					
2.1 Roof Covering Type:	Permit Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance	
1. Asphalt/Fiberglass Shingle	03/01/2012				
2. Concrete/Clay Tile	<u> </u>				
☐ 3. Metal					
	00/04/0040				
✓ 4. Built Up	03/01/2012				
5. Membrane					
6. Other					
 ✓ A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later. □ B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later. □ C. One or more roof coverings do not meet the requirements of Answer "A" or "B". □ D. No roof coverings meet the requirements of Answer "A" or "B". 					
3. Roof Deck Attachment : What	t is the weakest form of ro	oof deck attachment?			
A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c. by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.					
B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum 24" inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesis other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spa a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.					
24"inches o.c.) by 8d comdecking with a minimum	24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Grooved decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent				
*This verification form is valid finaccuracies found on the form.	for up to five (5) years pr	rovided no material chan	ges have been made to the	e structure, or	

		182 psf.	esistance than 8d common hans spaced a maximum of 6 inches in the field of has a mean upint resistance of at least
		D. Reinfor	ced Concrete Roof Deck.
		E. Other: _	
			n or unidentified.
		G. No attic	access.
4.			ttachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within ide or outside corner of the roof in determination of WEAKEST type)
		A. Toe Nai	ils
			Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
			Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
	Mi	nimal condi	tions to qualify for categories B, C, or D. All visible metal connectors are:
		V	
		~	Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
	•	B. Clips	
		•	Metal connectors that do not wrap over the top of the truss/rafter, or
			position requirements of C or D, but is secured with a minimum of 3 nails.
		C. Single V	Vraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
		D. Double	
			•
			Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
		E. Structur	al Anchor bolts structurally connected or reinforced concrete roof.
		F. Other:	
		G. Unknov	vn or unidentified
		H. No attic	access
5.			What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of the over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
		A. Hip Roo	Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: feet; Total roof system perimeter: feet
		B. Flat Roo	less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof areasq ft
	•	C. Other R	oof Any roof that does not qualify as either (A) or (B) above.
6.	Sec	A. SWR (a sheathir dwelling	ter Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the ag or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the g from water intrusion in the event of roof covering loss.
		B. No SWI	R. vn or undetermined.
In	spec	tors Initials	Property Address
*1	his	verification	form is valid for up to five (5) years provided no material changes have been made to the structure or

Page 2 of 4

inaccuracies found on the form.

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

7. **Opening Protection:** What is the <u>weakest</u> form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. **Second**, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings **and** (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart Place an "X" in each row to identify all forms of protection in use for each opening type. Check only one answer below (A thru X), based on the weakest form of protection (lowest row) for any of the Glazed openings and indicate the weakest form of protection (lowest row) for Non-Glazed openings.		Glazed Openings				Non-Glazed Openings	
		Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure		$ \times $	$\mid \times \mid$	$ \times $	$I \times I$	\times
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)						
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
IN	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection	X					

A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at
a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval
system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure
and Large Missile Impact" (Level A in the table above).

- Miami-Dade County PA 201, 202, and 203
- Florida Building Code Testing Application Standard (TAS) 201, 202, and 203

A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist

- American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
- Southern Standards Technical Document (SSTD) 12
- For Skylights Only: ASTM E 1886 and ASTM E 1996
- For Garage Doors Only: ANSI/DASMA 115

	X in the table above			
	☐ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above			
	B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed			
	openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices			
in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the follow				
for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):				
	• ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile – 4.5 lb.)			
	• SSTD 12 (Large Missile – 4 lb. to 8 lb.)			
	• For Skylights Only: ASTM E 1886 <u>and</u> ASTM E 1996 (Large Missile - 2 to 4.5 lb.)			
	☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist			

A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or

☐ B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above

☐ B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

□ <u>C. Exterior Opening Protection- Wood Structural Panels meeting FBC 2007</u> All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above).

C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist

☐ C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above

 \square C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter sprotective coverings not meeting the requirements of An	nswer "A", "B", or C" or system			
with no documentation of compliance (Level N in the ta	, and the second			
N.1 All Non-Glazed openings classified as Level A, B, C, o		· ·		
 N.2 One or More Non-Glazed openings classified as Level table above 	D in the table above, and no Non-G	lazed openings classified as Level X in the		
N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above			
✓ X. None or Some Glazed Openings One or more Glaze	ed openings classified and Level	l X in the table above.		
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi				
Qualified Inspector Name: Kapp A. McMullin, HI11423	License Type: Home Inspector	License or Certificate #: HI 11423		
Inspection Company: KMI Home Inspections, Inc.	Pho			
Qualified Inspector – I hold an active license as a	: (check one)			
 ✓ Home inspector licensed under Section 468.8314, Florida Statutes who has completed the statutory number of hours of hurricane mitigation training approved by the Construction Industry Licensing Board and completion of a proficiency exam. ☐ Building code inspector certified under Section 468.607, Florida Statutes. ☐ General, building or residential contractor licensed under Section 489.111, Florida Statutes. ☐ Professional engineer licensed under Section 471.015, Florida Statutes. ☐ Professional architect licensed under Section 481.213, Florida Statutes. 				
Any other individual or entity recognized by the insurer as posse verification form pursuant to Section 627.711(2), Florida Statute		o properly complete a uniform mitigation		
(print name) contractors and professional engineers only) I had my emplo	cuctures personally and not the ect employee who possesses the end I personally performed the	e inspection or (licensed) perform the inspection		
and I agree to be responsible for his/her work. Qualified Inspector Signature:	Date: _			
An individual or entity who knowingly or through gross ne subject to investigation by the Florida Division of Insuranc appropriate licensing agency or to criminal prosecution. (S certifies this form shall be directly liable for the misconduc performed the inspection.	gligence provides a false or fra e Fraud and may be subject to ection 627.711(4)-(7), Florida	o administrative action by the Statutes) The Qualified Inspector who		
<u>Homeowner to complete</u> : I certify that the named Qualified residence identified on this form and that proof of identification				
Signature: Date:				
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)				
The definitions on this form are for inspection purposes only and cannot be used to certify any product or construction feature as offering protection from hurricanes.				
Inspectors Initials Property Address_				
*This verification form is valid for up to five (5) years prov	ided no material changes have	e been made to the structure or		

OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155

Page 4 of 4

House Front



House Number



Left Elevation



Rear Elevation



Right Elevation



Roof 1



Roof 2



Roof 3



Roof 4



Roof 5



Roof 6



Roof to Wall 1



Roof to Wall 2



1/2" Sheathing



8d Nails



Nail Spacing 1



Nail Spacing 2

