PVDF (Kynar 500) Paint Finish

The Best Defense Against Chalking and Fading



manufacturing corporation

PVDF (Kynar 500) Finish

THE WINNING DEFENSE AGAINST NATURE'S OFFENSE



Metal Sales PVDF (Kynar 500®) finish couples premium ceramic pigments with fluorpolymer resins for long life resistance against color fading and chalking. As a result color performance is warranted for a full 35 years in accordance with ASTM test standards. All metal panel finishes will fade with years of sun exposure. However, panels from Metal Sales with PVDF (Kynar 500) will look almost as good years from now as they did in their first year. Visit www.metalsales.us.com for complete warranty details. New Panel Maximum* fade in 35 years

35 YEAR KYNAR 500 FADE PERFORMANCE CHART

* Based on extreme, real outdoor, south Florida exposure performance data; exposure conditions in more northerly climates will likely demonstrate greater performance (less fade). This chart represents a maximum allowable fade over thirty-five years measured as five Hunter units. This chart is a mechanical representation and may vary slightly from actual test panels.

KYNAR COMPARED TO OTHER COATINGS

Blue: 15 years exposure Yellow: 17 years exposure



With excellent exterior durability this PVDF steel panel color coating will keep you in the game right into overtime. PVDF (Kynar 500) coated panels from Metal Sales Manufacturing provide such an outstanding defense against ultraviolet radiation that they are warranted for 35 years against chalking and fading.

This exceptional color and gloss retention is not possible with any other coating available today.

Also warranted against blistering, cracking and peeling for 45 years, PVDF (Kynar 500) coating is architect preferred and your best defense against the rigors of nature and atmospheric pollution.

metal sa manufacturing corporation

45 Year Demonstrating its competitive edge, PVDF (Kynar 500) performance leads the league in defense against the sun, DURABILIT weather and pollution. Its carbon-fluorine chemistry creates one Warranty of the strongest bonds in the universe. It is warranted against blistering, cracking and peeling for 45 years. Visit www.metalsales.us.com for complete warranty details.

PVDF (Kynar 500) Coating System

The PVDF (Kynar 500) system is tougher than just the front line; its superior performance is a result of a layered, fluoropolymer bonded coating system, each component layer providing a unique performance characteristic.

Topcoat | Premium ceramic and inorganic pigmented PVDF (PolyVinylidine DiFluoride) for exceptional color durability and gloss retention

Primer | UV & moisture resistant modified polyester, provides corrosion resistance and bonding

Chemical Rinse | Acts as a sealer providing additional corrosion protection

Pretreatment | Promotes adhesion, moisture and corrosion resistance

Galvanized or Galvalume[®] | Barrier protection on base steel, inhibits corrosion

BARE STEEL | Mill certified meeting ASTM standards

Galvanized or Galvalume® Pretreatment **Chemical Rinse** Primer Back coat | Finish coat on backside, covers primer and insures

Reduce building energy use by up to 50% with select PVDF (Kynar 500) colors

consistent color Metal Sales recognizes that architects and consumers are becoming more and more concerned with ways of making their building project more energy efficient. All of Metal Sales' PVDF (Kynar 500) colors are ENERGY STAR[®] listed. They use special pigments for solar reflectance to meet ENERGY STAR guidelines. These

Metal Sales roof panels are "Eligible Building Envelope Components" that



Cool Roofing

qualify for tax credits for consumers and LEED (Leadership in Energy and Environmental Design) credits for architects. See www.metalsales.us.com for complete details and certificates.

GALVANIZED OR GALVALUME ® BACK COAT

GALVANIZED OR GALVALUME ®

TOPCOAT

PRIMER

CHEMICAL RINSE

PRETREATMENT

A construction of widths, colors, and gauges readily available for new construction or retrofit from 20 convenient locations across the country.

For more information, visit our website at www.metalsales.us.com or contact Metal Sales at 800.406.7387.

Test Performance & Specifications PVDF (Kynar 500) Formulated for the 21st Century

Humidity Resistance - No blistering, cracking, peeling, loss of gloss of softening of the finish after 2000 hours of exposure to 100% humidity at 100°F ±5°F, per Federal Test Method Standard 141, Method 6201 or ASTM D 2247.

Chalk Resistance - No chalking greater than #8 rating per ASTM D 4214, Method ASTM D 659 test procedure after a 2000 hour weatherometer test.

Color Change - Finish color coat change not to exceed 5 Hunter units per ASTM D 2244 test procedure, after 2000 hour weatherometer test.

Abrasion Resistance - Per ASTM D 968, Method A, PVDF (Kynar 500) will pass 30 liters/mil, minimum of falling sand.

Salt Spray Resistance - Samples diagonally scored and subjected to 5% neutral salt spray per ASTM B 117, then taped with cellophane tape: 1000 hours-no blistering, and no loss of adhesion greater than 1/8" from score line. Samples taped 1 hour after removal from test cabinet.

SEE WWW.METALSALES.US.COM FOR COMPLETE SPECIFICATIONS, TEST DATA AND WARRANTIES.

SALES AND MANUFACTURING LOCATIONS

Denver, Colorado 800.289.7663

Jacksonville, Florida 800.394.4419

Jefferson, Ohio 800.321.5833

Independence, Missouri 800.747.0012

Sellersburg, Indiana 800.999.7777

Rogers, Minnesota 800.328.9316

Nashville, Tennessee 800.251.8508

Spokane, Washington 800.572.6565

Seattle, Washington 800.431.3470

Sioux Falls, South Dakota 888.902.8320

Rock Island, Illinois 800.747.1206

Deer Lake, Pennsylvania 800.544.2577

Temple, Texas 800.543.4415

Woodland, California 800.759.6019

Fontana, California 800.782.7953 Anchorage, Alaska 866.640.7663

Bay City, Michigan 888.777.7640

Detroit Lakes, Minnesota 888.594.1394

Mocksville, North Carolina 800.228.6119

Fort Smith, Arkansas 877.452.3915

manufacturing corporation