

# 10020 GASPM EHD

EXTRA HEAVY DUTY HINGE OFFSET DISK HARROW



THE BRAND OF THE LAND

The model **10020 GASPM EHD** is specially designed to meet the extreme conditions in construction, road building, deep tillage, tilling new ground and recently deforested land.

### STANDARD FEATURES:

- TATU oil bath bearings assemblies with tapered roller blade and duo-cone seals.
- 1/2" x 5" x 10" gang carriers, reinforced through two-welded "U" profile.
- 2.1/2" round heat treated alloy steel gang axles.
- Heavy steel disc spacer spoils.
- Heat treated boron steel disc blades, notched front and rear.
- Heavy duty disc blade scrapers.
- Stabilizer bar front and rear disc gangs leveling.
- Perforated offset bar to allow lateral adjustments under varying draft conditions.
- Box type construction drawbar with standard draw bar plates.
- Adjustable gang axles up to 42 degrees.
- Removable bushings on articulated points.




Articulated drawbar for easier transportation.



Transport lock.

### RUGGEDLY BUILT FOR LONGER LIFE



SPECIAL OIL BATH BEARING ASSEMBLIES



TAPERED BEARINGS AND DUO-CONE TYPE SEALS.

THE LIFE OF YOUR DISK HARROW. REQUIRES ORIGINAL TATU REPLACEMENT PARTS.

### ESPECIFICATIONS:

Model	Number of Disc Blades	Working Width ft. in. (mm)	Disc Blades		Weight per Disc lbs (Kg)	Approx. Net Weight* lbs (Kg)	Tractor Draw Bar Horse Power
			Dimensions	Spacing			
10020 GASPM EHD	10	8' 0" (2,400)	36"x12mm,	20" (507mm)	791 (359)	7,915 (3,590)	180 - 200
	12	9' 6" (2,900)	38"x12mm,		791 (359)	9,498 (4,308)	200 - 220
	16	12' 5" (3,800)	and		818 (371)	13,087 (5,936)	260 - 280
	20	14' 8" (4,500)	40"x12mm		688 (312)	13,768 (6,245)	300 - 320

\* Approx. Net Weight with 36" x 12.0mm disc blades.

\*\* Please note that the tractor draw bar horse power are suggested ranges and vary according to soil conditions and weight added to harrow.

### MARCHESAN IMPLEMENTOS E MÁQUINAS AGRÍCOLAS TATU S.A.

Av. Marchesan, 1979 | CEP 15994-900 | Phone: +55 16 3382.8282 | Matão-SP-Brasil | CNPJ.: 52.311.289/0001-63 | Inscr. Est.: 441.000.151.114