



# 8917 GASPCR

## SUPER STUBBLE WHEEL OFFSET DISK HARROW



The model 8917 GASPCR, is specially designed for operate effectively under those difficult conditions and tough plowing jobs found in newly cleared forest areas or heavy sugar cane stubble left after the last ratoon crop.











**THE BRAND OF THE LAND**

All models have hydraulic controlled depth gauge and transport wheels which make them more maneuverable and easier to transport to other fields.



Hydraulic cylinders with hoses and quick couplers.


**FEATURES:**

-  TATU oil bath bearing assemblies with tapered roller bearings and duo-cone seals.
-  Welded and rugged tubular steel frames.
-  Stabilizer bar for front and rear disc gangs leveling.
-  Perforated offset bar to allow lateral drawbar adjustments under varying draft conditions.
-  Box type construction drawbar with standard drawbar plates.
-  Hydraulic controlled depth gauge and transport wheels mounted to wheel hubs that have greasable tapered roller bearings.
-  Two single 9.00x20-12 ply rib implement tires.
-  Double acting hydraulic cylinders with hoses and quick couplers.
-  Rugged 2.1/2" round, heat-treated steel disc gang axles.
-  Greasable or oil bath disc gang bearing assemblies.

SPECIAL OIL BATH BEARING ASSEMBLIES



RUGGEDLY BUILT FOR LONGER LIFE



TAPERED BEARINGS AND DUO-CONE TYPE SEALS. THE LIFE OF YOUR DISK HARROW. REQUIRES ORIGINAL TATU REPLACEMENT PARTS.

**TECHNICAL SPECIFICATIONS:**

Modelo	Number of Disc Blades	Working Width ft. in. (mm)	Disc Blades		Weight per Disc lbs (Kg)	Approx. Net Weight* lbs (Kg)	Tractor Draw Bar Power
			Dimensions	Spacing			
8917 GASPCR	10	5' 10" (1,770)	32"x9.0mm, 32"x12.0mm, 34"x9.0mm, 34"x12.0mm, 36"x9.0mm, or 36"x12.0mm	17.3/8" 440 mm	692 (314)	6,926 (3,142)	150 - 170
	12	7' 3" (2,210)			737 (362)	9,592 (4,351)	180 - 200
	14	8' 8" (2,650)			720 (326)	10,083 (4,574)	220 - 230
	16	10' 2" (3,100)			725 (329)	11,613 (5,268)	240 - 260
	18	11' 7" (3,520)			700 (318)	12,610 (5,720)	260 - 270
	20	13' 2" (4,000)			651 (295)	13,024 (5,908)	270 - 280
	22	14' 7" (4,440)			630 (285)	13,860 (6,287)	290 - 300

\* Approx. net weight with 34" x 12.0mm disc blades - Depth of cut: up to 10.1/4" (260mm)

**MARCHESAN IMPLEMENTOS E MÁQUINAS AGRÍCOLAS TATU S.A.**

Av. Marchesan, 1979 | CEP 15994-900 | Phone: +55 16 3382.8282 | Matão-SP-Brasil | CNPJ.: 52.311.289/0001-63 | Inscr. Est.: 441.000.151.114