



**Advanced
Control
Technology Inc.**

The Leader in Industrial and Commercial Sensors and Controls

"If You don't see what you need Contact Us"

Contact Us



[Home](#)

[Custom Sensors](#)

[Switches](#)

[Controls](#)

[About Us](#)

[Search](#)

[Contact Us](#)

Toll Free:

1-877-800-8820

Email:

info@actsensors.com

Float Switch

Miniature float switch 1000 series

Application:

Designed for fluid detection applications with limited space or restricted access, only 1" (25.4 mm) diameter.

Features:

- ✓ Field adjustable switch (N.O.& N.C.)
- ✓ Fits through 3/4" npt coupling
- ✓ NSF certified
- ✓ Rugged solid cellular float

Options:

- ✓ Connectors
- ✓ Custom lead wires
- ✓ Custom molding



- ✓ Female threads
- ✓ Hall effect sensor
- ✓ Jacketed cable
- ✓ Metric-British threads
- ✓ Stilling well
- ✓ Submersible
- ✓ Temperature sensor

[Home](#)
[Elec](#)
[Liquid](#)










[Level](#)
[Pressure](#)

[F.A.Q.](#)
[Site](#)
[Minneapolis](#)

A

705
 Sh
 © 20

Ordering Information

Select Qty:	Part Number	Image & Data	Stem Material	Float			Switch		Qty. in Stock	
				Material	Diameter		Specific gravity in water	Ratings (watts)		Operation (s.p.s.t.)
					in.	(mm)				
0	N 1000 N	Select a part number, and enter the quantity								
	N 1000 N		Nylon	Nylon	1"	(25.4)	.68	50w	NO & NC	1400
	P 1000 P		PP	PP	1"	(25.4)	.68	50w	NO & NC	2415
	P 1000 P 5/16"-18 unc		PP	PP	1"	(25.4)	.68	50w	NO & NC	364
	B 1000 N		Brass	Nylon	1"	(25.4)	.68	50w	NO & NC	714
	B 1000 P		Brass	PP	1"	(25.4)	.68	50w	NO & NC	382
	B 1000 B		Brass	NBR	7/8"	(22.8)	.48	50w	NO & NC	25
	S 1000 P		SS	PP	1"	(25.4)	.68	50w	NO & NC	78
	S 1000 S		SS	316 SS	1-1/16"	(27.0)	.79	50w	NO & NC	43
	S 1002 S		SS	316 SS	1-1/2"	(38.1)	.50	50w	NO & NC	31

SS = Stainless Steel, PP = Polypropylene, NBR = Buna-N

Quantities greater than 10 qualify for quantity discounts.