



^{Advanced} Greaseless Formula with Improved Penetration & Lubrication ^{Nozzle} Provides Targeted Application ^{Contoured} Can for Improved Hand Grip

DANGES: EXTREMELY FLAMMABLE AEROSOL UNITENTS UNDER PRESSUBE: READ WARNINGS ON BACK PAREL PELIBON-AEROSOL EXTERNAMENTE: INTANAMEL CONTENTIO BAIO PRESIÓN. LEER LAS PRECAUCIONES DEL PAREL TRASERI. Net Contents / Contenido Neto: 11 wt oz / 312 g



TABLE OF



INDUSTRIAL LUBRICANTS



INDUSTRIAL DEGREASERS



INDUSTRIAL ELECTRONIC CLEANERS



For 60 years, the LPS[®] line of products has been the industry standard for maintenance repair and operations chemicals (MRO).

LPS 1[®] Greaseless Lubricant, LPS 2[®] Heavy-Duty Lubricant and KB 88 The Ultimate Penetrant are among the most applied MRO products in the industry.

But the industry faces new demands for products and performance. MRO applications are focused on increased performance, safety and regulatory/environmental compliance. In response, LPS[®] is evolving with LPS[®] MAX; a new line of MRO lubricants, degreasers and electronic cleaners that are safe, efficient and sustainable.

The LPS® MAX product line focuses on meeting the needs of heavy industry through increased product performance, packaging improvements, regulatory/environmental compliance and sustainability.

The 10 products feature a slip resistant aerosol can topped with a lockable, integrated flip straw actuator that allows the operator the choice of focused precision to broad stroke product application.

Simply put, it's MAXimum control, MAXimum application and MAXimum performance in the palm of your hand.



NSF® Nonfood Compounds Registration: NSF® is a continuation of the USDA product approval and listing program for chemical products which can be used in food plants

H1	
For use throughout the facility.	
INCIDENTAL FOOD CONTACT	

C1	H2	K1	K2	
Exercise caution when in use.				
NO FOOD CONTACT				

FEATURES & BENEFITS

ACTUATOR (CAP)

Ability to lock the spray nozzle to prevent unintended spray.

ACTUATOR (BUTTON)

Industrial sized spray button provides ease of use.

INTEGRATED DUAL APPLICATION FLIP STRAW

Two options for product delivery:



Straw DOWN position broad stroke application

Straw UP position precision application

LITHOGRAPHED LABELS

No paper or similar type label means no peeling and loss of legibility.

SLIP RESISTANT AEROSOL CAN

Contoured texture provides enhanced/ firmer grip on the can during use.



INDUSTRIAL LUBRICAN LUBRICANTE INDUSTRI



'Advanced Greaseles **Nozzle Provides Targ** Contoured Can for I

DANGER: EXTREMELY FI Contents under pressure. Rea Peligro: Aerosol Extrem Contento bajo presión. Leer Las Net Contents / Contenid

2 PIECE CAN

UNLOCK TO USE

LOCK TO STORE

Fewer areas for corrosion attack versus a 3 piece can



SUPERIOR PENETRATION & UP TO 1 YEAR INDOOR METAL PARTS PROTECTION

INDUSTRIAL FORMULA FOR EXTREME DEGREASING

INDUSTRIAL DEGREASER

REMOVES GRIME WITH MAX SPEED



Presolve Industrial RANGE DEGREASE INDUSTRIAL DESENGRASADOR DE NARANJA

Moves Grime with MAX Speed Izzle Provides Targeted or Broad roke Application

intoured Can for Improved Hand Gr

DWERE EXTREMENT FLAMMABLE AEROSOL. CONTINUS UNDER MESE Many IL OF FATAL IF SWALLOWED. READ WARNINGS ON BACC MA Rused Aerosol Extremadamente inflamaale. Contenido 14.0 h Na 60 o Mortal IS se inferel Leer Las Precauciones del Panel

Net Contents/Contenido Neto: 15 wt oz / 425 g

PS MAX

INDUSTRIAL DEGREASER DESENGRASANTE INDUSTRIAL

Instant SUPER Degreaser20

5

NON-FLAMMABLE INDUSTRIAL DEGREASER DESENGRASANTE INDUSTRIAL NO INFLAMABLE

¹ Industrial Formula for Extreme Degreasin ⁴ Nozzle Provides Targeted or Broad ⁵ Stroke Application ⁴ Contoured Can for Improved Hand Grip

> WARNING: VAROR HAGHFUL HARNFUL IS SWALLOAED. OWERD WOER PRESSNE, BEAD CAUTIONS ON TAX-MAEL. ATENDIN: WAROR PREJUDICAL LANKON SIS SHIFTER OWERDD A PRESIDN. LEA LAS PRECAUCIÓN EN ERIVERSO. Net Contents/Contenido Neto: 20 wt oz / 567 9

INDUSTRIAL LUBRICANT LUBRICANTE INDUSTRIA

T

INDUSTRIAL LUBRICANT

LUBRICANTE INDUSTRIAL

DRY LUBRICANT &

WATER DISPLACER

LUBRICANTE SECO Y DESPLAZADOR DE AGUA

Advanced Greaseless Formula with

*Nozzle Provides Targeted Application *Contoured Can for Improved Hand Grip

INVERE EXTREMELY FLANMABLE ACROSSI. DRITENTS UNDER PRESSURE. READ WARNINGS ON BACK FANEL PELKRO: AEROSOL EXTREMADAMENTE INFLAMBLE. INVERTO BAD PRESIÓN. LEER LAS PRECAUCIONES DEL PANEL TENSIRO.

Net Contents / Contenido Neto: 11 wt oz / 312 g



KB 88 MAXIMUM PENETRANT PENETRANTE MÁXIMO

Advanced Penetration Formula Frees Frozen Parts Faster Nozzle Provides Targeted Application Contoured Can for Improved Hand Grip

MARE ENDINELY RAMMARE ARBOSOL CONTENS UNCER MESSIN HAWKIL OF FAMILY SYMALLOWER, READ WRADINGS ON HALT MEE DRIVEN ARBOSOL CONTENAME CONTINUAME. MED AND A STATEMAN AND AN AND AN AND AN AND MED AND A STATEMAN AND AND AND AND AND AND HEL CONTENLS IS EINIGER. LEER LAS PRECADORES BEL PARE THE HEL CONTENTS / CONTENIDO NECS: 13 WL 02 / 359 S

ADVANCED PENETRATION FORMULA FREES FROZEN PARTS FASTER



INDUSTRIAL LUBRICANT

ChainMate



LUBRICANTE, PENETRANTE Y PROTECTOR

Lubricates Chain / Wire Rope for Extreme Loads & Temperatures Nozzle Provides Targeted or Broad Stroke Application ^{Contoured} Can for Improved Hand Grip

COMPRESENTIONELY FLAMMABIE ARDONE COMPRESENTIONE PRASON ADMANNES ON BACK PAREL PRIMER AND REPOSITIONE PRAMEMATIC COMPRESENTIATION ADMANDS ON THE PAREL REPOSITION ADMANDS ON THE PAREL PAREL REPOSITION ADMANDS ON THE PAREL PAREL PAREL REPOSITION ADMANDS ON THE PAREL PAREL PAREL REPOSITION ADMANDS ON THE PAREL ANNER ETTEMEN FLAMMABLE ALROSOL, CONTENTS UNDER VESSUL

LUBRICATES CHAIN/WIRE ROPE FOR EXTREME LOADS & TEMPERATURES

ADVANCED GREASELESS FORMULA WITH IMPROVED PENETRATION & LUBRICATION

INDUSTRIAL LUBRICANTS



LPS MAX 1[™]

Dry Lubricant & Water Displacer

Fast penetration into metal crevices to Nonfood Compounds clean (carbon & other debris) & displace moisture; provides long lasting dry film

lubrication for precision instruments, locks, etc. Prevents excessive wet grime and debris accumulation.

APPLICATIONS

Cables
Circuit Breakers
Electric Motors
Electronic Connectors
Molds
Nuts & Bolts
Locks

Power Tools Hinges Sliding Mechanisms **Ignition Systems** Switch Gears Relays

NSF

H2

NET CONTENTS	CONTAINER TYPE	UNITS/CASE	LPS #
11 wt. oz./312 g/379 mL	aerosol	12	901 16



38.7% MORE **PENETRATION***

> 19.3% **MORE LUBRICITY** (4 ball scar)*



et Contents / Contenido Neto: 11 wt oz / 312 g



LPS MAX 2[™]

Lubricant, Penetrant & Protectant



H2

This multi-purpose lubricant penetrates quickly to displace moisture leaving behind a light, non-drying film that provides ongoing lubrication and added corrosion protection for up to 1 year on indoor, metal parts.

The formula reduces wear from friction and corrosion, features an extremely high flash point and is non-conductive.

APPLICATIONS

Bearings & Valves	Slides & Tracks
Cables & Linkages	Metal Parts in Storage
Hand Tools	Pulleys & Rollers
Dies, Bits & Fasteners	Engines & Electric Motors
Productions &	Relays
Transportation Equipment	

Iransportation Equipment

NET CONTENTS	CONTAINER TYPE	UNITS/CASE	LPS #
11 wt. oz./312 g/369 mL	aerosol	12	90216





LPS[®] MAX KB 88 **Maximum Penetrant**



Attacks and penetrates corrosion that Nonfood Compounds binds fasteners for a faster release, saving time. Displaces moisture, drying

out fasteners and allowing for a smoother release with less mess.

APPLICATIONS

Frozen Nuts & Bolts	Conve
Chains	Froze
Corroded Fasteners	Beariı
Equipment Disassembly	Screw
Hinges	Pulley
Plumbing Fixtures	Engin
Shafts	Relays

eyors n Gears & Cogs ngs /S VS es & Electric Motors S

H2

NET CONTENTS	CONTAINER TYPE	UNITS/CASE	LPS #
13 wt. oz./369 g/417 mL	aerosol	12	92316



INDUSTRIAL LUBRICANTS







Water-Based Lubricant & Protectant

This silicone-rich, water-based lubricant eliminates sticking, binding and squeaking. The formula dries to a clear, thin film that

protects pieces. Particularly effective for rubber and plastic parts, this product can also be used on metal. Free of chlorinated solvents, this formula is colorless and odorless. Ideal alternative for petroleum-based lubricants.

APPLICATIONS

Cables	Rubber Mountings	
Castors	Seals	
Moving Plastic Parts	Sprockets	
O-Rings	Valves	
Plastic Gears	Ignition Systems	
Plastic Rollers	Switch Gears	
Rubber Bushings	Relays	

			/
NET CONTENTS	CONTAINER TYPE	UNITS/CASE	LPS #
13 wt. oz./369 g/439 mL	aerosol	12	91516

ELIMINATES BINDING/ PROVIDES RUBBER & PLASTIC PARTS PROTECTION



LPS[®] MAX ChainMate[®]

Lubricant, Penetrant & Protectant

Severe loads and extreme temps are no match for this moly-fortified formula that provides lubrication and protection for chains and wire ropes. Containing water-displacing solvents, the anti-sling formula quickly penetrates and provides friction and corrosion protection with less mess.

APPLICATIONS

≣

Bushings	Forklifts
Cables	Pins
Chains	Pulleys
Cranes	Rollers
Cutting Tools	Saws
Drag Lines	Sprockets
Drives	Wire Ropes

NET CONTENTS	CONTAINER TYPE	UNITS/CASE	LPS #
11 wt. oz./312 g/405 mL	aerosol	12	92416

LUBRICATES CHAIN/ WIRE ROPE FOR EXTREME LOADS & TEMPERATURES



Catterne Loades & Temperaturés Mazile Provides Targeted or Broad Strike Application Cattered Can for Improved Hand Gib Desender Breiter research and the Maxie Research and the Cattered Strike Maxie Research and the Cattered Strike Maxie Research and the Cattered Strike Research and the Cattered Strike Third Cattered Strike Str

INDUSTRIAL DEGREASERS



LPS® MAX Instant Super Degreaser 2.0 Non-Flammable



Industrial Degreaser

An industrial-strength degreaser for extreme applications formulated with worker safety in mind. The fast-evaporating formula contains no brominated solvents, trichloroethylene or perchloroethylene for an improved health and safety profile. And no residue means no rinsing or wiping is needed to keep the project moving.

APPLICATIONS

Air Compressors	Forklifts
Bearings	Gears
Cables	Heavy Equipment
Chains	Power Tools

NET CONTENTS	CONTAINER TYPE	UNITS/CASE	LPS #
20 wt. oz./567 g/437 mL	aerosol	12	97220

INDUSTRIAL FORMULA FOR EXTREME DEGREASING

Avoid harsh chlorinated & brominated chemicals with







LPS[®] MAX PreSolve[®] ≣ **Industrial Orange Degreaser**

Grease, grime and oil are no match for this industrial-strength, orange degreaser. The formula works on



contact to quickly dissolve and remove grime. Safe on all metals and most plastics, this product features controlled evaporation and leaves little residue behind.

APPLICATIONS

REMOVES GRIME

WITH MAX SPEED

Air Compressors	Forklifts
Alternators	Gears
Bearings	Heavy Equipment
Chains & Cable Connections	Power & Air Tools
Cranes	Printing Presses
Engines	Pulleys

NET CONTENTS	CONTAINER TYPE	UNITS/CASE	LPS #
15 wt. oz./425 g/523 mL	aerosol	12	91420



INDUSTRIAL ELECTRONIC CLEANERS



LPS® MAX NoFlash® 2.0 **Non-Flammable Contact Cleaner**

This non-flammable, industrial-strength Nonfood Compounds contact cleaner is formulated with worker safety in mind. The fastevaporating formula contains no brominated solvents for an improved health and safety profile. And no residue means no rinsing or wiping is needed to keep the project moving.

NSF

K2

APPLICATIONS	
Contacts	Instrumentation
Contacts Controls Sensors	Meters
Sensors	
· / / /	

NET CONTENTS	CONTAINER TYPE	UNITS/CASE	LPS #
12 wt. oz./340 g/268 mL	aerosol	12	97416

HEAVY DUTY, LOW VOC FORMULA

Avoid harsh chlorinated & brominated chemicals with



asha CONTACT CLEANER LIMPIADOR DE CONTACTOS NO INFLAMABLE Heavy Duty, Low VOC Formula Nozzle Provides Targeted or Broad Stroke Application Can for Improved Hand Grip

Net Contents / Contenido Neto: 12 wt oz/340g



LPS[®] MAX CFC Free **Contact Cleaner**



K2

A fast evaporating contact cleaner that Nonfood Compounds does not contain HCFCs and is plastic safe. The formula penetrates to remove

oil, grease, dirt, flux and other contaminants. Leaves no residue and is low-odor.

APPLICATIONS

	Cables	Power Tools
	Circuit Breakers	Hinges
	Electric Motors	Sliding Mechanisms
	Electronic Connectors	Ignition Systems
	Molds	Switch Gears
Ă.	Nuts & Bolts	Relays
	Locks	

NET CONTENTS	CONTAINER TYPE	UNITS/CASE	LPS #
11 wt. oz./312 g/465 mL	aerosol	12	93116



LPS® MAX CFC Free NU Low VOC Contact Cleaner

This residue-free, fast-drying formula contains no chlorinated solvents and is safe on plastics. The low VOC formula



removes dirt, moisture, dust, flux and oxides from the internal components of electronic or precision equipment such as circuit boards. Conforms to VOC regulations of CARB, OTC and LADCO.

APPLICATIONS

Connectors	Semiconductor Assemblies
Contacts	Switches
Magnetic Tap Heads	Telecommunication
Printed Circuits	Equipment
Office Equipment	

NET CONTENTS	CONTAINER TYPE	UNITS/CASE	LPS #
11 wt. oz./312g/416 mL	aerosol	12	95416

MEETS AIR QUALITY STANDARDS & PLASTIC-SAFE



FAST EVAPORATING FORMULA, SAFE **ON PLASTICS**



