

1. Identification

Product Identifier Clear Seal Solvent Based

Other means of

identification HS-2450

Product code

Recommended use Solvent based sealer for stone and grout.

Recommended restrictions Professional use only. **Manufacturer/distributor/supplier/importer information**

Company name Harper Supply LLC

Address 8821 Knight Rd

Houston, TX 77054

nousion, ix //os

Telephone (817) 529-1091

Emergency phone number PERS (800) 633-8253

24-hour Emergency (800) 633-8253

2. Hazard(s) Identification

Physical hazardsFlammable LiquidsCategory 3Health hazardsEye irritationCategory 2AAspiration HazardCategory 1

Environmental hazards Not classified.

OSHA defined hazards None.

Label elements







Signal word DANGER

Hazard statement Flammable liquid and vapor.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/ hot surfaces. No smoking. Keep container

tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take

precautionary measures against static discharge. Wear protective gloves/ eye protection/

face protection. Wash hands and exposed skin thoroughly after handling.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower. In case of fire: Use dry sand, dry chemical, or alcohol-resistant foam for

extinction.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

IF SWALLOWED: Immediately call a POISON CENTER/doctor/medical professional. Do NOT

induce vomiting.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Material Name: Clear Seal Solvent Based Page 1 of 8 SDS US



Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazard(s) not otherwise classified (HNOC)

None.

Supplemental information

None

3. Composition/information on ingredients

Mixture Component(s)			
Chemical name	CAS number	%	
Hydrotreated heavy naphtha	64742-48-9	89-95	
Fluorinated alcohol surfactant	Mixture	6-8	
Other components below reportable levels		1-5	

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water for at least 15 minutes. Remove contact lenses if present and easy to do so.

Get medical attention if irritation develops and persists.

Dermatitis. Rash. May cause an allergic skin reaction.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Only induce vomiting at the instruction

of medical personnel.

Most important

.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information

Provide widespread support measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to the affected area. Call an ambulance. Continue flushing during transport to the hospital. Keep the victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Carbon dioxide (CO₂). Dry chemical powder, sand, or earth may be used for

small fires only.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source or ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding

procedures. During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for

firefighters

Self-contained breathing apparatus and full protecting clothing must be worn in case of fire.

Material Name: Clear Seal Solvent Based Page 2 of 8 SDS US



Fire-fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment, and emergency procedures Keep unnecessary personnel away. Keep people away from upwind spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mist. Ensure adequate ventilation. Remove all sources of ignition. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources. Use only non-sparking tools. Take precautionary measures against static discharge. Keep combustibles away from spilled material.

Large spills: Stop the flow of material if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewers, basements, or confined areas. Following product recovery, flush area with water.

Small spills: Absorb with earth, sand, or other non-combustible material and transfer to container for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original container for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the open environment. Avoid discharge into surface drainage paths and other areas not consistent with package labeling.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Do not smoke. Use explosion proof equipment and non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks, and open flame. Ground/bond container and equipment. Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Synthetic Isoparaffinic OSHA PEL 500 ppm (2,900 mg/m3) Hydrocarbon ACGIH TWA 350 ppm (1,800 mg/m3)

Biological limit values

No information.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust

Material Name: Clear Seal Solvent Based Page 3 of 8 SDS US



ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves Nitrile and polyvinylchloride polymers are suitable

barrier materials

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene When using do not smoke or use chewing tobacco. Always observe good personal hygiene considerations measures, such as washing after managing the material and before eating, drinking, and/or

smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical State Liquid.
Color Colorless.

Odor Characteristic petroleum

Odor threshold Not available.

pH Not available.

Melting/freezing point Not available.

Initial boiling point and

300-410°F (148.9-210°C) - estimated.

boiling range

Flash point 120°F (37.8°C) - estimated.

Evaporation rate Not available.
Flammability Not available.

Flammability Limits

Upper6% estimated.Lower0.7% estimated.Vapor pressureNot available.Vapor densityNot available.

Specific gravity (water=1) 0.85

Solubility in water Insoluble.

Partition coefficient Not applicable

(n-octanol/water)

Auto-ignition temperature 540°F (282.2°C) -Estimated.

Decomposition temperature Not available. **Viscosity** Not available.

10. Stability and reactivity

Reactivity This product is stable and non-reactive under normal conditions of use.

Material Name: Clear Seal Solvent Based Page 4 of 8 SDS US



Chemical stability Material is stable under normal conditions. Store in a cool dark place.

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Avoid heat, sparks, open flames, and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Oxidizing agents, acids.

Hazardous decomposition

products

Carbon dioxide, carbon monoxide.

11. Toxicological information

Information on likely routes of exposure

IngestionExpected to be low ingestion hazard.InhalationProlonged inhalation may be harmful.

Skin contact May cause mild skin irritation.

Eye contact Causes serious eye irritation. Wear eye/face protection.

Symptoms related to the physical, chemical, and

toxicological characteristics

Dermatitis. Rash.

Acute toxicity Not established.

Product Clear Seal Solvent Based (CAS mixture)			
Exposure Classification	Route and Species	LD50 /LC50	
Acute	Oral, rat	>3,100 mg/kg (estimated)	
*Estimates for product may be based on additional component data not shown			

Skin corrosion/irritation Not classified.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitizationNot available.Skin sensitizationNot available.

Germ cell mutagenicity No data available to indicate product or any

components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not expected to be a carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not Listed

Reproductive toxicityThis product is not expected to cause reproductive or

developmental effects.

Specific target organ toxicity – single exposureNot classified.Specific target organ toxicity – repeated exposureNot classified.

Aspiration hazard May be harmful or fatal if product enters airways.

12. Ecological information

Ecotoxicity			
Product Clear Seal Solvent Based (CAS mixture)			
Aquatic Receptor	Species	Test ThreshOlds	
Crustacea	Daphnia magna (water flea)	EC ₅₀ (48-hr): 206 mg/L (estimated)	

Material Name: Clear Seal Solvent Based Page 5 of 8 SDS US



Fish	Fathead minnow	LC ₅₀ (96-hr): 90 mg/L (estimated)
*Estimates for product may be based on additional component data not shown		

Persistence and degradability No data available. Chemicals of this class are not expected to exhibit persistence in the

environment due to volatility and readiness to accept oxidation in an aerobic environment.

Bio-accumulative potential Potential to bioaccumulation is expected to be moderate due to lipophilic nature of organic

solvent constituents

Mobility in soil No data available. Chemicals of these classes are expected to exhibit moderate to high

mobility in saturated and semi-saturated soils. Low density of the product constituents is expected to result in LDNAPL phase separation of product above the static water table

Other adverse effects Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose of sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations. As packaged, this product is expected to

meet criteria defining RCRA ignitable (D001) hazardous wastes when disposed. (40 CFR Part 261, Subpart C). Before selecting disposal method, ensure that the waste materials have been

accurately assessed and, as necessary, tested to confirm regulatory status.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer, and the

waste disposal company. Suggested federal code is D001 (ignitable waste)

Waste from residues/unused

product

Dispose of it in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. (See:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may contain product residue, follow label warnings even after

container is emptied.

14. Transport information

USDOT

UN number UN1268

UN proper shipping name Petroleum Distillates Mixture, n.o.s (Naphtha)

Transport hazard class(es)

Class 3
Subsidiary risk -

Packaging group III

Special precautions for user Read safety instructions, SDS, and emergency procedures before handling.

Marine pollutant No

Special precautions for user

Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC Code

DOT Label/Placard

This product is not intended to be transported in bulk.

Material Name: Clear Seal Solvent Based Page 6 of 8 SDS US





15. Regulatory information

US Federal regulations

SARA 302 Extremely hazardous substance Not listed.

SARA 304 Emergency release notification Not listed.

SARA 311/312 Hazard Categories

Immediate Hazard - Yes
Delayed Hazard – Yes
Fire Hazard – Yes
Pressure Hazard – No

Reactivity Hazard – No

SARA 313 (TRI reporting) Not listed.

California Proposition 65

WARNING: This product can expose you to chemicals Napthalene and Ethylene Glycol Monoethyl Ether, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

16. Other information, including date of preparation or last revision

Issue date 11/8/2023

Revision date

Version # 1

HMIS® ratings Health: 1

Flammability: 2 Physical hazard: 0





NFPA ratings Health: 1

Flammability: 2
Instability: 0



Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge and

has been obtained from resources believed to be reliable. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified by the text.

Revision information First issue.