



MARCH SCOPES CANADA

207-3916 64 Ave SE Calgary AB T2C 2B4

WWW.MARCHSCOPES.CA 403 236 0032 doug@marchscopes.ca

TORQUE SPECIFICATIONS

For all March Scopes, the manufacturer recommends a torque of 17 inch pound for tightening the screws that hold the cap to the lower half of the scope ring. A torque in the range of 15 inch pound to 18 inch pound is permissible.

Torque conversion Chart Inch-Pounds to Newton-Meters

in lbs	N m	in lbs	N m	in lbs	N m	in lbs	N m	in lbs	N m
10	1.13	25	2.82	40	4.52	55	6.21	70	7.91
11	1.24	26	2.94	41	4.63	56	6.33	71	8.02
12	1.36	27	3.05	42	4.75	57	6.44	72	8.13
13	1.47	28	3.16	43	4.86	58	6.55	73	8.25
14	1.58	29	3.28	44	4.97	59	6.67	74	8.36
15	1.69	30	3.39	45	5.08	60	6.78	75	8.47
16	1.81	31	3.50	46	5.20	61	6.89	76	8.59
17	1.92	32	3.62	47	5.31	62	7.01	77	8.70
18	2.03	33	3.73	48	5.42	63	7.12	78	8.81
19	2.15	34	3.84	49	5.54	64	7.23	79	8.93
20	2.26	35	3.95	50	5.65	65	7.34	80	9.04
21	2.37	36	4.07	51	5.76	66	7.46	81	9.15
22	2.49	37	4.18	52	5.88	67	7.57	82	9.26
23	2.60	38	4.29	53	5.99	68	7.68	83	9.38
24	2.71	39	4.41	54	6.10	69	7.80	84	9.49