

SliX PRINGS

SliX-Scraper

The SliX-Scraper is a tool to clean and restore .357 Mag, .44 Mag, .45 Colt and .327 Fed. Mag, Chambers and cylinder throats. It removes carbon and lead fouling. It is especially helpful for removing the ring of residue left after using shorter (aka. "Special") versions of these cartridges. It will not harm or alter the original chamber dimensions.

Instructions:

Caution: All SliX-Scraper are to be used with the appropriate caliber rifle and pistol. TK4B is not responsible for any occurrence resulting from any user other than the recommended caliber.

Rifles:

- 1) Place SliX-Scraper into the rifle chamber.
- 2) Insert a standard 8-32 UNC threaded cleaning rod down the bore and thread rod onto the scraper.
- 3) Turn to the RIGHT while GENTLY pulling on the rod.
- 4) When SliX-Scraper has fully seated into the chamber, remove cleaning rod and scraper from chamber.

Revolvers:

- 1) Remove cylinder from revolver.
- 2) Insert SliX-Scraper into the chamber.
- 3) Use a Screwdriver and Turn to the LEFT. Do NOT apply much pressure with the screwdriver. Let the scraper do the work.
- 4) When SliX-Scraper has fully seated into the chamber, remove scraper from chamber.
- 5) Repeat until all cylinder chambers have been cleaned.

All TK4B SliXprings Products are Proudly Made in the USA!!

TK4B Enterprises, LLC is a Limited Liability Corporation Licensed in the State of Oregon.