





SPECIFICATIONS

Length 30' Width 95"

Running Gear Two 12,000 lb. duel wheel axle with oil bath hubs

Brakes 12 1/4" x 5" electric with self-charging break-away system

Landing Gear 12,000 lb. static drop leg jack

Wheels 16" 8-hole Steel Tires 235/80R 16" 14-Ply

Frame $10" \times 4" \times 1/4"$ A500 rectangular tubing

Coupling System 42,000 lb capacity \times 2 $\frac{1}{2}$ " pintle eye, adjustable in 2 $\frac{1}{4}$ " increments

Lights Sealed beam with waterproof wiring in nylon tubing

G.V.W.R. 27,500 lbs. **Empty Weight** 7500 lbs.

Payload Approximately 20,000 lbs.

Configuration Model built as shown will hold a: 36", 48", 42", 54", 60" & 72". However, it can be

built to custom configurations to fit your needs

Misc. Can safely secure both core bits as well as conventional augers, tie down chains,

boomer ratchet binders, wheel chocks, safety chains, slide in tube stanchions,

Kelly staub tie downs, toolboxes

OPTIONS

15,000 lb. Axle / Additional length / Electric over hydraulic disc or drum brakes / Custom paint color Additional auger storage / Custom layouts