


Model 4K4DP



4K 4 DRUM OVERHEAD PULLER

DIMENSIONS AND WEIGHTS

Length: 21' **Width:** 101" OAW
Height: 9' 3" **G.V.W.R.:** 23,000 lbs.
Empty Weight: 15,500 lbs.
Payload: Approximately 7,500 lbs.

UNIT PERFORMANCE

Continuous Torque Rating: 108,000 in. lbs
Line Speed: 4 mph average
Actual Full Drum Pull Rating: 4,000 lbs

PULLING REEL SPECIFICATIONS

Quantity: Four **Reel Diameter:** 54" OD
Reel Inside Width: 31 1/2"
Core Diameter: 10 3/4"
Line Capacity:
 15,000 ft. of 5/8" synthetic rope
Reel Brakes: Hydraulic actuated caliper from operator station with 30" diameter Disc
Reel Engagement: Mechanical clutch engage with lockout function

STANDARD FEATURES

Engine: 74 hp water cooled diesel
Levelwind: Four independent electric over hydraulic levelwind arms that can be manually operated or auto adjusting
Running Gear:
 Two 10,000 lb. single wheel axle with oil bath hubs
Brakes:
 12 1/4" x 3-3/8" electric with self-charging break-away system
Landing Gear/Outriggers: Three independent electric over hydraulic 10,000 lb. hydraulic jacks that can be manually operated with built in function of an automatic leveling
Wheels: 17" Steel Disc
Tires: 235/75R 17.5" 18-Ply
Frame:
 6x4 frame with 6x3 reel supports

Lights: Sealed beam with waterproof wiring in nylon tubing

Controls: Electric over hydraulic joystick for payout and take up. HP limiting function to allow operator maintainable line speed from full drum to empty drum. 11" touch screen for operating and monitoring. Manual and automatic levelwind joystick paddles. Custom keypads for hydraulic jack and engine operations on console and at lower level for convenient access.

Pressure Control:
 Hydraulic pressure control valve

Hydraulics: Closed loop hydrostatic hydraulic drive. Integrated 4.4 gal hydraulic tank and cooler. Hydraulic gearbox with sprocket chain driven drums. Emergency shut down feature for operator safety