## SECOND IN UNIT TRENCH RESCUE

## MABAS Division 2 Operational Checklist #32-F

**Reviewed 1/30/17 Reviewed 6/23/21** 

Responsibilities	Ensure all Fire Department personnel, co-workers, family members, and bystanders do not enter	Establish and secure "Hot Zone" perimeter with barricade tape a minimum of 50'x50' around trench
	Establish "Warm" and "Cold" zones	Keep spectators, unnecessary personnel, and unnecessary apparatus and equipment a minimum of 300' away from the "Hot Zone"
	Request PD assistance with site control and rerouting or stopping of traffic, including air traffic, from vicinity of trench site	Shut down all devices capable of causing vibrations within 300'of the "Hot Zone"
	Do not allow the use of backhoes, etc. to be used in the rescue effort	Shut down all unnecessary devices capable of causing adverse changes in the atmospheric conditions near the trench (i.e., exhaust producing equipment)
	Consider wind direction and its effect on vehicle exhaust travel	Ensure the elimination of potential ignition sources
	Ensure fire protection is in place when potentially flammable atmospheres exist	Ensure all systems (electrical, pneumatic, hydraulic, gravity, etc.) not needed in or around the trench are rendered safe from accidental start-up
	If positive lockout control is not possible, a guard shall be posted at the controls to ensure a "zero mechanical state"	Ensure access for Technical Rescue Team vehicles and personnel
	Ensure adequate site access for placement of TRT equipment near trench	Ensure ambulance access to the site
	Ensure adequate exterior lighting.	Assist in moving superimposed loads