



JOMON
PERSADA
NUSANTARA

DEWATERING PUMP CATALOG





Description	PUMP, PAC H64, SKID, FSC03, 1940x3250 x2155 MM
Part Number	JAAA0113
Qmax	128 l/s - 460 m ³ /h - 7.670 l/min (2,030 USgpm)
Hmax	153 m (508 ft)
Q max eff.	146 l/s - 525 m ³ /h - 8.750 l/min (2,300 USgpm)
Eff. max	69%
Suction port	6" Flange
Delivery port	4" Flange
Impeller type	Closed, 2 vane
Impeller diameter	17"
Solids handling	3"
Vaccum pump type	Diaphragm
Nominal air capacity	85 m ³ /h (50.0 cfm)
Max Vaccum	0,9 bar
Engine	5 Cylinders, Water Cooled, Diesel Engine
Dimensions	1940 x 3250 x 2155 mm
	76 x 128 x 85"



Description	DEWATERING PUMP, ATLAS COPCO, PAC H108, 325HP, SKID
Part Number	JAAB0110
Qmax	408 l/s - 1.470 m ³ /h - 24.500 l/min (6,470 USgpm)
Hmax	109 m (358 ft)
Q max eff.	272 l/s - 980 m ³ /h - 16.300 l/min (4,310 USgpm)
Eff. max	82%
Suction port	10" Flange
Delivery port	8" Flange
Impeller type	Enclosed, 2 vane
Impeller diameter	17"
Solids handling	3.5"
Vaccum pump type	Diaphragm
Nominal air capacity	85 m ³ /h (50.0 cfm)
Max Vaccum	0,9 bar
Engine	5 Cylinders, Water Cooled, Diesel Engine
Dimensions	1970 x 3250 x 2150 mm
	77 x 128 x 84"



OUR WEBSITE



Phone: +6221 2294 6465

Email: sales@jomonindonesia.com

**Address: Central Cakung Business Park Blok G2
No. 1-2, Jl. Cakung Cilincing Raya KM. 3, Rorotan,
Cilincing, Jakarta Utara, Indonesia - 14140**



PT Jomon Persada Nusantara



@jomonindonesia