


AUTOMATIC WASHER-DISINFECTOR



Working principle and function

HUAXI automatic washer disinfecter is carefully designed and manufactured in strict accordance with the requirements of the Ministry of Health of the People's Republic of China "technical operation specification for cleaning, disinfection and sterilization of hospital disinfection and supply center". The whole decontamination process is automated, which greatly reduces the labor intensity to meet the strict demand of hospital supply center.

By equipping with different cleaning racks, HUAXI washer-disinfecter realizes the cleaning and disinfection of various types of instruments. It is balanced and perfect in terms of functionality and reliability, and can adapt to complex and diverse cleaning and disinfection environment.



- Excellent decontamination effect**
 Excellent cleaning and disinfection effect which fully conforms to the current relevant norms or standards
- Excellent loading capacity**
 Can be equipped with four layers of instrument cleaning rack, which greatly improves the loading capacity
- Strong energy saving effect**
 Using a large number of water circulation and spray system, greatly saving the consumption of water and energy
- Convenient operation interface**
 Using touch screen control system, the operation interface is very user-friendly, and the program setting is simple and easy
- Excellent record keeping ability**
 Detect and record the operation data of the whole cycle, and print the data directly

- **Operation interface:** 7-inch HD touch screen
- **Cleaning procedures:** 36 standard procedures
- **Cabin door:** automatic door opening and closing
- **Cleaning capacity:** $\geq 480L$
- **Basket:** ICA modular basket
- **Maximum cleaning temperature:** $\geq 95^{\circ}C$
- **Single cleaning amount:** depends on the number of layers of the basket
- **Double circulation pump flow rate:** 1300L / min
- **Heating power:** 27kw
- **Drying power:** 4kw

Type	Dimensions LxWxH	Basket Layer	Voltage AC	power kW	Shell Material	Chamber Material
HX/RWD-308	935x775x1385	1~3	380 50Hz	24	304 stainless steel	316 stainless steel
HX/RWD-480	1250x1105x2350	1~4	380 50Hz	30	304 stainless steel	316 stainless steel

Note: All dimensions are in mm, the product will be configured according to the demand in actual production, parameters are for reference only.