GRAVITY AUTOCLAVE





Control system

Stable performance, can consult or output through printer

7 inch Touch screen, clear and easy to operate

Three levels of operation password to ensure the operation authority at all levels

Configuration

Automatic vertical lift door

Sanitary stainless steel pipe with stainless steel high temperature steam filter Adopt high quality imported Italian zero pressure start solenoid valve

I Technical performance

Automatic water filling, low water level alarm prompt
The double door interlock is opened after sterilization
Function and solution of automatic fault prompt

Safety performance

Automatic protection of leakage current and over current

Ultra high temperature, ultra low temperature, overpressure, water shortage alarm Release the safety interlock function of sealed quick opening door

ICS 11.020 C 05



中华人民共和国卫生行业标准

WS 310.2—2016 代替 WS 310.2 2009

医院消毒供应中心 清洗消毒及灭菌技术操作规范

 $\label{lem:control} Central \ sterile \ supply \ department \ (CSSD) —$ Standard for operating procedure of cleaning-disinfection and sterilization









Water processor

Filter

Stainless steel pipe





High temperature resistant sealing ring

Controller

Model	Dimension(L×W×H)(cm)	Chamber Dimension(cm)	Cleaning Capacity(L)	Voltage	Power(kw)	Note
HX-60BS-3E	140×80×172	φ 60×100	300	three-phase	12	Single door, Gravity, Operation via button
HX-60BS-3	140×80×175	φ 60×100	300	three-phase	12	Single door, Gravity, LCD Touch screen
HX-60BD-3	140×80×175	φ 60×100	300	three-phase	12	Double door, Gravity, LCD Touch screen
HX-60×70BS-4	121×97×175	$60 \times 70 \times 100$	400	three-phase	18	Single door, Gravity, LCD Touch screen
HX-60×70BD-4	121×97×175	$60 \times 70 \times 100$	400	three-phase	18	Double door, Gravity, LCD Touch screen
HX-60×70BS-5	145× 97×175	60×70×120	500	three-phase	21	Single door, Gravity, LCD Touch screen
HX-60×70BD-5	145× 97×175	$60 \times 70 \times 120$	500	three-phase	21	Double door, Gravity, LCD Touch screen
HX-65×78BS-6	145×110×185	$65 \times 78 \times 120$	600	three-phase	27	Single door, Gravity, LCD Touch screen
HX-65×78BD-6	145×110×185	65×78×120	600	three-phase	27	Double door, Gravity, LCD Touch screen
HX-65×78BS-8	175×110×185	65×78×150	800	three-phase	33	Single door, Gravity, LCD Touch screen
HX-65×78BD-8	175×110×185	65×78×150	800	three-phase	33	Double door, Gravity, LCD Touch screen
HX-75×105BS-12	185×195×176	75×105×150	1200	three-phase	43	Single door, Gravity, LCD Touch screen
HX-75×105BD-12	185×195×176	75×105×150	1200	three-phase	43	Double door, Gravity, LCD Touch screen

Note: The product will be configured according to the demand in actual production, parameters are for reference only.