

PULSE VACUUM AUTOCLAVE



HUAXI 

Control system

- Stable performance, can consult or output through printer
- 7 inch Touch screen, clear and easy to operate
- Three levels of operation password to ensure the operation authority at all levels

Configuration

- Automatic vertical lift door
- Sanitary stainless steel pipe with stainless steel high temperature steam filter
- Adopt high quality imported Italian zero pressure start solenoid valve

Technical performance

- Automatic water filling, low water level alarm prompt
- The double door interlock is opened after sterilization
- Function and solution of automatic fault prompt

Safety performance

- Automatic protection of leakage current and over current
- Ultra high temperature, ultra low temperature, overpressure, water shortage alarm
- Release the safety interlock function of sealed quick opening door

ICS 11.020
C 05

WS

中华人民共和国卫生行业标准

WS 310.2—2016
代替 WS 310.2 2009

医院消毒供应中心
清洗消毒及灭菌技术操作规范

Central sterile supply department (CSSD)—
Standard for operating procedure of cleaning, disinfection and sterilization



Water processor



Filter



Stainless steel pipe



High temperature
resistant sealing ring



Controller

Model	Dimension (L×W×H) (cm)	Chamber Dimension (cm)	Cleaning Capacity (L)	Voltage	Power (kw)	Note
HX-60BS-3P	140×80×175	Φ 60×100	300	three-phase	15	Single door, Pulse Vacuum
HX-60BD-3P	140×80×175	Φ 60×100	300	three-phase	15	Double door, Pulse Vacuum
HX-60×70BS-4P	125×97×175	60×70×100	400	three-phase	18	Single door, Pulse Vacuum
HX-60×70BD-4P	125×97×175	60×70×100	400	three-phase	18	Double door, Pulse Vacuum
HX-60×70BS-5P	145× 97×175	60×70×120	500	three-phase	21	Single door, Pulse Vacuum
HX-60×70BD-5P	145× 97×175	60×70×120	500	three-phase	21	Double door, Pulse Vacuum
HX-65×78BS-6P	145×110×185	65×78×120	600	three-phase	27	Single door, Pulse Vacuum
HX-65×78BD-6P	145×110×185	65×78×120	600	three-phase	27	Double door, Pulse Vacuum
HX-65×78BS-8P	176×110×185	65×78×150	800	three-phase	33	Single door, Pulse Vacuum
HX-65×78BD-8P	176×110×185	65×78×150	800	three-phase	33	Double door, Pulse Vacuum
HX-75×105BS-12P	185×195×176	75×105×150	1200	three-phase	43	Single door, Pulse Vacuum
HX-75×105BD-12P	185×195×176	75×105×150	1200	three-phase	43	Double door, Pulse Vacuum

Note: The product will be configured according to the demand in actual production, parameters are for reference only.