



# WEBB MULTICLASS READER

## RFID CARDS, NFC & BLUETOOTH

### FEATURES AND BENEFITS

- RFID, Bluetooth® and NFC secure identification
- Discreet and elegant integration
- Easy installation on door frames and narrow electrical pots
- Retro compatible and interoperable



**MULLION READER**



**SINGLE-GANG READER**

#### TYPICAL APPLICATIONS

- Residential
- Commercial
- Industrial
- Instructional
- Garage Gates
- Elevators
- Hospitals
- Universities
- Seniors Homes



**Hands Free Mode**— by simply passing in front of the reader



**Card Mode**— by placing your smartphone in front of the reader



**Voice Control Mode** — by using voice command on your iPhone (iOS)



**Tap Tap Mode**— by tapping your smartphone twice in your pocket for near or remote opening



**Remote Mode**— by using your smartphone as a remote control

**Description:** It's optimized design ensures perfect integration, whatever the installation environment and without additional spaces (even on metal). The pluggable cable and the mounting base make it very easy to install. **Virtual cards** promote acceptance of and compliance with the security policy of businesses, industries and governments.

### Ordering Information

**WEBB MULLION READER—**  
(W/O) Wiegand or OSDP

Webb Connects to existing access control or Webb Access WAC-1001

**WEBB SWITCH PLATE READER—**  
(W/O) Wiegand or OSDP

Webb Connects to existing access control or Webb Access WAC-1001





# WEBB MULTICLASS READER

## RFID CARDS, NFC & BLUETOOTH

### Additional Features:

<b>Features:</b>	<b>Description:</b>
<b>Operating frequency</b>	13.56: ISO 14443 types A&B, ISO18092
<b>Chip Compatibility</b>	Webb Multiclass Reader RFID CARDS, NFC & BLUETOOTH
<b>Functions</b>	Insert any mpeg or Avi files
<b>Communication interfaces and protocols</b>	OSDP or Wiegand
<b>Decoder Compatibility</b>	Compatible with EasySecure interface ( encrypted communication)
<b>Reader Distances</b>	Up to 6cm/ 2.36" with MIFARE DESFire EV2 or Classic card Up to 20m/65.6ft with Bluetooth Smartphone ( adjustable distances on each reader)
<b>Data Protection</b>	Yes—Software protection and EAL5+ crypto processor for secure data storage.
<b>Light Indicator</b>	2 RGB LEDs—360 colors configurable by card software or controlled by external command.
<b>Audio Indicator</b>	Integrated buzzer with adjustable intensity
<b>Power</b>	150 mA/12VDC Max 9VDC to 15 VDC
<b>Connectors</b>	Cable with plug connector 3m/9.8ft
<b>Material</b>	ABS-PC UL -V0 (Black) / ASA-PC-UL-V0 (White)
<b>Temperatures</b>	-30 °C at 70 °C/ -22°F to 158 °F
<b>Tamper Switch</b>	Accelerometer-based tamper detection system with key deletion and/or message to the controller.
<b>Water Resistance</b>	IP65 level Weather, water and dust resistant
<b>Mounting</b>	Wall-mounted, on door jambs and on narrow electrical junction boxes. Mount on any type of support including metal without spacer.
<b>Warranty</b>	2 year warranty