

# CRIMPING MACHINERY

Price including Handling and Shipping to Any major sea port worldwide



**Crimping Range: 10-65 mm**

**Model: S32**

Hydraulic Hose : 1 1/2" hose

System Power: 2.2KW ABB

Opening: +24mm

Width: 450 mm Length:550 mm Height: 900mm Weight:280KG

Die sets with machine: 10 14 17 20 24 28 33 38 44 (mm)

Voltage Option: 220V/380V/400V/415V/440V/660V 3 phase;

220V/230V/240V single phase; 12V/24V DC for Mobile Van Service



**Crimping Range: 10-87 mm**

**Model: S51**

Hydraulic Hose : 2" 4SP/4SH

System Power: 3KW ABB

Opening: +24mm

Width: 450 mm Length:550 mm Height: 950mm Weight:330KG

Die sets with machine: 10 14 17 20 24 28 33 38 44 50 56 62 68 (mm)

Voltage Option: 220V/380V/400V/415V/440V/660V 3 phase;

220V/230V/240V single phase; 12V/24V DC for Mobile Van Service



**Crimping Range: 10-87 mm**

**Model: P32**

Hydraulic Hose : 2" 4SP/4SH

System Power: 3KW ABB

Opening: +34mm

Control: PLC touch screen control precision to 0.01mm

Width: 550 mm Length:650 mm Height: 950mm Weight 280KG

Die sets with machine: 10 13 16 19 22 26 30 39 45 51 57 63 69 (mm)

Voltage Option: 220V/380V/400V/415V/440V/660V 3 phase;

220V/230V/240V single phase; 12V/24V DC for Mobile Van Service



**Crimping Range: 10-120 mm**

**Model: P51**

Hydraulic Hose : 2 1/2" 4SP or 4" Industrial Hose

System Power: 4KW ABB

Opening: +46mm

Control: PLC touch screen control precision to 0.01mm

Width: 650 mm Length:750 mm Height: 1150mm Weight 380KG

Die sets with machine: 10 13 16 19 22 26 30 39 45 51 57 63 69 (mm)

Voltage Option: 220V/380V/400V/415V/440V/660V 3 phase;

220V/230V/240V single phase



**Crimping Range: 10-140mm**

**NEW Model: FP140**

Hydraulic Hose : 2 1/2" 4SP , 2" 6SH

**Industrial hose to 4"**

System Power: 5.5KW ABB

Opening: +86mm

Control: PLC touch screen control precision to 0.01mm

Width: 900 mm Length:1000 mm Height: 1650mm Weight: 1250 KG

Die sets with machine: 10 13 16 19 22 26 30 39 45 51 57 63 69

Voltage Option: 220V/380V/400V/415V/440V/660V 3 phase



**Crimping Range: 10-202mm** **Model: P80**  
**Industrial Hose: 6"**  
 Hydraulic Hose : 3"  
 System Power: 11 KW ABB  
 Opening: +50mm  
 Width: 800 mm Length:1000 mm Height: 1450mm Weight:750KG  
 Die sets optional according to drawing  
 Cotrol: PLC touch screen precision control  
 Voltage Option: 380V/400V/415V/440V/660V 3 phase



**Crimping Range: 10-320 mm** **Model: FP175**  
**Industrial Hose: 12"**  
 Hydraulic Hose : 6" 4SP/4SH  
 System Power: 11 KW ABB  
 Opening: +155mm  
 Width: 1200 mm Length:1500 mm Height: 2150mm Weight:4200KG  
 Die sets optional according to drawing  
 Voltage Option: 380V/400V/415V/440V/660V 3 phase  
 Cotrol: PLC touch screen precision control  
 Pressure sensor optional (stop by pressure not diameter)  
 Acoustic sensor monitor (For insulators defects detecting)



**Cutting Range: 2" 4SP hydraulic hose** **Model: SC50**  
 Cutting blade diameter:400mm  
 Standard : Pedal force ; Option: Air Force  
 Power:3.37KW by ABB 220V/380V/400V/415V/440V/480V 3 phase  
 Width/Length/Height/Weight:400mm/1000mm/1000mm/150KG  
 Ventilation system is standard for in-house dust and smoke control.



**Skiving Range: 2" 4SP hydraulic hose** **Model: SS50**  
 Skiving up to 2" 4SP hydraulic hose  
 System Power: 0.37KW  
 220V/380V/400V/415V/440V/480V 3 phase or single phase  
 Width/Length/Height/Weight:500mm/600mm/1000mm/200KG  
 Tool included:1/4",1/2",3/4",1",1 1/4",1 1/2",1 3/4",2", 3/8".  
 Optional ineternal skiving tool (barely used so which is not standard)



**Crimping Range: 12-63** **Model:Nut Crimper NP-50**  
**Crimping Force: 85 ton**  
 System Power: 3 KW ABB  
 Opening: +26mm  
 Width: 450 mm Length:550 mm Height: 900 Weight:180KG  
 Die sets:12 14 16 19 22 26 30 34 39 45 51 57  
 Cotrol: Electrical, optional Precision PLC touch screen control  
 Optional Pressure sensor (stop by pressure not diameter)  
 Voltage Option: 380V/400V/415V/440V/660V 3 phase or  
 220V/230V/240V single phase.

NP-50  
NUT CRIMPING MACHINE