


Straight Guardrail Delineator

(Mounts to Guardrail Support Posts)

Easy Installation on Wood or Metal Posts

Reflective Sheeting*
 1Y --> Yellow 1-way
 2Y --> Yellow 2-way
 1W --> White 1-way
 2W --> White 2-way
 *Additional colors available by special order



(Cal Trans specification is 10" height)

The bodies shall be made from a high-impact, weatherable engineering thermoplastic .090 (min) thick that conforms to the following:

Property	Results	ASTM Test Method
Tensile Strength @ Yield (min. psi)	5,000	D638
Impact Strength @ 73°F (Ft #/in notch)	10.0	D256
Impact Strength @ -40°F	1.5	D256
Flexural Strength 1/4" @ 73°F	8,000	D790
Flexural Modulus 1/4" @ 73°F	24,000	D790

Reflective Sheeting Available	
ASTM D-4956 Spec	Traffic/Work Zone Colors
III/IV	White, Yellow, Blue, Green, Red, Brown
VIII	White, Yellow, Blue, Green, Red, Fluorescent Yellow, Fluorescent Yellow/Green, Fluorescent Orange
IX	White, Yellow, Blue, Green, Red, Fluorescent Yellow, Fluorescent Yellow/Green, Fluorescent Orange
XI	White, Yellow, Blue, Green, Red, Brown, Fluorescent Yellow, Fluorescent Yellow/Green, Fluorescent Orange

Straight Style

Straight Delineators may be mounted directly to wooden or metal guardrail support posts. Use 2-16 DG nails and 2 - 3/16 washers in predilled holes for wooden support post. Or Artuk adhesive Cement for metal support posts.