

Brake operation:- Foot 4 wheels.
 Hand Rear wheels
 Wheel Brake Drum, sizes 305 m/m
 Road springs, type Semi Elliptic
 Road springs, anchorage Silent bloc bushes (no lubrication required).
 Shock absorbers fitted Front and Rear
 Rear axle, type Semi-floating
 Tyres (Dunlop) size 29 x 5.25.
 Wheelbase and track. 9'6" x 4'8".
 Overall length and width 13'7" x 5'8½".
 Ground clearance. 8".
 Turning circle. 42'.
 Weight of coachbuilt saloon, Unladen (ready for road). 1 ton. 6¾ cwt.

BODY STYLES & PRICES.

Tourer) Beige & Maroon	£310
Safety Tourer) Grey & Blue	£325
) Fawn & Nutria	
Saloon) Maroon & Beige	£325
Safety Saloon) Blue & Grey	£375
) Nutria & Fawn	
+ Four Door Segrave Coupe	Green & Beige Black & Primrose	£385
+ Six Light Weymann Saloon	Brown Black & Red	£375
Drop Head Coupe) Maroon & Beige) Blue & Grey) Nutria & Fawn	£415

= + Sunshine Roof can be fitted at an extra charge of £10.
 N.B. Wire wheels can be fitted to Standard Models at an extra charge of £10.
 Artillery wheels can be substituted for wire wheels on Safety models.

BRAKES.

According to an early Ferodo Brake Lining Catalogue, the 1931 Hillman Fourteen had different sizes of linings from the 1930 model. This probably means the late 1930 Hillman Fourteen, so it is as well to check with one's own shoes before using these dimensions when ordering linings.

Front - Foot (4 shoes).

Drum diameter	12"
Length	13½"
Width	1½"
Thickness	¾"
Inside radius	5 23/32".

Rear - Hand & Foot (8 shoes)

Drum diameter	12"
Length	13½"
Width	1½"
Thickness	¾"
Inside radius	5 23/32"