

# **Material Safety Data Sheet**

Issuing Date 04-Apr-2007	Revision Date 25-Oct-2011	<b>Revision Number</b> 2
1.	PRODUCT AND COMPANY IDENTIFICATION	
Product Name	Mothers California Gold Brazilian Carnauba Cleaner Wax	
Product Code(s)	05500	
Recommended Use	Car care	
Supplier Address MOTHERS POLISHES WAXES CLEANERS 5456 Industrial Drive Huntington Beach, CA 92649 TEL: 714-891-3364 FAX: 714-893-1827		
Emergency Telephone Number	Chemtrec 1-800-424-9300	
	2. HAZARDS IDENTIFICATION	
WARNING!		
	Emergency Overview	
	May cause eye irritation ontact may cause allergic reactions in very susceptible persons lay cause sensitization by inhalation and skin contact May cause drowsiness and dizziness Harmful: may cause lung damage if swallowed May cause central nervous system depression	
Appearance Pink	Physical State Paste.	Odor Perfume
Potential Health Effects Principle Routes of Exposure	Skin contact. Eye contact. Inhalation.	
Acute Toxicity Eyes Skin	Contact with eyes may cause irritation. May cause sensitization by skin contact. Repeated exposure may cause s cracking. Repeated or prolonged skin contact may cause allergic reaction persons.	
Inhalation	May cause central nervous system depression with nausea, headache, di	izziness, vomiting,
Ingestion	and incoordination. May cause allergic respiratory reaction. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarr additional affects as listed under "Inhalation". Harmful: may cause lung da	
Chronic Effects	No known effect based on information supplied.	
Aggravated Medical Conditions	Skin disorders. Respiratory disorders. Central nervous system. Pre-existin Allergies.	ng eye disorders.
Interactions with Other Chemicals	Use of alcoholic beverages may enhance toxic effects. Irritants. Sensitize	ers. Epoxies.

**Environmental Hazard** 

See Section 12 for additional Ecological Information. May cause long-term adverse effects in the aquatic environment

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS-No	Weight %
Naphtha (petroleum), heavy alkylate	64741-65-7	25-50
Paraffinic, naphthenic solvent	64742-47-8	25-50
Calcined kaolin clay	66402-68-4	<10
Paraffin	8002-74-2	1-5
Turpentine	8006-64-2	<1

#### 4. FIRST AID MEASURES

General Advice	May produce an allergic reaction Immediate medical attention is not required. If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If symptoms persist, call a physician.
Skin Contact	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Move to fresh air. Get medical attention immediately if symptoms occur. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, give oxygen.
Ingestion	Rinse mouth. Drink plenty of water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately if symptoms occur.
Notes to Physician	May cause sensitization of susceptible persons. Use of epinephrine may be indicated Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

Flammable Properties		Combustible material: may burn but does not ignite readily.				
Flash Point		> 221.3°F / > 105°C				
Suitable Extinguishing I	Media	Carbon diox	Carbon dioxide (CO <sub>2</sub> ). Dry powder. Dry chemical. Foam.			
Unsuitable Extinguishin	ig Media	Do not use	a solid water strea	m as it ma	ay scatter and spread fire.	
Explosion Data Sensitivity to Mechanica Sensitivity to Static Disc	•	None None				
Specific Hazards Arising Chemical	g from the	Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer.				
Protective Equipment an Precautions for Firefigh		As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.			emand, MSHA/NIOSH	
NFPA	Health Haz	ard 2	Flammability 1		Instability 0	Physical and Chemical Hazards N/A
HMIS	Health Haz	ard 2	Flammability 1		Physical Hazard 0	Personal Protection B

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Avoid contact with skin, eyes and clothing. Use personal protective equipment. Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces to become very slippery.
Environmental Precautions	Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.
Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Cleaning Up	Dam up. Soak up with inert absorbent material. Keep in suitable and closed containers for disposal. Clean contaminated surface thoroughly. Prevent product from entering drains.

#### 7. HANDLING AND STORAGE

HandlingEnsure adequate ventilation. Wear personal protective equipment. Avoid contact with skin,<br/>eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.<br/>Keep away from open flames, hot surfaces and sources of ignition. Do not breathe vapors or<br/>spray mist. Remove and wash contaminated clothing before re-use. Wash thoroughly after<br/>handling. Do not eat, drink or smoke when using this product.StorageKeep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in<br/>properly labeled containers. Keep out of the reach of children.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Paraffin 8002-74-2	TWA: 2 mg/m <sup>3</sup>	(vacated) TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
Turpentine 8006-64-2	TWA: 20 ppm	TWA: 100 ppm TWA: 560 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 560 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 560 mg/m <sup>3</sup>
Calcined kaolin clay 66402-68-4	STEL: 10 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> Zr TWA: 0.2 mg/m <sup>3</sup> Mn	TWA: 5 mg/m <sup>3</sup> Zr (vacated) TWA: 5 mg/m <sup>3</sup> Zr (vacated) STEL: 10 mg/m <sup>3</sup> Zr	TWA: 5 mg/m <sup>3</sup> respirable dust TWA: 10 mg/m <sup>3</sup> total dust

Immediately Dangerous to Life or Health.

Engineering Measures	Showers Eyewash stations Ventilation systems
Personal Protective Equipment Eye/Face Protection Skin and Body Protection Respiratory Protection	Safety glasses with side-shields. Protective gloves. Long sleeved clothing. No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice. When using, do not eat, drink or smoke. Remove and wash contaminated clothing before re-use. Provide regular cleaning of equipment, work area and clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Threshold pH	Pink. No information available No information available.	Odor Physical State	Perfume. Paste
Flash Point Decomposition Temperature Melting Point/Range	> 221.3°F / > 105°C No information available. 64°C	Autoignition Temperature Boiling Point/Boiling Range	No information available. No information available
Flammability Limits in Air	No information available.	Explosion Limits	No information available.
Solubility Vapor Pressure VOC Content (%)	No information available. No data available. <45	Evaporation Rate Vapor Density	No information available No data available.

## **10. STABILITY AND REACTIVITY**

Stability	Stable under recommended storage conditions.
Incompatible Products	Strong oxidizing agents. Strong acids.
Conditions to Avoid	Heat, flames and sparks.
Hazardous Decomposition Products	Thermal decomposition can lead to release of irritating gases and vapors. Carbon oxides.
Hazardous Polymerization	Hazardous polymerization does not occur.

## **11. TOXICOLOGICAL INFORMATION**

#### Acute Toxicity

#### Product Information

Inhalation	May cause sensitization of susceptible persons. Avoid breathing vapors or mists. May cause central nervous system depression with nausea, headache, dizziness, vomiting, and incoordination.
Eye Contact	Contact with eyes may cause irritation.
Skin Contact	May cause sensitization by skin contact. Repeated exposure may cause skin dryness or cracking.
Ingestion	May cause drowsiness and dizziness

#### Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Poly(dimethylsiloxane)	> 17 g/kg (Rat)	> 2 g/kg (Rabbit)	
Paraffin	> 3750 mg/kg (Rat)	> 3600 mg/kg (Rabbit)	-
Fatty acids, montan-wax, ethylene esters	> 2000 mg/kg (Rat)		
Naphtha (petroleum), heavy alkylate	> 7000 mg/kg (Rat)	> 2000 mg/kg (Rabbit) > 3000 mg/kg (Rat)	> 5.04 mg/L (Rat)4 h
Paraffinic, naphthenic solvent	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
Turpentine	= 5760 mg/kg (Rat)		= 13700 mg/m³( Rat ) 4 h

#### **Chronic Toxicity**

#### Carcinogenicity

Occupational health effects due to inhalation of mineral dusts incorporating crystalline silica (quartz, cristobalite, tridymite), crystalline silicates (kaolin, talc) graphite or coal unlikely to occur from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Calcined kaolin clay		Group 2B		Х

IARC: (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans OSHA: (Occupational Safety & Health Administration) X - Present

Sensitization	May cause sensitization by skin contact.
Reproductive Toxicity	This product does not contain any known or suspected reproductive hazards.
Target Organ Effects	Blood. Eyes. Hematopoietic system. Kidney. Liver. Respiratory system. Skin. Central nervous system (CNS).

## **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

May cause long-term adverse effects in the aquatic environment.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms Daphnia Magna (Water Flea)
Naphtha (petroleum), heavy alkylate	EC50 72 h: = 30000 mg/L (Pseudokirchneriella subcapitata)		LC50 48 h: = 2 mg/L (Mysidopsis bahia)
Paraffinic, naphthenic solvent		LC50: 45 mg/L Pimephales promelas 96 h flow-through LC50: 2.2 mg/L Lepomis macrochirus 96 h static LC50: 2.4 mg/L Oncorhynchus mykiss 96 h static	LC50 96 h: = 4720 mg/L (Den-dronereides heteropoda)

#### **13. DISPOSAL CONSIDERATIONS**

#### Waste Disposal Methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements. Should not be released into the environment.

#### Contaminated Packaging Dispose of in accordance with local regulations.

#### California Hazardous Waste Codes 331

Chemical Name	California Hazardous Waste
Calcined kaolin clay	Toxic soluble
	Toxic

## **14. TRANSPORT INFORMATION**

DOT	Not regulated
TDG	Not regulated
MEX	Not regulated

Δ	n	N	

Not regulated

## **15. REGULATORY INFORMATION**

## International Inventories

TSCA EINECS ELINCS Complies Complies Complies

#### **15. REGULATORY INFORMATION**

#### Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

#### **U.S. Federal Regulations**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Calcined kaolin clay	66402-68-4	<10	1.0

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Calcined kaolin clay		Х		

#### CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

#### U.S. State Regulations

#### California Proposition 65

This product does not contain any Proposition 65 chemicals.

#### U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Paraffin	X	X	Х	-	Х
Turpentine	Х	Х			Х
Calcined kaolin clay			Х		Х

#### **International Regulations**

#### Mexico - Grade

Slight risk, Grade 1

Chemical Name	Carcinogen Status	Exposure Limits
Paraffin		Mexico: TWA= 2 mg/m <sup>3</sup>
		Mexico: STEL= 6 mg/m <sup>3</sup>
Turpentine		Mexico: TWA 100 ppm
		Mexico: TWA 560 mg/m <sup>3</sup>
Calcined kaolin clay		Mexico: TWA 5 mg/m <sup>3</sup>
		Mexico: TWA 0.2 mg/m <sup>3</sup>
		Mexico: STEL 10 mg/m <sup>3</sup>

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class D2B Toxic materials



#### **16. OTHER INFORMATION**

Prepared By	Product Stewardship 23 British American Blvd. Latham, NY 12110 1-800-572-6501	
Issuing Date	04-Apr-2007	
Revision Date	25-Oct-2011	
Revision Note	Name change.	

**General Disclaimer** 

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet