SAFETY DATA SHEET

1. Identification

Product identifier Pool Brite Other means of identification None.

Cement is used as a binder in concrete and mortars that are widely used in construction. Recommended use

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Suppliier

Southern Grouts and Mortars, Inc. Company name

1502 SW 2nd Place **Address**

Pompano Beach, Florida 33069

Telephone number (954) 943-2288 Fax (954) 943-2402 **Contact name Technical Manager** WWW.SGM.CC Website **Emergency telephone** (954) 943-2288

number

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

> Serious eye damage/eye irritation Category 1 Sensitization, skin Category 1 Carcinogenicity Category 1A

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, repeated Category 2 (Lung)

exposure

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Causes skin irritation. Causes serious eve damage. May cause an allergic skin reaction. May

cause cancer. May cause respiratory irritation. May cause damage to organs (Lung) through

prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

> and understood. Do not breathe dust. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after

handling. Contaminated work clothing must not be allowed out of the workplace.

Response If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. **Storage**

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

SDS US Pool Brite 1/8 Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

Product becomes alkaline when exposed to moisture.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Calcium Carbonate	471-34-1	30-60
Portland Cement	65997-15-1	15-60
29H,31H-Phthalocyaninato(2-)- N29,N30,N31,N32 copper	147-14-8	0.01-6.5
Pigment Blue 29	57455-37-5	0.01-6.5

Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation

Inhalation of wet product not foreseeable route of exposure. If dust from the material is inhaled, remove the affected person immediately to fresh air. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids wide apart. Continue rinsing. Get medical attention immediately.

Ingestion

Never give anything by mouth to a victim who is unconscious or is having convulsions. DO NOT INDUCE VOMITING. Rinse mouth thoroughly with water and give large amounts of water, if person

is conscious. Get medical attention.

Most important

symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Use fire-extinguishing media

appropriate for surrounding fire.

Unsuitable extinguishing

media

Water jet.

Specific hazards arising from

the chemical

During fire, hazardous combustion products are released that may include: Carbon oxides (COx). Silicon oxides. Metal oxides.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Move containers from fire area if you can do so without risk.

equipment/instructions
Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Avoid formation of dust. Avoid contact with skin and eyes. Ensure adequate ventilation. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust from the spilled material. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Pool Brite
933570 Version #: 01 Revision date: - Issue date: 30 January.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. If sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. For a dry material spill, use a HEPA (high efficiency particle air) vacuum to collect material and place in a sealable container for disposal. Avoid dust formation. For a wet spill, absorb or cover with dry earth, sand or other non-combustible material and transfer to containers for disposal. Neutralize the spill area. Use materials that can withstand the potentially corrosive nature of this product. Do not get water inside containers. Following product recovery, flush area with water. Use materials that can withstand the potentially corrosive nature of this product. Do not get water inside containers.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Prevent entry into drains.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get this material in contact with eyes. Avoid contact with skin and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Observe good industrial hygiene practices. Practice good housekeeping.

Conditions for safe storage. including any incompatibilities

Store locked up. Protect from moisture. Store in original tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US OSHA Table 7.4 Limits for Air Conteminants (20 CER 1010 1000)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)					
Components	Туре	Value	Form		
Portland Cement (CAS	PEL	5 mg/m3	Respirable fraction.		
65997-15-1)		15 mg/m3	Total dust.		
Calcium Carbonate		15 mg/m3			
US. OSHA Table Z-3 (29 CFR 1910	.1000)				
Components	Туре	Value	Form		
Portland Cement (CAS	TWA	50 mppcf			
65997-15-1)					
ACGIH					
Components	Туре	Value	Form		
Pigment Blue 29 (CAS	TWA	3 mg/m3	RESPIRABLE		
57455-37-5)		10 mg/m3	PARTICLES INHALABLE PARTICLES		
US. ACGIH Threshold Limit Values	S	. o mg/me	WWW.CABELTYWWW.GEE		
Components	Туре	Value	Form		
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.		
Calcium Carbonate		10 mg/m3			
US. NIOSH: Pocket Guide to Chen	nical Hazards				
Components	Туре	Value	Form		
29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32	TWA	1 mg/m3	Dust and mist.		
copper (CAS 147-14-8)	T10/0	F	Deeninable		
Portland Cement (CAS 65997-15-1)	TWA	5 mg/m3 10 mg/m3	Respirable. Total		

Biological limit values

Exposure guidelines

No biological exposure limits noted for the ingredient(s).

Occupational exposure to nuisance dust (total and respirable) and respirable

crystalline silica should be monitored and controlled.

SDS US Pool Brite 3/8

Appropriate engineering controls

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Ventilation should be sufficient to effectively remove and prevent buildup of any dusts or fumes that may be generated during handling or thermal processing. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection

In situations where there is potential splash or puff exposure of cement products, wear unvented goggles or a faceshield. In extremely dusty or unpredictable environments wear unvented or indirectly vented goggles or a faceshield. Contact lenses should not be worn when working with cement or cement products.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Prevention is essential to avoiding potentially severe skin injury. Avoid contact with unhardened

wet Portland cement products. If contact occurs, promptly wash affected area with soap and water. Where prolonged exposure to unhardened Portland cement products might occur, wear

impervious clothing and gloves to prevent skin contact. Wear sturdy boots that are impervious to water and eliminate foot and ankle exposure. Do not rely on barrier crèmes; barrier crèmes should

not be used in place of gloves.

Avoid tasks which cause dust to become airborne. Use local or general ventilation to control Respiratory protection

exposure below applicable exposure limits. Use NIOSH/MSHA approved (30 CFR 11) or NIOSH approved (42 CFR 84) respirators in poorly ventilated areas, or if an applicable exposure limit is

exceeded, or when dust causes discomfort or irritation.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Periodically wash affected areas contacted by dry or wet cement products with a pH neutral soap. When using, do not eat, drink, or smoke. Wash again at the end of work. If clothing becomes saturated with wet cement products, it should be removed and replace with clean dry clothing.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Coarse Textured Powder.

Color Whitish gray.

Odor None.

Odor threshold Not available. Not available. Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

Not available. Flash point Not available. **Evaporation rate** Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Not available. Vapor pressure Vapor density Not available.

2.5 Relative density

Solubility(ies)

Solubility (water) Miscible.

SDS US Pool Brite 4/8 Partition coefficient (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Explosive properties Not explosive. Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity Material is stable under normal temperatures and pressures. The product reacts with water and will

generate heat.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials. Moisture. Incompatible materials Powerful oxidizers, Chlorine, Mineral acid, Water, No hazardous decomposition products are known. Hazardous decomposition

products

11. Toxicological information

Information on likely routes of exposure

Dust may irritate respiratory system. Contact with moist mucous membranes of the respiratory Inhalation

system can cause a caustic condition resulting in burns. May cause damage to organs through

prolonged or repeated exposure by inhalation.

Skin contact Causes skin irritation. May cause an allergic skin reaction. Prolonged contact with wet

cement/mixture may cause burns.

Causes serious eye damage. Eye contact

May cause discomfort if swallowed. Irritating. May cause nausea, stomach pain and vomiting. Ingestion

However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Discomfort in the chest. Shortness of breath. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged

exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity May cause respiratory irritation. May cause an allergic skin reaction.

Components **Species Test Results**

29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper (CAS 147-14-8)

Acute Dermal

LD50 Rat > 5000 mg/kg, 24 hours

Oral

Rat 15000 mg/kg

Pigment Blue 29 (CAS 57455-37-5)

Acute Dermal

LD50 Rabbit > 3000 mg/kg

Oral

LD50 Rat > 2000 mg/kg

Skin corrosion/irritation Causes skin irritation.

Causes serious eye damage. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

SDS US Pool Brite 5/8 Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer by inhalation. This product has the potential for generation of respirable dust

during handling and use. Dust may contain respirable crystalline silica. Crystalline silica (inhaled in the form of cristobalite or quartz) has been classified by IARC, NTP and ACGIH as a known human carcinogen and suspected human carcinogen respectively. Overexposure to dust may result in pneumocononiosis, a respiratory disease caused by inhalation of mineral dust, which can lead to fibrotic changes to the lung tissue, or silicosis, a respiratory disease caused by inhalation of silica dust, which can lead to inflammation and fibrosis of the lung tissue. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

May cause delayed lung injury.

IARC Monographs. Overall Evaluation of Carcinogenicity

NTP Report on Carcinogens

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (Lung) through prolonged or repeated exposure.

Not an aspiration hazard. Aspiration hazard

Chronic effects Prolonged inhalation may be harmful. Inhalation can cause inflammation of interior of the nose,

throat, respiratory tract and symptoms of headache and nausea. Excess dust beyond appropriate

exposure limits can cause lung disease/cancer.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this product.

No data available. Bioaccumulative potential No data available. Mobility in soil Other adverse effects None known

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

SDS US Pool Brite 6/8

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper LISTED

(CAS 147-14-8)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Portland Cement (CAS 65997-15-1)

Quartz (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

29H,31H-Phthalocyaninato(2-)-N29,N30,N31,N32 copper (CAS 147-14-8)

Portland Cement (CAS 65997-15-1)

Quartz (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Portland Cement (CAS 65997-15-1)

Quartz (CAS 14808-60-7)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Quartz (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No

Pool Brite SDS US

On inventory (yes/no)* Country(s) or region Inventory name

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL) Yes

New Zealand New Zealand Inventory Yes **Philippines** Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 23-May-2016

Revision date Version # 01

HMIS® ratings Health: 3*

Flammability: 0 Physical hazard: 0

NFPA ratings



Disclaimer

Southern Grouts and Mortars cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

SDS US Pool Brite 8/8