

## Conductivity Sensor For High Temperature

**Designed for Pure, Boiler Feed water,  
Power Plant, Condensate Water.**



Measuring specific conductivity of aqueous solutions is becoming increasingly important for determining impurities in water. The measurement accuracy is greatly affected by temperature variation, polarization of the contact electrode surface, cable capacitance, etc. Twinno has designed a variety of sophisticated sensors and meters that can handle these measurements even in extreme conditions.

Suitable for low conductivity applications in the semiconductor, power, water and pharmaceutical industries, these sensors are compact and easy to use. The meter can be installed in several ways, one of which is through the compression gland, which is a simple and effective method of direct insertion into the process pipeline.

The sensor is made from a combination of FDA-approved fluid receiving materials. This makes them ideal for monitoring pure water systems for the preparation of injectable solutions and similar applications. In this application, the sanitary crimping method is used for installation.

<b>Model No.</b>	AS2030EHT
<b>Cell constant</b>	K=0.4
<b>Electrode type</b>	2-electrode Conductivity sensor
<b>Measure material</b>	SS316L
<b>Waterproof rating</b>	IP68
<b>Measurement range</b>	0.1-1000us/cm
<b>Accuracy</b>	±1%F.S
<b>Pressure resistance</b>	≤1.0Mpa
<b>Temperature compensation</b>	NTC10K
<b>Temperature range</b>	-10-130°C
<b>Measuring/Storage Temperature</b>	0-45°C
<b>Calibration</b>	Sample calibration, standard liquid calibration
<b>Connection methods</b>	4 core cable
<b>Cable length</b>	Standard 5m cable, can be extended to 100m
<b>Installation thread</b>	NPT3/4"
<b>Application</b>	Pure, Boiler Feed water, Power Plant, Condensate Water.



**CONNECT+**  
IoT Solution Enabled

**Labtech Electronics Private Limited**  
1/3, Kundrathur High Road, Periyapanicheri  
Chennai-600128, TamilNadu, India  
sales@labtech.co.in, www.labtech.co.in  
+91 9840839875, 044-48605048

