

# AimSAFETY™

PORTABLE GAS DETECTION SOLUTIONS  
by Macurco

AimSafety by Macurco blends 50 years of gas detection innovation and development into new, advanced gas monitor solutions that help organizations protect workers and the community, and increase safety, compliance and revenue.



PM100-CO



PM100-H<sub>2</sub>S



PM100-O<sub>2</sub>

## PM100 Series

### Newest, Advanced Disposable Single Gas, Personal Monitor for CO, H<sub>2</sub>S, O<sub>2</sub>, NH<sub>3</sub>, or SO<sub>2</sub>

The PM100 is a maintenance-free, disposable portable single-gas monitor that protects workers by providing exposure detection for specific gases in hazardous environments. The PM100 continuously monitors ambient air conditions and provides real-time gas concentrations on an easy to read LCD display. A three-tier alarm system warns the user of the presence of unsafe gas levels with audible, visual, and vibrating alarms. The PM100 has sensor options for Carbon Monoxide (CO), Hydrogen Sulfide (H<sub>2</sub>S), Oxygen (O<sub>2</sub>), Ammonia (NH<sub>3</sub>) and Sulfur Dioxide (SO<sub>2</sub>).

#### Key Features


- Visible calibration status
- Maintenance-free
- Operates continuously for two years
- Single button operation
- Event logging
- Rugged, high visual housing
- Easy-to-read LCD display
- IP67 dust tight & water resistant
- 30-day end-of-life warning & notification

#### Applications

- Oil & gas
- Heavy metal & steel
- Chemical plants
- Pulp & paper
- Municipalities
- Food & beverage
- Contractor / construction
- General industry

# PM100 Series

## Specifications

Size	3.34"(L) x 1.92"(W) x 1.56"(H) *with clip 8.48 cm x 4.87 cm x 3.96 cm
Weight	3.3 oz. (93 g.) Toxic models 3.8 oz. (107 g.) O <sub>2</sub> model (Battery, clip included)
Battery	Lithium (Non-replaceable)
Operating Period	Two years*
Event Logging	30 events (Alarms / bumps)
IP Rating	IP67
Display	LCD display
Alarms	<ul style="list-style-type: none"> <li>▪ Audible buzzer - 90 dB (at 4 in. typical)</li> <li>▪ Vibration alarm</li> <li>▪ Flashing red LEDs</li> <li>▪ On-screen indication</li> <li>▪ Differentiating audible &amp; visual high and low alarms indication</li> </ul>
Temperature	CO, H <sub>2</sub> S, NH <sub>3</sub> , SO <sub>2</sub> : -40°F to 122°F (-40°C to 50°C) O <sub>2</sub> : -31°F to 122°F (-35°C to 50°C)
Humidity	5% to 95% RH (Non-condensing)
Certifications	UL-913 & CSA-C22.2 No.157 Class 1 Div.1 & 2, Groups A,B,C & D. ATEX II 1G Ex ia IIC T4 Ga IECEx Ex ia IIC T4 INMETRO 
Warranty	Two year limited warranty
Sensor Life Notification	<ul style="list-style-type: none"> <li>▪ Sensor life indication screen (Month(s), days or hours)</li> <li>▪ &lt;30-Day end-of-life display warning (Days or hours)</li> </ul>
Policy Enforcement (Configurable)	<ul style="list-style-type: none"> <li>▪ End-of-life notification</li> <li>▪ Alarm test due</li> <li>▪ Bump test due</li> <li>▪ Calibration due</li> </ul>

\*Normal alarm use: Based on two minutes of alarm per day

## Gas Options

Gas	Range	Resolution
CO	0 - 500 ppm	1 ppm
H <sub>2</sub> S	0 - 100 ppm	0.1 ppm
O <sub>2</sub>	0 - 30% Vol	0.1% Vol
NH <sub>3</sub>	0 - 100 ppm	1 ppm
SO <sub>2</sub>	0 - 50 ppm	0.1 ppm

## Ordering Information

Gas	Model Number	Low Alarm	High Alarm
CO	PM100-CO	35 ppm	100 ppm
H <sub>2</sub> S	PM100-H <sub>2</sub> S	10 ppm	15 ppm
O <sub>2</sub>	PM100-O <sub>2</sub>	19.5%	23.5%
NH <sub>3</sub>	PM100-NH <sub>3</sub>	25 ppm	50 ppm
SO <sub>2</sub>	PM100-SO <sub>2</sub>	2 ppm	5 ppm

## Accessories

Name	Model Number
PM Link (PC Interface)	PM-Link
Bump/Cal Test Station	PM100-STN



Bump/Cal Test Station



PM Link