



SAFETY DATA SHEET

Part No.: SDR 4020 A

Date: March 15, 2019

PRODUCT NAME(S): StitchDog™ 4020 Adhesive (Part “A”)

SECTION 1 – IDENTIFICATION

Manufacturer’s Info:

Professional Construction Products, LLC
61 East 4800 South
Murray, UT 84107

Product name:
Chemical Name

StitchDog™ 4020 Adhesive (Part “A”)
Epoxy Resin Mixture

Information phone: (801) 707-1189

Emergency contact: CHEMTEL (813) 248-0585

SECTION 2 – HAZARD(S) IDENTIFICATION

OSHA Hazard Communication Standard:

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

GHS-Label Elements:

Signal Word:
WARNING

Pictogram(s):



GHS 07

Classification of the substance or mixture:

Hazard Class	Category	Hazard Statement Codes	Hazard Statements
Skin Corrosion / Irritation	2	H315	Causes skin irritation
Serious Eye Damage / Eye Irritation	2	H319	Causes serious eye irritation
Skin Sensitization	1	H317	May cause an allergic skin reaction
Specific Target Organ Toxicity–Single Exposure	3	H335	May cause respiratory irritation
Hazardous to Aquatic Environment–Chronic	4	H413	May cause long lasting harmful effects to aquatic life

Precautionary Statements:

Prevention:	P201 P202 P261 P264 P270 P271 P272 P273 P280	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash exposed area with plenty of water and soap thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Response:	P302+P352 P333+P313 P363 P304+P340 P312 P305+P351+P338 P337+P313	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Storage:	P403+P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal:	P501	Dispose of contents/container to hazardous or special waste collection point in accordance with local/regional/national/international regulations.

Hazards not otherwise classified:

None known.



SAFETY DATA SHEET

Part No.: SDR 4020 A

Date: March 15, 2019

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Components	CAS #	EC #	Concentration, %
Bisphenol A-Epoxy Resin	25068-38-6	500-033-5	60 – 70
Cashew nutshell liquid, oligomeric reaction products with epichlorohydrin	68413-24-1	500-210-7	10 – 15
Calcium Carbonate	471-34-1	207-439-9	1 – 10
Silicon Dioxide, chemically prepared	112945-52-5	601-216-3	1 – 10
Glass Fiber	65997-17-3	266-046-0	1 – 5

SECTION 4 – FIRST-AID MEASURES

Description of First Aid measures:

- Inhalation:** Move to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory problems, seek medical attention.
- Skin:** Wash material off of the skin with plenty of soap and water for at least 15 minutes. Remove contaminated clothing and shoes immediately and wash them before reuse. Get medical advice/attention if irritation occurs.
- Eye:** Rinse cautiously with water for several minutes, especially under the eyelids. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Do not rub eyes in order to prevent corneal injury. Get medical advice/attention if eye irritation persists.
- Ingestion:** Remove the exposed person to fresh air and keep at rest in a position comfortable for breathing. Remove dentures if any. Rinse mouth thoroughly with water and then give 60 to 240 mL (2 to 8 oz) of water to drink. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. Never induce vomiting or give anything by mouth if the person is unconscious or having convulsions.

Most important symptoms/effects, acute and delayed: See Section 11 for more details.

General advice for First Aid responders: No action should be taken involving any personal risk or without suitable training. If potential for exposure exist refer to Section 8 for specific personal protective equipment. Show this SDS to physician.

Note to physician: Specific antidotes or neutralizers do not exist. Treatment should be supportive and based on the judgment of the physician in response to the reaction of the patient. Recommended medical monitoring for at least 24hours.

SECTION 5 – FIRE-FIGHTING MEASURES

Suitable extinguishing media: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media: Do Data Available

Specific hazards arising from the chemical: This product is non-flammable and non-combustible. Containers at risk from fire should be cooled with water spray and, if possible, removed from the danger area. Hazardous combustion products: carbon, nitrogen and silica oxides, oxides of metals present in mixture (Section 3).

Special Protective Equipment and Precautions for fire-fighters: Wear NIOSH or OSHA approved self-contained breathing apparatus in positive pressure mode with full face piece and full protective gear. Isolate the scene by removing all persons from the incident area. No action should be taken involving any personal risk or without suitable training.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Keep unnecessary and unprotected personnel from entering. Ensure adequate ventilation/exhaust extraction. Use protective equipment as described in Section 8. Do not touch or walk through spilled material; spilled material may cause a slipping hazard.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. Inform the relevant authorities if the product has caused environmental pollution. See Section 12 for more details.

Methods and materials for containment and cleaning up: Remove mechanically; cover the remainder with non-combustible absorbent material (e.g. sand, earth, vermiculite or diatomaceous earth). Following absorption, transfer into properly labeled chemical waste containers. If necessary, repeat application of absorbent material until all liquid has been removed from the surface. Wash the spill site with soap and water. Cover container and remove from work to a well ventilated area. Properly dispose of the waste material and any contaminated equipment (i.e., broom or brush) in accordance with existing federal, state and local regulations. For major spills: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Wash spillages into an effluent treatment plant or contain and collect with an absorbent material as described in the previous paragraph. For minor spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly with soap and water to remove residual contamination.



SAFETY DATA SHEET

Part No.: SDR 4020 A

Date: March 15, 2019

Residues from spill cleanup may continue to be regulated under provisions of RCRA and require storage and disposal as hazardous waste. For major spills, see Section 1 for the Emergency contact; for further disposal measures, see Section 13.

SECTION 7 – HANDLING AND STORAGE

Precautions for safe handling: Do not breathe vapors and mists. Avoid contact with skin and eyes. Wear appropriate respiratory, eye and skin protection. Wash hands thoroughly after handling.

Conditions for safe storage, including any incompatibilities: Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10 for details), food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed. Protect from freezing. Keep out of the reach of children.

Storage stability: Stable under normal conditions.

Employee education and training in the safe use and handling of this product are required under the OSHA Hazard Communication Standard 29 CFR 1910.1200. Employees and consumers should be warned of health risks associated with product use. See Section 8 for additional information on hygiene measures.

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters/Occupational exposure limit values: Not available for mixture. Results for components listed below.

Occupational exposure limits (OEL):

Component	CAS-No.	Value	Control parameters	Basis
Epichlorohydrin	106-89-8	TWA	0.500000 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Upper Respiratory Tract irritation Male reproductive Confirmed animal carcinogen with unknown relevance to humans Danger of cutaneous absorption Potential Occupational Carcinogen		
		TWA	5.000000 ppm 19.000000 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		Skin designation The value in mg/m3 is approximate.		
		PEL	0.05 ppm 0.19 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		Skin		
Silicon Dioxide, chemically prepared	112945-52-5	TWA	20 millions of particles per cubic foot of air 0.8 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
	Remarks	The exposure limit is calculated from the equation, $80/(\%SiO_2)$, using a value of 100% SiO ₂ .		
Fiber Glass	65997-17-3	TWA	15 mg/m3 (Non-Respirable) 5 mg/m3 (Respirable)	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts

Appropriate engineering controls: Good local and general ventilation should be sufficient to control worker exposure to airborne contaminants below recommended exposure limits. Local exhaust may be required in some areas.

Personal protective equipment:

Eye/face protection:

When directly handling the product, eye protection is required. Examples of eye protection include safety glasses with side shields or chemical goggles. Contact lenses should not be worn when working with chemicals.

Skin/body protection:

Impervious, waterproof, abrasion and alkali-resistant gloves should be worn always when working with this product. Do not rely on barrier creams in place of impervious gloves. Do not get product inside gloves.

Body should be covered with appropriate clothing (apron, arm covers or full body suit) depending on the task being performed and the risks involved. Protective clothing should be selected and used in accordance with "Guidelines for the Selection of Chemical Protective Clothing" published by ACGIH. Remove clothing and protective equipment that becomes saturated with the product and immediately wash exposed areas of the body. Wash contaminated clothing before reuse. Store work clothing separately. Appropriate footwear should be also selected based on the task being performed and the risks involved.

Respiratory protection:

Use properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product, and assigned protection factor of the selected respirator.



SAFETY DATA SHEET

Part No.: SDR 4020 A

Date: March 15, 2019

Additional Protective Measures: Educate and train employees in safe handling of this product. Follow all label instructions. As a general hygiene practice, wash hands and face after use. Clean water should always be readily available for emergency skin and eye washing. Use administrative controls such as job rotation to supplement engineering controls. Emergency eyewash fountains and safety shower should be in close proximity as a matter of good practice.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Viscous liquid
Odor:	Slightly sweet
Odor threshold:	Not data available
pH:	No data available
Melting point/ freezing point:	Not available / 0°C
Initial boiling point and boiling range:	>200°C
Flash point:	>200°C
Evaporation rate:	No data available
Flammability (solid, gas):	No data available
Upper/ lower flammability or explosive limits:	No data available
Vapor pressure:	No data available
Vapor density:	No data available
Specific Gravity:	No data available
Solubility (water):	No data available
Partition coefficient n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
Viscosity:	No data available

SECTION 10 – STABILITY AND REACTIVITY

Reactivity: Product will not undergo hazardous polymerization. Based on its structural properties the product is not classified as oxidizing.

Chemical stability: Stable under recommended storage conditions.

Conditions to avoid: Do not freeze. To avoid thermal decomposition, do not overheat.

Incompatible materials: Strong oxidizing agents (strong acids and bases; halogenated compounds), metal alloys, caustics, oxidizers, and epoxy hardeners in an uncontrolled condition.

Hazardous decomposition products: Under normal conditions of storage and use, hazardous decomposition products should not be produced. In fire conditions, depending on temperature, air supply and presence of other materials, decomposition products can include, but are not limited to carbon, nitrogen and silica oxides, oxides of metals present in mixture (Section 3).

SECTION 11 – TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin and Eye Contact, Inhalation and Ingestion.

Symptoms of exposure:

Acute toxicity:

Oral:

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

Dermal:

Harmful in contact with skin. May cause an allergic skin reaction. Prolonged or repeated contact may cause skin irritation with local redness.

Inhalation:

Not classified.

Skin corrosion / irritation:

May cause skin irritation if not removed accordingly. Adverse symptoms may include irritation and redness.

Serious eye damage / eye irritation:

May cause eye irritation. Adverse symptoms may include tearing, redness and pain. Dispersed solid particles may cause abrasion of the cornea.

Specific target organ toxicity, single exposure:

Not classified. This product contains components that may cause respiratory irritation; however, since they are dispersed in a liquid as opposed to an inhalable fine powder form their effect is neutralized.

Aspiration hazard:

Not an aspiration hazard.



SAFETY DATA SHEET

Part No.: SDR 4020 A

Date: March 15, 2019

Chronic toxicity:

Respiratory and Skin Sensitizer:

This product does not contain components that are reported to be a respiratory sensitizer. Over exposure may be a skin sensitizer in some cases.

Germ cell mutagenicity:

Risk to humans is not expected from exposure to this product.

Carcinogenicity:

No data available.

Reproductive toxicity:

Risk to humans is not expected from exposure to this product.

Specific target organ toxicity, repeated exposure:

No data available on mix.

Medical conditions aggravated by overexposure:

In some cases this could result in skin sensitization.

Toxicity test results: Not available for mixture. Results for components, when available:

Components	Test Results
Bisphenol-A Epoxy Resin CAS #: 25068-38-6	<p><u>Acute Toxicity</u> Oral Toxicity: LD50 (Rat): >5,000 mg/kg Skin Toxicity: LD50 (Rabbit): 20,000 mg/kg Skin corrosion/irritation: (Rabbit): Causes slight skin irritation Serious eye damage/eye irritation: can cause serious eye irritation. Corneal injury is unlikely.</p> <p><u>Chronic Toxicity</u> Sensitization: (Guinea Pig): Causes allergic skin reactions. Germ cell mutagenicity: No evidence of mutagenic effects. Carcinogenicity: Not classified based on available data. Not listed by IARC, NTP, OSHA.</p>
Cashew nutshell liquid, oligomeric reaction products with epichlorohydrin CAS #: 68413-24-1	<p><u>Acute Toxicity</u> Oral Toxicity: LD50 (Rat): >1,000 mg/kg Skin Toxicity: No data available Inhalation: No data available Skin corrosion/irritation: (Rabbit): No irritating effect Serious eye damage/eye irritation: can cause serious eye irritation. Corneal injury is unlikely.</p> <p><u>Chronic Toxicity</u> Sensitization: (Guinea Pig): Causes allergic skin reactions. Germ cell mutagenicity: Not classified based on available data. Carcinogenicity: Not classified based on available data. Not listed by IARC, NTP, OSHA. Reproductive: Not classified based on available data. STOT-RE: Not classified based on available data.</p>
Calcium Carbonate CAS # 471-34-1	No data available on the product itself.
Silicon Dioxide, chemically prepared CAS # 112945-52-5	<p><u>Acute Toxicity</u> Oral LD50 (Rat): >5,000 mg/kg;(OECD Test Guideline 401) Inhalation LC50 (Rat): 0/139 mg/l / 4 h (maximum concentration attainable in experiments) Skin corrosion/irritation LD50 (Rabbit): >5,000 mg/kg / Not irritating (literature value) Serious eye damage/eye irritation (Rabbit): Not irritating (literature value)</p> <p><u>Chronic Toxicity</u> Sensitization: Not known Germ cell mutagenicity: No evidence of mutagenic effects. Carcinogenicity: Contains no carcinogenic substances as defined by NTP, IARC and /or OSHA.</p>
Glass Fiber CAS #: 65997-17-3	<p><u>Acute Toxicity</u> General Product Information: Dusts may cause mechanical irritation to eyes and skin. Ingestion may cause transient irritation of throat, stomach and gastrointestinal tract. Inhalation may cause coughing, nose and throat irritation, and sneezing. People with pre-existing respiratory conditions, may experience difficulty breathing, congestion and chest tightness.</p> <p><u>Chronic Toxicity</u> Carcinogenicity: ACGIH: A4 – Not classifiable as a human carcinogen. IARC: Group 3 “not classifiable as to its carcinogenicity to humans” The International Agency for Research on Cancer (IARC) in June 1987, categorized fiberglass continuous filament as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify fiberglass continuous filament as a possible, probable, or confirmed cancer causing material. This conclusion was confirmed by IARC in October 2001. The American Conference of Governmental Industrial Hygienists (ACGIH) A4 classification, not classifiable as a human carcinogen, for Respirable continuous filament glass fibers is based on inadequate data in terms of its carcinogenicity in humans and/or animals. For Respirable continuous filament glass fibers, a TLV-TWA of 1 fiber/cc was adopted to protect workers against mechanical irritation. The TLV-TWA of 5 mg/m3 was adopted for nonrespirable glass filament fiber, measured as inhalable dust, to prevent mechanical irritation of the upper respiratory tract. Note: There are no known chronic health effects connected with long term use or contact with these products. Products that are chopped, crushed or severely mechanically processed during manufacture or use may contain a very small amount of Respirable glass fiber-like fragments. Persistent Respirable glass fibers are suspected to cause cancer. NIOSH defines “Respirable fibers “ as greater than 5 microns in length and less than 3 microns in diameter with an aspect ratio of > 5:1(length-to-width ratio).</p>

The products in question have been evaluated against the Hazardous Products Regulations (WHMIS 2015) and no additional classifications, ingredient disclosure or exposure limits are required for those regulations.



SAFETY DATA SHEET

Part No.: SDR 4020 A

Date: March 15, 2019

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicity: Not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability: Not readily biodegradable by OECD criteria.

Bioaccumulative potential: Not known.

Mobility in soil: Not known.

Other adverse effects: Not known.

Ecotoxicity test results: Not available for the mixture. Results for components, where available:

Components	Test Results
Bisphenol-A Epoxy Resin CAS #: 25068-38-6	<u>Aquatic Toxicity</u> Fish LC50 (Fathead Minnow), 96h: 3.1 mg/L Acute toxicity to bacteria: EC50 (Daphnia Magna), 24h: 3.6 mg/L Acute toxicity to Algae/aquatic plants: No data available. <u>Ecological Data:</u> Biodegradation: 5%, 28d (OECD test Guideline 302B or equivalent), Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable. Bioaccumulation potential: Low (BCF = 31, Log Pow = 3 (low potential to bioaccumulate in aquatic organisms) Mobility in soil: No data available.
Cashew nutshell liquid, oligomeric reaction products with epichlorohydrin CAS #: 68413-24-1	No data available on the product itself.
Calcium Carbonate CAS # 471-34-1	No data available on the product itself.
Silicon Dioxide, chemically prepared CAS # 112945-52-5	<u>Aquatic Toxicity</u> Fish LC50 (Brachydanio rerio): >10,000 mg/l / 96 h (OECD 203) Acute toxicity to bacteria: EC50 (Daphnia Magna), 24h: 1,000 mg/L (OECD 202) Acute toxicity to Algae/aquatic plants: No data found <u>Ecological Data:</u> Biodegradation: Methods for determining biodegradability are not applicable to inorganic substances. Bioaccumulation potential: Not to be expected Mobility in soil: No remarkable mobility in soil is to be expected.
Glass Fiber CAS #: 65997-17-3	No data available for this product. This product is not anticipated to harm animals, plants or fish.

SECTION 13 – DISPOSAL CONSIDERATIONS

Product Disposal: The generation of waste should be avoided or minimized wherever possible. If product becomes a waste, it does not meet criteria of hazardous waste as defined in 40 CFR 261, Subpart C and D. Do not discharge into sewer system. Spill cleanup residues may still be subject to RCRA storage and disposal requirements. Dispose waste in compliance with local, state and federal regulations via licensed waste disposal contractor.

Container disposal: Even after emptying, container may retain residues. Containers should be completely emptied and safely stored until appropriately reconditioned or disposed through licensed contractor in accordance with government regulation. This material and its container must be disposed of in a safe way.

SECTION 14 – TRANSPORT INFORMATION

Land transport, U.S. DOT:

Non-Regulated

Sea transport, IMDG:

Hazard Class: 9
 Packaging group: III
 ID number: UN3082
 Hazard label:
 Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
 Environmental hazards: ---

Air transport, IATA/ICAO:

Hazard Class: 9
 Packaging group: III
 ID number: UN3082
 Hazard label: 9
 Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
 Environmental hazards: ---



SAFETY DATA SHEET

Part No.: SDR 4020 A

Date: March 15, 2019

SECTION 15 – REGULATORY INFORMATION

U.S. Regulations:

OSHA HCS: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29CFR 1910.1200.

TSCA Regulations:

All components of this product are listed or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

EPCRA Section 302 (40 CFR Part 355) (Emergency Response Planning, Extremely Hazardous Substance):

No components are subject to the reporting.

EPCRA Section 304 (40 CFR Part 355) (Emergency Release Notification Requirements):

No components are subject to the reporting.

EPCRA Sections 311 & 312 (Hazardous Chemical Inventory Reporting, Hazard Categories):

- Acute Health Hazard

EPCRA Section 313 (40 CFR Part 372) (Toxic Chemical Release Inventory Reporting):

No components are subject to the reporting.

CERCLA Sections 102-103 (40 CFR Part 302) (Hazardous Substances Release Notification):

No components are subject to the reporting.

Clean Air Act:

- Ozone Depleting Substances (ODS): This product does not contain and is not manufactured with ozone depleting substances.
- Hazardous Air Pollutants, OSHA, Section 112(b), Table Z-1 and Table Z-3: See Section 8.

Clean Water Act:

- Section 307(a) (Toxic pollutants): No components are listed.
- Section 311(b)(2): Table 116.4A (Hazardous chemicals) / Table 117.3 (RQ): No components are listed.

NFPA rating: Health: 2 Fire: 1 Reactivity: 0 Special: 0

HMIS rating: Health: 2 Flammability: 1 Physical hazard: 0

Rating: 0 – Minimal | 1 – Slight | 2 – Moderate | 3 – Serious – 4 – Severe

State Regulations:

California Prop. 65 Components:



WARNING: This product can expose you to chemicals including Epichlorohydrin, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov



WARNING: This product can expose you to chemicals including Epichlorohydrin, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

Massachusetts, New Jersey or Pennsylvania Right to Know Substance Lists:

- Epichlorohydrin – CAS# 106-89-8

Instruction: for regulatory information on components of this mixture, check the appropriate state websites.

Canada regulations/legislation:

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

International Regulations/Inventories:

No data available.



SECTION 16 – OTHER INFORMATION

LEGEND

GHS	Globally Harmonized System
CAS	Chemical Abstracts Services
EC	European Community
EPA	Environmental Protection Agency
OSHA	Occupational Safety and Health Administration
ACGIH	American Conference of Governmental Industrial Hygienists
NIOSH	National Institute of Occupational Safety and Health
PEL	Permissible Exposure Limits
TLV	Threshold Limit Value
REL	Recommended Exposure Limit
TWA	Time-Weighted Average
STEL	Short-term exposure limit
HEPA	High Efficiency Particulate Air
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
STOT, SE	Specific Target Organ Toxicity following Single Exposure
STOT, RE	Specific Target Organ Toxicity following Repeated Exposure
DOT	Department of Transportation
IMDG	International maritime dangerous goods code
IATA, ICAO	International Air Transport Association, International Civil Aviation Organization
TSCA	Toxic Substances Control Act
EPCRA	Emergency Planning and Community Right-to-Know Act
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act
CFR	Code of Federal Regulations
RQ	Reportable Quantity
DSL	Domestic Substance List
WHMIS	Workplace Hazardous Materials Information System

Latest revision date: March 15, 2019 – New Format, Section 14

Date of the previous revision: March 20, 2015

Disclaimer: The data set forth in this sheet are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. Professional Construction Products, LLC makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof.