

8164W

# 1/2 HP AC CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

Simple access for reliable performance.



## KEY FEATURES

**STANDARD**  
Lifting Power

**WI-FI**  
Built In



myQ integrates with leading smart home platforms.  
Visit [myQ.com](http://myQ.com) to learn more.

## INCLUDED ACCESSORIES:

### DOOR CONTROL BUTTON

Controls the opener and the opener's lights.



883LMW

### 1-BUTTON REMOTE CONTROL

Operates a single opener.



891LM

## POWERFUL ADD-ONS:

### myQ HOME BRIDGE

Adds Apple® HomeKit™ compatibility and Siri® voice control to Wi-Fi-enabled openers. Installs easily in the garage within Wi-Fi range.\*\*



819LMB

### MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



374UT

## RELIABLE

**1/2 HP AC MOTOR** IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

**CHAIN DRIVE SYSTEM** FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

**WARRANTY** 4-YEAR MOTOR, 1-YEAR PARTS.

## SMART

**BUILT-IN WI-FI** FOR THE EASIEST WAY TO CONNECT THE GARAGE.

**myQ MOBILE APP** LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.

## SECURE

**SECURITY+ 2.0®** SENDS A NEW CODE WITH EVERY REMOTE CLICK.

**POSILOCK®** ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

**ALERT-2-CLOSE** SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ.

**THE PROTECTOR SYSTEM®** INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

Smartphone not included.

PRODUCT GUIDE 8164W  
1/2 HP AC CHAIN DRIVE WI-FI  
GARAGE DOOR OPENER

**LiftMaster®**

# MASTERFUL ENGINEERING.

1/2 HP AC CHAIN DRIVE WI-FI®  
GARAGE DOOR OPENER

## MOTOR

- 1/2 Horsepower AC
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

## POWER

- 120V AC
- 60 Hz Voltage
- 6A Current Rating
- UL® Listed
- 4' Power Cord (3-Prong)

## MECHANICS

- **Steel Chassis, T-Rail and Trolley**
- **Full Chain Drive Mechanism** (16:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **AC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)

5.75"



15"

10"

## DIMENSIONS

Rail Options	7'	8'	10'
Installed Length	124"	136"	160"
Max. Opening	7'6"	8'6"	10'6"

Headroom Clearance Required: 2"

7"

Per second for door to move upward

## SPEED

7"

Per second for door to move downward

# STANDARD SPECS.

## SECURITY

### SECURITY+ 2.0® RADIO CONTROLS

1-Button Remote Control (891LM)

Operating Range: ~200'

Operating Temperature: -30°F to 150°F  
Frequency:

- Remote Control Code Format: Security+2.0
- Garage Door Opener Code Format: Security+2.0
- Security+ 2.0 Anti-Burglary Coding

### SECURITY+ 2.0 ENCRYPTED CONTROLS

Door Control Button (883LMW)

- Program Remote Controls
- Turn Opener Lights On and Off
- Easy Wi-Fi Setup

## SMART

### myQ® RADIO

902-928 MHz  
50-Channel FHSS  
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers via smartphone or tablet.

### HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER\*)

\*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

## ELECTRICAL

### LIGHTING



- Max. 1 100-Watt Lightbulb
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

# SHIPPING.

SHIPPING WEIGHT (in lbs.)



HEAD



RAIL (7')

## CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Door Control Button (883LMW)
- 1-Button Remote Control (891LM)
- Garage Door Opener Head (8164W)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

# CONVENIENCE AND SAFETY.



- Alert-2-Close with Unattended Close Operation†
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Garage Door Opener Capacity of up to 12 Remote Controls, 1 Keyless Entry System and 16 myQ Devices

\*WARNING: to reduce the risk of injury to persons—ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.