

Model	Description	Blade Diameter (ft.)	Coverage (sq. ft.)	Recommended Hanging Height (ft. above floor)	Maximum CFM	Input Power	Horsepower	Speed	Hanging Weight (lbs.)	Typical Spacing (ft.)
AIRSTAR	Ideal in applications with ceilings less than 20' high.	6	600	<20	16,186	100-120V	0.167	Variable Speed	85	25
		8	1024	<20	35,242	100-120V	0.167	Variable Speed	90	32
		10	1600	<20	40,040	100-120V	0.167	Variable Speed	100	40
		12	2,300	<20	45,300	100-120V	0.167	Variable Speed	110	48
AIRELITE	Sleek design with 1/2 horsepower for applications that need broad air distribution.	8	3,600	<30	48,200	120-240V, 1P, 3P	0.5	Variable Speed	111	50
		10	4,500	<30	62,300	120-240V, 1P, 3P	0.5	Variable Speed	118	55
		12	6,500	<30	79,300	120-240V, 1P, 3P	0.5	Variable Speed	125	60
		14	8,400	<30	111,180	120-240V, 1P, 3P	0.5	Variable Speed	132	65
		16	9,500	<30	124,600	120-240V, 1P, 3P	0.5	Variable Speed	139	75
		18	12,000	<30	158,590	120-240V, 1P, 3P	0.5	Variable Speed	146	80
		20	14,000	<30	173,436	120-240V, 1P, 3P	0.5	Variable Speed	153	85
AIRVOLUTION	Perfect for large spaces such as large service shops and car dealerships with 20'+ ceilings and need high CFM.	8	3,600	<50	53,623	120-480V, 1P, 3P	1	Variable Speed	160	50
		10	6,000	<50	83,082	120-480V, 1P, 3P	1	Variable Speed	181	60
		12	8,000	<50	97,695	120-480V, 1P, 3P	1	Variable Speed	190	65
		14	10,000	<50	128,010	120-480V, 1P, 3P	1	Variable Speed	194	70
		16	12,000	<50	158,911	120-480V, 1P, 3P	1	Variable Speed	208	85
		18	14,000	<50	179,015	120-480V, 1P, 3P	1	Variable Speed	222	90
		20	16,000	<50	201,805	120-480V, 1P, 3P	1	Variable Speed	232	95
AIRSPAN	Ideal for spaces over 10,000 sq. ft.	20	18,000	up to 100	237,231	120-480V, 1P, 3P	1.5	Variable Speed	217	100
		24	20,000	up to 100	376,804	208-480V, 1P, 3P	2	Variable Speed	236	110
AIRECO	Portable, powerful and efficient. Can be mounted on a pole, stand or to a wall, indoors or out.	6	100 x 20	< 30 when horizontal	26,432	120-480V, 1P, 3P	0.375	Single Speed	201	45