

STRONGEST, SAFEST, and MOST RELIABLE hoists in the world.



Product Number	Capacity (ton)	Capacity (lbs)	Chain (ft)
ADSCH-032-10	3.2	7,040	10
ADSCH-032-20	3.2	7,040	20
ADSCH-050-10	5	11,000	10
ADSCH-050-20	5	11,000	20
ADSCH-075-10	7.5	15,400	10
ADSCH-075-20	7.5	15,400	20
ADSCH-100-10	10	22,000	10
ADSCH-100-20	10	22,000	20
ADSCH-150-10	15	33,000	10
ADSCH-150-20	15	33,000	20
ADSCH-200-10	20	44,000	10
ADSCH-200-20	20	44,000	20

Custom Chain Lengths Available

ADSCH SERIES CHAIN HOIST SPECIFICATIONS & DIMENSIONS

Product Number		ADSCH-032	ADSCH-050	ADSCH-075	ADSCH-100	ADSCH-150	ADSCH-200	
Capacity		(ton)	3.2	5	7.5	10	15	20
No. of Falls			1	2	3	3	5	6
Capacity		(lbs)	7,040	11,000	15,400	22,000	33,000	44,000
Capacity Test Load		(lbs)	10,560	16,500	24,750	33,000	49,500	55,000
Capacity Test Load		(ton)	4.8	7.5	11.25	15	22.5	25
Load Chain Grade			100	100	100	100	100	100
Load Chain		(mm)	10x30					
Hand Chain		(mm)	5x25x18					
Standard Lift		(ft)	10	10	15	15	15	15
High Speed to Low		(lbs)	>121	>242	>363	>363	>606	>727
Low Speed to High		(lbs)	<55	<110	<165	<165	<275	<330
Pull to Rated Load		(N)	360	296	312	328	345	328x2
Weight		(lbs)	68.34	99.21	168.66	190.7	318.57	405.65
Height	h	(in)	18.31	23.62	29.13	29.92	39.37	45.28
Length	b	(in)	9.72	10.83	14.41	14.41	19.09	9.06
Width	a	(in)	9.72	9.72	9.72	9.72	10.83	25.79
Dimensions	a	(mm)	247	247	247	247	275	285
	b	(mm)	227	275	366	366	485	648
	c	(mm)	68.5	133	120	263	110	286
	d	(mm)	38.5	64	70	95	168	123
	e	(mm)	43	51	64	64	80	82
	f	(mm)	49.5	60	85	85	100	110
	g	(mm)	62	79				
	h	(mm)	465	600	740	760	1000	1150

5X FASTER

