

**STRONGEST, SAFEST, and MOST RELIABLE hoists in the world.**

**Backward & Forward lever**

placed in tandem providing a slim design and assuring power transfer along the center

**Built-in shearing pin**

prevent overload  
It functions at approx. 25% overload  
The pins can be replaced without removing the load

**Safety pin**

fastens the anchor bolt

**Spare shear pins**

Two pieces of spare shear pins located in the carrying handle

**Rope clamp system**

Easily disengaged with a lever allowing smooth installation of the wire rope

**High strength cast aluminium alloy body**

Light weight  
Simple to operate  
Smooth contour  
Design with large, flat bottom surface for increased stability in horizontal as well as vertical working position

**Anchor bolt**

Offers numerous and versatile connection possibilities with load hooks, sling ropes and sling chains

**Stamped serial number** for easy identification



GRIP PULLER

**HAND HOIST SPECIFICATIONS**

Product Number		AGP-008	AGP-016	AGP-032	AGP-054
Lifting Capacity (Rated Load)	(tonnes)	0.8	1.6	3.2	5.4
*Pulling Capacity	(tonnes)	1.2	2.4	4	8.1
Lever Pull at Rated Load	(N)	284	412	441	850
Forward Travel	(mm)	52	55	28	25
Wire Rope Diameter	(mm)	8.3	11	16	20
Net Weight (Body)	(kg)	6.4	12.4	23.3	58
Net Weight (20 meter Wire Rope)	(kg)	7	11.5	23.5	36
Net Weight (Lever Handle)	(kg)	1.15	2.5	2.5	3.7
Dimensions (Body) L x W x H	(mm)	440 x 70 x 255	560 x 100 x 295	675 x 120 x 350	940 x 170 x 440

**Every ALR Hoist meets or exceeds OSHA and ANSI / ASME HST-3 Standards**

