

CG GILSONITE

PRODUCT DATA

CG GILSONITE is a naturally occurring, hard, thermoplastic hydrocarbon resin.

APPLICATION

CG Gilsonite is added to cement slurries to produce a light weight slurry for cementing weak formations and controlling circulation losses.

TYPICAL PROPERTIES

Softening Point (ASTM E28-51T)	330°-355°F (166°-180°C)
Ash	Less than 1.0%
Color (lump)	Black
Color (powder)	Brown
Penetration	0
Specific Gravity	1.04
Sulfur	0.3%

TYPICAL PARTICLE SIZE ANALYSIS

U.S. Sieve Size	% Retained Cumulative
4	0.5
10	8-12
60	70-90
150	90-95

Packaging is available in 50 lb palletized, and shrink-wrapped. Packaging is also available in 2,000 lb super sacks, palletized and banded or bulk trucks.

Recommendations given in this bulletin are based on tests believed to be reliable. However, the use of the information is beyond the control of Integrity Chemical Solutions Inc. and no guarantee, expressed or implied is made to the results obtained if not used in accordance with directions or established safe practice. The buyer must assume all responsibility, including injury or damage from the misuse of the product as such, or in combination with other materials. This bulletin is not to be taken as a license to operate under or recommendation to infringe any patent.

Revised: February 1, 2019