



Vacuum Tanker Odour Control Spray System

Simple & Efficient Odour Neutraliser

The Ecosorb Odour Neutralizer Model A2500 distributed by Air & Gas Industries is designed to eliminate odours while pumping from Grease Traps, Septic Tanks and other related job sites.



- **Fully enclosed system**
- **Easily adjustable flow rate**
- **Simple installation**
- **100% safe**
- **Environmentally friendly**
- **Completely eliminates odours**

Delivery Method:	Single HP Nozzle (Cone); 0.012"
Operating Pressure:	Low pressure liquid spray (60 psi)
Nozzle Mounting:	Mounted in-line in (3-4inch) vacuum exhaust pipe (supplied w/20ft tubing)
Nozzle Output:	1.7 L/hr. (40.8LPD, 0.0M)
	Output could vary by using a smaller or larger nozzle
Pump type:	(Aquatec) Diaphragm, Int. bypass, 3/8NPT, Viton/Santoprene wet parts
Switch	Manual on/off rocker switch (lighted to show activation)
Tank:	Uses standard 20 litre pails of Ecosorb
Operating Capacity:	10-12 hours
Run Time (Duty):	30 minutes normally, 1 hour maximum
Enclosure:	Hinged & lockable door
	45cm X 45 X 45 cube
	Steel w/textured black wrinkle powder coat
System Weight:	27kg (without liquid tank or optional mounting brackets)
Mounting:	3 types of standard bracket arms available separately
Orientation:	Driver's side & passenger side configurations available (<i>please specify when ordering</i>)

For more information on our services and products contact us:-



Ph: (07) 3271 5899 Fax: (07) 3271 5726
mail@airgas.com.au