



# Ceramic Pro 9H

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Date of issue: 9/6/2018 Revision date: 9/6/2018 Version: 1.00

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Ceramic Pro 9H

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Use of the substance/mixture : Industrial use  
Automotive Care Products.  
Surface treatment  
COATING SOLUTION

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer/Supplier

Ceramic Pro Car GmbH  
Bültenweg 42  
38106 Braunschweig - Germany  
T 0531/87897810 - F 0531/87897812  
[kontakt@ceramic-pro.de](mailto:kontakt@ceramic-pro.de) - [www.ceramicpro-car.de](http://www.ceramicpro-car.de)

##### Email competent person

sds@kft.de

#### 1.4. Emergency telephone number

Emergency number : National Health Service (NHS)  
24 hour national number consumer  
England and Scotland: 111  
Wales: 0845 46 47  
Northern Ireland: call your local General Practitioner  
  
Call 999 if there is a life-threatening incident.

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226  
Specific target organ toxicity — Single exposure, Category 3, Narcosis H336  
Full text of H statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause drowsiness or dizziness.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Warning

Hazardous ingredients :

n-butyl acetate; 2-methoxy-1-methylethyl acetate

Hazard statements (CLP) :

H226 - Flammable liquid and vapour.  
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.  
P261 - Avoid breathing gas, vapours, mist, spray.  
P271 - Use only outdoors or in a well-ventilated area.  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 - Call a POISON CENTER, a doctor if you feel unwell.  
P403+P235 - Store in a well-ventilated place. Keep cool.

# Ceramic Pro 9H

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
2-methoxy-1-methylethyl acetate	(CAS-No.) 108-65-6 (EC-No.) 203-603-9 (EC Index-No.) 607-195-00-7	>=25 - <50	Flam. Liq. 3, H226 STOT SE 3, H336
n-butyl acetate	(CAS-No.) 123-86-4 (EC-No.) 204-658-1 (EC Index-No.) 607-025-00-1	>=20 - <25	Flam. Liq. 3, H226 STOT SE 3, H336
ethanol substance with national workplace exposure limit(s) (GB)	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5	<= 0.54	Flam. Liq. 2, H225 Eye Irrit. 2, H319

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
ethanol	(CAS-No.) 64-17-5 (EC-No.) 200-578-6 (EC Index-No.) 603-002-00-5	( 50 =<C < 100) Eye Irrit. 2, H319

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: Explosive vapour/air mixtures may be formed.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Silicon oxide.

### 5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Do not allow run-off from fire fighting to enter drains or water courses. Disposal must be done according to official regulations.

# Ceramic Pro 9H

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing gas, vapours, mist, spray. Keep away from sources of ignition.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid sub-soil penetration. Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Cover spill with non combustible material, e.g.: sand/earth. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal.

Other information : Disposal must be done according to official regulations.

#### 6.4. Reference to other sections

Information for safe handling. See section 7. Concerning personal protective equipment to use, see section 8. For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing gas, vapours, mist, spray. Vapours may form flammable and explosive mixture with air.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Storage temperature : 10 - 30 °C

Heat and ignition sources : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Information about storage in one common storage facility : Keep away from food, drink and animal feeding stuffs.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

n-butyl acetate (123-86-4)		
EU	Local name	n-butyl acetate
EU	Notes	(Ongoing)
EU	Regulatory reference	SCOEL Recommendations
United Kingdom	Local name	Butyl acetate
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	724 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	150 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	966 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	200 ppm
United Kingdom	Regulatory reference	EH40. HSE

# Ceramic Pro 9H

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>		
EU	Local name	2-Methoxy-1-methylethylacetate
EU	IOELV TWA (mg/m <sup>3</sup> )	275 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	550 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
EU	Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC
United Kingdom	Local name	1-Methoxypropyl acetate
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	274 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	548 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
United Kingdom	Regulatory reference	EH40. HSE

<b>ethanol (64-17-5)</b>		
United Kingdom	Local name	Ethanol
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	1920 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	1000 ppm
United Kingdom	Regulatory reference	EH40. HSE

### 8.2. Exposure controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

#### Hand protection:

Chemically resistant protective gloves. Butyl rubber. EN 374. Choosing the proper glove is a decision that depends not only on the type of material, but also on other quality features, which differ for each manufacturer. Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Gloves must be replaced after each use and whenever signs of wear or perforation appear

#### Eye protection:

Use splash goggles when eye contact due to splashing is possible. EN 166

#### Skin and body protection:

Wear suitable protective clothing. EN 340. EN 13034

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. EN 143. Breathing apparatus with filter. Filter A (colour code: brown). . Breathing equipment is only to be used in order to handle the residual risk of short term jobs if all other risk minimizing measures have been carried out e.g. retention and/or local exhaust

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Do not eat, drink or smoke when using this product. Avoid contact with skin and eyes. Always wash hands after handling the product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

# Ceramic Pro 9H

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Colour	: yellowish.
Odour	: ammonia odour.
Odour threshold	: No data available
pH	: 6 - 8
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: Not applicable; Hydrolyses
Flash point	: 59 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1.02 - 1.04
Solubility	: Water: practically insoluble Reacts with water
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Explosive vapour/air mixtures may be formed.
Oxidising properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Flammable or explosive vapour/air mixtures may be formed.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal)	: Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation)	: Not classified (Based on available data, the classification criteria are not met)
Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: 6 - 8
Serious eye damage/irritation	: Not classified (Based on available data, the classification criteria are not met) pH: 6 - 8
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity	: Not classified (Based on available data, the classification criteria are not met)
Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)

# Ceramic Pro 9H

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)

### SECTION 12: Ecological information

#### 12.1. Toxicity

Acute aquatic toxicity	: Not classified (Based on available data, the classification criteria are not met)
Chronic aquatic toxicity	: Not classified (Based on available data, the classification criteria are not met)

#### 12.2. Persistence and degradability

<b>n-butyl acetate (123-86-4)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	83 % (28 d; (OECD 301D method))

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	90 - 99 % (28 d; (OECD 301F method))

<b>ethanol (64-17-5)</b>	
Persistence and degradability	Readily biodegradable.
Biodegradation	84 % (20 d)

#### 12.3. Bioaccumulative potential

<b>n-butyl acetate (123-86-4)</b>	
Log Pow	2.3 (25 °C; (OECD 117 method))
Bioaccumulative potential	Slightly bioaccumulative.

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
Log Pow	1.2 (20 °C; pH 6.8; (OECD 117 method))
Bioaccumulative potential	Bioaccumulation unlikely.

<b>ethanol (64-17-5)</b>	
Log Kow	-0.35 (24 °C)
Bioaccumulative potential	Bioaccumulation unlikely.

#### 12.4. Mobility in soil

<b>n-butyl acetate (123-86-4)</b>	
Surface tension	61.3 mN/m (1 g/L; 20 °C; (OECD 115 method))
Log Koc	1.268 - 1.844 (Quantitative structure-activity relationship (QSAR))
Ecology - soil	Product adsorbs little onto the soil.

<b>2-methoxy-1-methylethyl acetate (108-65-6)</b>	
Surface tension	29.4 mN/m (20 °C)

<b>ethanol (64-17-5)</b>	
Surface tension	22.31 mN/m (20 °C)

# Ceramic Pro 9H

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### 12.5. Results of PBT and vPvB assessment

Component	
n-butyl acetate (123-86-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
2-methoxy-1-methylethyl acetate (108-65-6)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
ethanol (64-17-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods

: Disposal must be done according to official regulations. European waste catalogue. Do not dispose of with domestic waste. Do not discharge into drains or the environment.

Additional information

: Flammable vapours may accumulate in the container.

HP Code






: HP3 - "Flammable:"

- flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C;
- flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air;
- flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction;
- flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa;
- water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities;
- other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste.

HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
1139	1139	1139	1139	1139
<b>14.2. UN proper shipping name</b>				
COATING SOLUTION	COATING SOLUTION	Coating solution	COATING SOLUTION	COATING SOLUTION
<b>Transport document description</b>				
UN 1139 COATING SOLUTION, 3, III, (D/E)	UN 1139 COATING SOLUTION, 3, III	UN 1139 Coating solution, 3, III	UN 1139 COATING SOLUTION, 3, III	UN 1139 COATING SOLUTION, 3, III
<b>14.3. Transport hazard class(es)</b>				
3	3	3	3	3
				
<b>14.4. Packing group</b>				
III	III	III	III	III

# Ceramic Pro 9H

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

### 14.5. Environmental hazards

Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Classification code (ADR) : F1  
Special provisions (ADR) : 640E  
Limited quantities (ADR) : 5I  
Excepted quantities (ADR) : E1  
Transport category (ADR) : 3  
Hazard identification number (Kemler No.) : 30  
Orange plates :



Tunnel restriction code (ADR) : D/E  
EAC code : •3YE

#### Transport by sea

Special provisions (IMDG) : 955  
Limited quantities (IMDG) : 5 L  
Excepted quantities (IMDG) : E1  
EmS-No. (Fire) : F-E  
EmS-No. (Spillage) : S-E

#### Air transport

PCA Excepted quantities (IATA) : E1  
PCA Limited quantities (IATA) : Y344  
PCA limited quantity max net quantity (IATA) : 10L  
PCA packing instructions (IATA) : 355  
PCA max net quantity (IATA) : 60L  
CAO max net quantity (IATA) : 220L  
Special provisions (IATA) : A3

#### Inland waterway transport

Classification code (ADN) : F1  
Limited quantities (ADN) : 5 L  
Excepted quantities (ADN) : E1

#### Rail transport

Classification code (RID) : F1  
Limited quantities (RID) : 5L  
Excepted quantities (RID) : E1  
Transport category (RID) : 3  
Hazard identification number (RID) : 30

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:



# Ceramic Pro 9H

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	2-methoxy-1-methylethyl acetate
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Ceramic Pro 9H - n-butyl acetate - 2-methoxy-1-methylethyl acetate - ethanol
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	ethanol
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	n-butyl acetate - 2-methoxy-1-methylethyl acetate - ethanol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Seveso III Part I (Categories of dangerous substances)	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
P5c FLAMMABLE LIQUIDS Flammable liquids, Categories 2 or 3 not covered by P5a and P5b	5000	50000

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development

# Ceramic Pro 9H

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative

Data sources : Information provided by the manufacturer. MSDS of the supplier. ECHA (European Chemicals Agency).

Department issuing data specification sheet: : KFT Chemieservice GmbH  
Im Leuschnerpark. 3 64347 Griesheim  
Postfach 1451 64345 Griesheim  
Germany

Phone: +49 6155-8981-400 Fax: +49 6155 8981-500  
Safety Data Sheet Service: +49 6155 8981-522

Contact person : Dr. Barbara Ridder

Full text of H- and EUH-statements:	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 3	H226	On basis of test data
STOT SE 3	H336	Calculation method

KFT SDS EU 00

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*