

MATERIAL SAFETY DATA SHEET (OSHA-20)  
IN CASE OF LEAK, SPILL, FIRE, EXPOSURE,  
OR ACCIDENT CALL CHEMTREC:  
UNITED STATES: 1-800-424-9300  
INTERNATIONAL: 202-483-7616 (collect)

Show Car Products LLC.  
53 Welcome Home Road  
Grant, AL 35747  
(256) 728-4925

#### Section I Product Identification

---

### E-612 Adhesive Remover

(Clear liquid with a hydrocarbon odor)

08/28/07

#### Section II Hazardous Ingredients

---

Chemical Name: NUMBER	%	PEL/OSHA	TLV-ACGIH	CAS
Mineral Spirits	90-94	250 ppm	250 ppm	64742-88-7

#### Section III Physical Data

---

Boiling Point: >360-510F	Specific Gravity: .850	Vapor Pressure: N/A	Volatiles: 100%
Vapor Density: 5.17 Sec.I	Solubility: 100% in water	Evaporation Rate: .93	Apper & Odor: See

#### Section IV Fire & Explosion Data

---

NFPA CODES: Health: 1 Flammability: 1 Reactivity: 0 Flash Point: 72F

Extinguishing Media: Regular Foam, Carbon Dioxide, or Dry Chemicals.

Hazardous Decomposition: May form toxic materials: Carbon dioxide and carbon monoxide, various hydrocarbons, etc.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode when fighting fires.

Unusual Fire & Explosion Hazards: Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames, and ignition sources at location distant from material handling point.

#### Section V Health Hazard Data

---

Permissible Exposure Level: See Section II under PEL/OSHA

#### Effects of Overexposure: (Acute & Chronic)

**Eyes:** Can cause severe irritation

**Skin:** Prolonged or repeated exposure can cause moderate irritation, defatting of the skin or dermatitis.

**Inhalation:** Excessive inhalation of vapors can cause nasal and respiratory irritation, central nervous system effects including dizziness, weakness, fatigue, nausea, headaches and possible unconsciousness, and even death.

**Ingestion:** Can cause gastro-intestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Carcinogenicity: NTP: No IARC: No OSHA: No

Signs and symptoms of exposure: See Health effects (Acute & Chronic)

Medical Conditions Aggravated by Exposure: Dermatitis

#### First Aid Procedures:

**Eyes:** Flush with large amounts of water, lifting upper and lower lids occasionally, get medical attention.

**Skin:** Thoroughly wash exposed area with soap and water. Remove contaminated clothing before reuse.

**Inhalation:** Remove individual to fresh air. If breathing is difficult, administer oxygen. Keep person warm, quiet and get medical aid.

**Ingestion:** DO NOT INDUCE VOMITING. Keep person warm, quiet and get medical attention. Aspiration of materials into the lungs due to vomiting can cause chemical pneumonitis, which can be fatal.

Primary routes of entry: Inhalation and skin contact

Continued on Back

### E-612 Adhesive Remover

#### Section VI Reactivity

---

**Incompatibility:** Avoid contact with strong oxidizing agents.

**Hazardous Decomposition:** See Section IV

**Hazardous Polymerization:** Will not Occur

**Stability:** Stable

#### **Section VII Spill or Leak Procedures**

---

**Steps to be taken in case material is Released or Spilled:** Absorb liquid on paper, vermiculite, floor absorbent or other absorbent material and transfer to proper waste disposal container. Large spill: Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, dike area of spill to prevent spreading, pump liquid. Follow all regulations.

**Waste disposal method:** Dispose of according to Local, State and Federal regulations for biodegradable detergents.

#### **Section VIII Protective Equipment to be Used**

---

**Respiratory Protection:** If workplace limits of product or any component exceed NIOSH/OSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit NIOSH/OSHA respirators, negative pressure type.

**Ventilation:** Provide sufficient mechanical ventilation to maintain exposure below TLV(s)

**Protective gloves:** Wear resistant gloves such as Nitrile Rubber.

**Eye Protection:** Chemical splash goggles in compliance with OSHA regulations are advised.

**Other protective equipment:** To prevent repeated or prolonged skin contact, wear impervious clothes and boots.

#### **Section IX Special Precautions and Other Comments**

---

**Other Controls:** Treat containers with all precautions that material should be treated as container retains tract quantities.

**Work Practices:** Watch all exposure limits to keep exposure below TLV(s) and PEL

**Hygienic Practices:** Chemical resistant gloves and goggles are recommended.

**Precautions to be taken in Storing and Handling:** KEEP OUT OF THE REACH OF CHILDREN. Follow all precautions given by MSDS.

#### **Disclaimer Of Liability**

---

The information contained herein is based on data considered to be accurate. However, the information is provided without any warranty, expressed or implied, regarding its correctness. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product.

End MSDS