

Aquaclear 100

clear finished-waterbased impregnator for porous stones

Product Data

Aquaclear 100 is clear water base impregnator specifically designed for porous stones.

To be use as a natural finished water & stain repellent for easy maintenance.

Aquaclear 100 does not change or turn yellowish on the treated surface. It's natural look and unique properties, allow true vapor transmission after curing. Aquaclear 100 is unaffected by ultra violet rays and does not create any film on the surface, and can be used for external and internal application.

Method of Application

- All areas must be fairly dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Use application with a soft brush / roller / sponge.
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- 1 thin application coat should be sufficient in most cases.
- Should a 2nd coat be required, apply before 1st coat cures.

Coverage Guide

1 litre / coat = 12m²approx

1 litre / coat = 10m²approx

1 litre / coat = 8m²approx

Type of Surfaces

Slates / Quartzite / Sandstone

Rough Limestone / Quarry & Terracotta Tiles

Flamed & Bush hammered Granite / Tumbled marble

Packing

Plastic Bottles in 1 litre, 4 litres and 25 litres

Specifications

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles prior to any treatment.

Applications of Aquaclear 100 must be applied in manner using either a roller / brush / sponge. Spread evenly in not more then 2-3m² in for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Aquaclear 100 be allowed without the consent of the product manufacturer or Specifier.

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.eurosealsealers.com

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Cover all metal components before application.

EUROSEAL SEALERS

www.eurosealsealers.com