

Proseal 1000

anti-efflorescence solvent base impregnator

Product Data

Proseal 1000 is a clear solvent based impregnator specially formulated with nano-tech silicones. Proseal 1000 has excellent vapor transmission ability and does not create any film barrier. Proseal 1000 has good alkaline resistances, water and oil and can be use on polished marble, granite, limestones, as well as homogeneous tiles and quartz stones. (man made).

Method of Application

- All areas must be fully dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Use application with a flat mop / sponge / non colored cotton cloth
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- Clean off excess Proseal 1000 before it dries.
- Always apply in thin application. Clean off excess or spillage with Stripper X 1100 immediately.
- Should a 2nd coat be required, apply after 1st coat has cured or at least 12 hour after.

Coverage Guide

1 litre / coat = 20m²

1 litre / coat = 25m²

Type of Surfaces

Polished granite / limestone

Polished marble / Tiles

Packing

Metal container in 1 litre, 5 litres and 20 litres

Specifications

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles and cement / grouts prior to any treatment.

Applications of Proseal 1000 must be applied in manner using either a roller / brush / sponge / non colored cotton cloth. Spread evenly in not more then 2-3m² for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Proseal 1000 be allowed without the consent of the product manufacturer or Specifier.

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.eurosealsealers.com.

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Use only in a well ventilated area and away from direct heat. Flammable product!

EUROSEAL SEALERS

www.eurosealsealers.com