

Aquapro 1010

 waterbased impregnator oil resistant impregnator
Product Data

Aquapro 1010 impregnator performs similarly to Proseal 1000 and Moistproof 1050. This is a special water based impregnator blended with nano - tech silicone with ultra fine resins for added resistances to oil and alkaline. Aquapro 1010 has deep penetrating properties similar to solvent based products but without any of the restrictions. Suitable for both polished or porous stone texture and for wall and floor applications. Aquapro 1010 is recommended for areas with high humidity or area prone to dampness. Aquapro 1010 has high vapor transmission and does not create any film on its surface. Recommended to all surface treatment especially limestones.

Method of Application

- All areas must be fairly dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Use application with a cotton flat mop / sponge / cloth.
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- Can be use for front and back application. Apply min 1 coat on the back and edge of stone before installation. Application on surface can be done after lippage grinding / polishing. Stones without polishing, all side can be applied before installation.
- 1 thin application coat should be sufficient in most cases.
- Clean off excess Aquapro 1010 before it is fully dried, with a clean cloth.
- Should a 2nd coat be required, apply within an hour before 1st coat cures.

Coverage Guide

1 litre / coat = 25m²
 1 litre / coat = 20m²
 1 litre / coat = 15m²
 1 litre / coat = 10m²

Type of Surfaces

Polished marble / granite
 Honed Limestone / marble/ Jura stone
 Flamed / Bush hammered Granite / Tumbled marble
 All sides (front & back) marble / limestone

Packing

Plastic Bottles in 1 litre, 4 litres and 25 litres

Specifications

All natural stones and grouts, must be thoroughly cleaned washed, dried and free from any loose particles and cement & grouts prior to any treatment.

Applications of Aquapro 1010 must be applied in manner using either a flat mop / sponge or cloth. Spread evenly in not more then 2-3m² in for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Aquapro 1010 be allowed without the consent of the product manufacturer or Specifier.

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.eurosealsealers.com.

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Cover all metal components before application

EUROSEAL SEALERS

www.eurosealsealers.com