

Moistproof 1050

moisture blocker solvent base impregnator**Product Data**

Moistproof 1050 is a clear solvent based penetrating impregnator designed for moisture prevention. Moistproof 1050 has excellent vapor transmission ability and does not create any film barrier. Has good alkaline resistances, water, oil and can be use on polished marble, granite, limestones, as well as dense homogeneous tiles and quartz stones. (man made). Recommended to be use as a full system for both front and back of marble before installation on site.

Method of Application

- All areas must be fully dry prior to application.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual application for surface sensitivity.
- Use application with a soft sponge / non colored cotton cloth / Flat mop.
- Apply evenly and only in THIN coats. Do not over apply with dripping or soaking wet!
- Always apply in thin application. Clean off excess or spillage with Stripper X 1100 immediately.
- Clean off excess Moistproof 1050 before it dries.
- Should a 2nd coat be required, apply after 1st coat has cured or at least 12 hour after.

Coverage Guide

1 litre / coat = 20m²
1 litre / coat = 25m²
1 litre / coat = 10m²

Type of Surfaces

Polished granite / limestone
Polished marble / tiles
All sides (front & back) marble / limestone

Specifications

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles and cement / grouts prior to any treatment.

Applications of Moistproof 1050 must be applied in manner using either a roller / brush / sponge / non colored cotton cloth. Spread evenly in not more then 2-3m² for each application and according to manufacture instructions and method. No dilution or mixture with other products which might cause the performance of Moistproof 1050 be allowed without the consent of the product manufacturer or Specifier.

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.eurosealsealers.com.

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Use only in a well ventilated area and away from direct heat. Flammable product!

EUROSEAL SEALERSwww.eurosealsealers.com