

**Poultice Powder 1111**

high absorption stain removing powder

**Product Data**

Poultice Powder 1111 is a high absorption stain removing powder and when mixed with Stripper X 1100 or Stone Poultice 1200 provides excellent results. Poultice Powder 1111 can also be used alone for removal of excessive moisture on any stone or tile surface. Poultice Powder 1111 is effective for wall application as well as floor. Its ultra fine powder does not contain any harmful chemical that may cause the stone surface to yellow.

**Method of Application**Oil / Ink / Paint – Use with Stripper X 1100

- Soak affected area with Stripper X and scrub off excessive stains.
- Mix Poultice Powder with Stripper X 1100 until a soft creamy consistency. Adjustment can be made to a slightly drier paste for wall and a more liquified paste for floor.
- Spread over affected area, with sufficient material similar to a toothpaste thickness.
- Cover with a plastic shrink-wrap
- Allow paste to dry out in a few hours.
- Sweep off the Poultice mix.
- Inspect surface and repeat application if necessary.
- Do not re-use powder.
- No rinsing is necessary after cleaning.

Wood stains, Tobacco, Coffee / Tea and most organic stains. Initial rust stains.

- Clean off area that has oil or grease stains with Afla 750 before application of Stone Poultice 1200.
- Mix Poultice Powder with Stone Poultice 1200 until a soft creamy consistency. Adjustment can be made to a slightly drier paste for wall and a more liquified paste for floor.
- Spread over affected area, with sufficient material similar to a toothpaste thickness.
- Cover with a plastic shrink-wrap
- Allow paste to dry out in a few hours.
- Sweep off the Poultice Powder mix.
- Inspect surface and repeat application if necessary.
- Do not re-use powder.
- Area can be cleaned with a damp cloth or rinse off with water after application.

**Coverage Guide**

1 litre of liquid : 2 kg powder

**Type of Surfaces**

All surfaces

**Packing**

1 kg Plastic bag

**Specifications**

All natural stones, ceramic tiles and grouts must be fully cured before cleaning process and free from any loose particles. Use Poultice Powder 1111 according to product's method of application and do not mix with any other non recommended products. All protection work must be done accordingly before any washing is to be carried out.

**Caution!**

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to [www.euroseal-sealers.com](http://www.euroseal-sealers.com).

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Cover all metal components before application

***EUROSEAL SEALERS***

[www.euroseal-sealers.com](http://www.euroseal-sealers.com)