stain remover for stones

Product Data

Stone poultice 1200 is recommended to be used on polished marble & granite to remove organic stains like coffee, tea, wood stains, urine stains, tobacco and sometime metallic stains in early stages. Stone Poultice 1200 penetrate deep into the stone's surface and draws up the stains through evaporation slowly. When mixed together with Poultice Powder 1111 the stains are lifted more effectively and faster.

Method of Application

- All areas must be free from oil or grease.
- Use directly from container / drum. No Dilution!
- Always test on a small area of the stone / tile away from the main area before actual • application for surface sensitivity.
- Use adequate protection like rubber gloves and proper eye protection, before usage
- Soak over area with cotton wool and cover up with shrink wrap plastic to prevent fast hydration (fast drying).
- Best to be used with Poultice Powder 1111. Mixed until a creamy paste form, slightly drier for wall application and wetter for floor. Cover with a non staining shrink-wrap plastic. Allow for up to 12 hours of reaction.
- Sweep off dried powder after removal of plastic
- Repeat until desire results.
- Rinsing after cleaning has completed

Coverage Guide 1 litre / coat = $5m^2$

Type of Surfaces Polished Stones 2 kg of Powder : 1 litre of liquid (approx)

Packing

Plastic container in 1 litre, 4 litres and 25 litres

Specifications

All natural stones, ceramic tiles, and grouts, must be thoroughly cleaned washed, dried and free from any loose particles and cement / grouts prior to any treatment.

Applications of Stone poultice 1200 must be used together with cotton wool and covered with a shrink-wrap plastic. Damp the cotton wool over the area for each application and allow soaking for up to 12 hours before rinsing with water as recommended according to manufacture instructions and method. No dilution, or mixture with other products which might cause the performance of Stone poultice 1200 be allowed without the consent of the product manufacturer or Specifier.

Caution!

There are many variables in stones & tiles and may react differently inclusive of different texture and finishes. Therefore a test application must be done on a sample piece before actual application. In case of unsure material or surfaces outside the norm, please check with a proper representative or email directly to www.eurosealsealers.com

Keep out of reach of children. Do not reuse container. Discard container in proper manner. Protect eye and skin from direct contact and use in a well ventilated area. Use only in a well ventilated area and away from direct heat. Flammable product!

> **EUROSEAL SEALERS** www.eurosealsealers.com